

EXHIBIT L

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

Exhibit G-10

Based on Headwater's apparent positions as to the scope of the patent's claims, as best they can be deciphered, the reference(s) charted below anticipate(s) or at least render(s) obvious the identified claims. The portions of the prior art system documents cited below are not exhaustive but are exemplary in nature. Additional citations may be found in the cover pleading.

This disclosure is not an admission that Samsung concedes any claim construction implied or suggested by Headwater's apparent positions as to the scope of the patent's claims, nor is it an admission by Samsung that any of its products are covered by or infringe the patent's claims, particularly when they are properly construed and applied. Samsung is not taking any claim construction positions through this disclosure, including whether the preamble is a limitation.

Samsung reserves the right to rely on additional citations or sources of evidence that also may be applicable, or that may become applicable in light of claim construction, changes in Headwater's infringement contentions, and/or information obtained during discovery as the case progresses. Samsung further reserves the right to amend or supplement this claim chart at a later date as more fully set forth in the Invalidity Contentions. For example, Defendants are currently in the process of taking discovery from non-parties including Nokia, HMD, Citrix, Google, Apple, and Microsoft. Accordingly, Defendants reserve the right to modify, amend, and/or supplement these contentions as information becomes available from non-parties.

Android is mobile device operating system that was initially released in September 2008. Applications (or "apps") can be installed on mobile devices that run Android. Any mobile device that predates the '433 patent, running an Android version with one or more apps that also predate the '433 patent, qualifies as prior art under at least pre-AIA 35 U.S.C. §§ 102(a)/(b). Such a device was known, used, offered for sale, and/or sold in the United States before the '433 patent.

Exemplary mobile devices that predate the '433 patent and were publicly available before the earliest possible priority date include:¹

- HTC Dream/T-Mobile G1 (released September 2008)
- Samsung GT-I7500 Galaxy (released June 2009)

¹ See, e.g., SAMSUNG_PRIORART0000001-334; SAMSUNG_PRIORART0005174-76; SAMSUNG_PRIORART0005177-317; SAMSUNG_PRIORART0005416-19; SAMSUNG_PRIORART0005420-23; SAMSUNG_PRIORART0005424-28; SAMSUNG_PRIORART0005429-44; SAMSUNG_PRIORART0005445-48; SAMSUNG_PRIORART0005449-52; SAMSUNG_PRIORART0005453-57; SAMSUNG_PRIORART0005458-71; SAMSUNG_PRIORART0005472-77; SAMSUNG_PRIORART0005478-84; SAMSUNG_PRIORART0005485-86; SAMSUNG_PRIORART0005488-5624.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

- Nexus One (released January 2010)

Exemplary Android versions that predate the '433 patent and were publicly available before the earliest possible priority date include:²

- Android 1.0 (released September 2008)
- Android 1.1 (released February 2009)
- Android Cupcake (1.5) (released April 2009)
- Android Donut (1.6) (released September 2009)
- Android Eclair (2.0, 2.0.1, 2.1) (released October 2009 - January 2010)
- Android Froyo (2.2) (released May 20, 2010)

Android included files³ such as ConnectivityManager, NetworkInfo, NetworkStateTracker, ThrottleManager, TrafficStats, ConnectivityManagerMobileTest, Socket, SocketTest, Power, PowerManager, PowerManagerTest, BatteryManager, and BatteryStats.

² See, e.g., SAMSUNG_PRIORART0003998; SAMSUNG_PRIORART0004085; SAMSUNG_PRIORART0004081; SAMSUNG_PRIORART0004086; SAMSUNG_PRIORART0004083; SAMSUNG_PRIORART0004084; GOOG-HEADWATER-000000001-123; HDWTR-GOOG00001-GOOG00013; SAMSUNG_PRIORART0005042; SAMSUNG_PRIORART0005062; SAMSUNG_PRIORART0005350; SAMSUNG_PRIORART0005351; SAMSUNG_PRIORART0005352; SAMSUNG_PRIORART0005353; SAMSUNG_PRIORART0005354; SAMSUNG_PRIORART0005355; SAMSUNG_PRIORART0005356; SAMSUNG_PRIORART0005357; SAMSUNG_PRIORART0005358; SAMSUNG_PRIORART0005359; SAMSUNG_PRIORART0005360; SAMSUNG_PRIORART0005361; SAMSUNG_PRIORART0005362; SAMSUNG_PRIORART0005363; SAMSUNG_PRIORART0005364; SAMSUNG_PRIORART0005046; SAMSUNG_PRIORART0005043; SAMSUNG_PRIORART0005044; SAMSUNG_PRIORART0005045; SAMSUNG_PRIORART0005054; SAMSUNG_PRIORART0005055; SAMSUNG_PRIORART0005056; SAMSUNG_PRIORART0005057; SAMSUNG_PRIORART0005058; SAMSUNG_PRIORART0005059; SAMSUNG_PRIORART0005060; SAMSUNG_PRIORART0005061; SAMSUNG_PRIORART0005318; SAMSUNG_PRIORART0005398; SAMSUNG_PRIORART0005047-53; SAMSUNG_PRIORART0005063-65; SAMSUNG_PRIORART0005066-74; SAMSUNG_PRIORART0005075-135; SAMSUNG_PRIORART0005136-52; SAMSUNG_PRIORART0005153-70; SAMSUNG_PRIORART0005171-73; SAMSUNG_PRIORART0005319-49; SAMSUNG_PRIORART0005365-74; SAMSUNG_PRIORART0005375-83; SAMSUNG_PRIORART0005384-94; SAMSUNG_PRIORART0005395-97; SAMSUNG_PRIORART0005487.

³ The files listed are Java source files, so the filenames are, e.g., ConnectivityManager.java, NetworkInfo.java, etc., except as noted.

Exhibit G-10 to Defendants’ Amended Invalidity Contentions
U.S. Patent No. 9,277,433

Exemplary apps that predate the ’433 patent and were publicly available before the earliest possible priority date include:⁴

- JuiceDefender (released January 2010) and its associated add-on application, UltimateJuice (collectively “JuiceDefender App”)
- GreenPower (released March 2010)

As specific examples, an HTC Dream/T-Mobile G1, Samsung GT-I7500 Galaxy, or a Nexus One mobile device running any of Android versions 1.0- 2.2 by itself, or with the JuiceDefender or GreenPower applications installed, qualifies as prior art under at least pre-AIA 35 U.S.C. §§ 102(a)/(b). This device was known, used, offered for sale, and/or sold in the United States on or before May 20, 2010. At least the various documents cited in this claim chart describe the functionality of this device.

To the extent it is argued that Android Device with One or More Apps does not disclose or include each and every asserted claim limitation, either expressly or inherently, it would have been obvious to a POSITA to incorporate any of the teachings from the references identified in Exhibits G-01 through G-11, and G-G (whose exemplary citations for each limitation are incorporated herein) into Android Device with One or More Apps. Indeed, it would have been obvious to make such combinations and a POSITA would have had reason and motivation to make such combinations at least for reasons described herein and in the cover pleading.

'433 Claims	Android Device with One or More Apps
[1 pre] A wireless end-user device, comprising:	<p>To the extent the preamble is a limitation, Android Device with One or More Apps discloses and/or renders obvious this element. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><u>Nexus One</u></p> <p>The Nexus One is an example of an Android smartphone.</p>

⁴ See, e.g., SAMSUNG_PRIORART0000335-SAMSUNG_PRIORART0000383; POUZERATE0000001-POUZERATE0000261.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g., SAMSUNG_PRIORART0000001 (Nexus) at 17:</i></p> <div data-bbox="961 391 1289 423"> <p>Getting to know your phone</p> </div>  <p><u>HTC Dream / T-Mobile G1</u></p> <p>The HTC Dream / T-Mobile G1 is an example of an Android smartphone.</p> <p>SAMSUNG_PRIORART0005184</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<div data-bbox="604 337 892 938"></div> <p data-bbox="674 971 821 1000">T-Mobile G1</p> <p data-bbox="556 1068 997 1101">SAMSUNG_PRIORART0005177</p> <p data-bbox="611 1162 1180 1263">Android™ mobile technology platform R1.0 Document Rev 08 - September 8, 2008 Copyright 2008 © Google, Inc. All rights reserved.</p> <p data-bbox="556 1328 928 1360"><u>Samsung GT-I7500 Galaxy</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>The Samsung GT-I7500 Galaxy is an example of an Android smartphone.</p> <p>SAMSUNG_PRIORART0005494 at pgs. PDF 2, 19:</p> <div data-bbox="550 506 1694 1183">  </div> <p><u>JuiceDefender App</u></p> <p>JuiceDefender is a mobile application (or “app”) intended to run on a mobile device, such an Android smartphone. The Nexus One is an example of an Android smartphone capable of running JuiceDefender.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>SAMSUNG_PRIORART0000379 (Latedroid) (“JuiceDefender saves battery power (lots of it!) by controlling the device data connection and/or WiFi ... You can schedule regular APN/WiFi activation to let background data sync occur and have APN/WiFi enabled while the screen is on. It also helps in minimizing distractions.”)</p> <p>SAMSUNG_PRIORART0000361 (Purdy) (“Android: Most phones don't make it easy to switch cellular data connection on and off, even if doing so really helps save your battery. JuiceDefender toggles wireless data and Wi-Fi on and off every so often to preserve power.”)</p> <p><u>GreenPower App</u></p> <p>GreenPower is a mobile application (or “app”) intended to run on a mobile device, such an Android smartphone. The Nexus One is an example of an Android smartphone capable of running GreenPower.</p> <p><i>See, e.g.</i>, POUZERATE0000015 (GDG Oslo) at 5:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<div><h2>Background</h2><ul style="list-style-type: none">History of GreenPower app<ul style="list-style-type: none">2010: My first HTC heroMarch 2010: First Free version publishedOctober 2010: First Paid version publishedJan 2013:<ul style="list-style-type: none">1.3M downloads Free (>2500/day)200.000 active users<div><p>23.01.2013 - GDG Oslo - 5/35</p></div><p><i>See, e.g.,</i> POUZERATE0000002 (App Circus) at 9:</p></div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>Be mainstream</p> <ul style="list-style-type: none"> ▶ Cross Android versions <ul style="list-style-type: none"> ◦ Froyo ◦ Gingerbread ◦ Honeycomb ◦ Ice cream sandwich (as soon as someone offers me a Galaxy Nexus) ▶ Cross technologies <ul style="list-style-type: none"> ◦ GSM ◦ CDMA ◦ 2G, 3G, LTE ▶ 18 languages (not everybody speaks English, I know, I'm French)  <p><i>See also</i> GOOG-HEADWATER-000000001-123.</p>
[1a] a wireless wide area network (WWAN) modem to communicate data for Internet service activities between the	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><u>Nexus One</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps				
device and at least one WWAN, when configured for and connected to the at least one WWAN, the at least one WWAN having a corresponding network type of a plurality of wireless network types supported by the device for data communication;	<p><i>See, e.g., SAMSUNG_PRIORART0000001 (Nexus) at 332:</i></p> <table border="1" data-bbox="699 355 1751 870"> <tr> <td data-bbox="699 355 1016 870">Cellular & wireless</td><td data-bbox="1016 355 1751 870"> <p>Nexus One GSM phones compatible with 3G mobile networks from AT&T (U.S.) and Rogers Wireless (Canada): 3G UMTS bands I/II/V: 2100, 1900, 850 MHz</p> <p>Nexus One GSM phones compatible with 3G mobile networks from T-Mobile (U.S.): 3G UMTS bands I/IV/VIII: 2100, 1700(AWS), 900 MHz</p> <p>All Nexus One GSM phones: HSDPA 7.2Mbps HSUPA 2Mbps GSM/EDGE 850, 900, 1800, 1900 MHz Wi-Fi 802.11b/g Bluetooth 2.1 + EDR A2DP stereo Bluetooth</p> </td></tr> </table> <p><u>HTC Dream / T-Mobile G1</u></p> <p>SAMSUNG_PRIORART0005202</p> <table data-bbox="583 1037 1680 1240"> <tr> <td data-bbox="583 1037 856 1240">Mobile network settings</td><td data-bbox="856 1037 1680 1240"> <ul style="list-style-type: none"> • Select data roaming capability. • Select to connect only to 2G (slower) networks to save battery power. • Select a wireless operator network - Scan for all available networks, or select a network automatically. • Add or edit network Access Point Names (APNs) - Do not change this setting unless advised to do so by your wireless operator! </td></tr> </table> <p>SAMSUNG_PRIORART0005200</p>	Cellular & wireless	<p>Nexus One GSM phones compatible with 3G mobile networks from AT&T (U.S.) and Rogers Wireless (Canada): 3G UMTS bands I/II/V: 2100, 1900, 850 MHz</p> <p>Nexus One GSM phones compatible with 3G mobile networks from T-Mobile (U.S.): 3G UMTS bands I/IV/VIII: 2100, 1700(AWS), 900 MHz</p> <p>All Nexus One GSM phones: HSDPA 7.2Mbps HSUPA 2Mbps GSM/EDGE 850, 900, 1800, 1900 MHz Wi-Fi 802.11b/g Bluetooth 2.1 + EDR A2DP stereo Bluetooth</p>	Mobile network settings	<ul style="list-style-type: none"> • Select data roaming capability. • Select to connect only to 2G (slower) networks to save battery power. • Select a wireless operator network - Scan for all available networks, or select a network automatically. • Add or edit network Access Point Names (APNs) - Do not change this setting unless advised to do so by your wireless operator!
Cellular & wireless	<p>Nexus One GSM phones compatible with 3G mobile networks from AT&T (U.S.) and Rogers Wireless (Canada): 3G UMTS bands I/II/V: 2100, 1900, 850 MHz</p> <p>Nexus One GSM phones compatible with 3G mobile networks from T-Mobile (U.S.): 3G UMTS bands I/IV/VIII: 2100, 1700(AWS), 900 MHz</p> <p>All Nexus One GSM phones: HSDPA 7.2Mbps HSUPA 2Mbps GSM/EDGE 850, 900, 1800, 1900 MHz Wi-Fi 802.11b/g Bluetooth 2.1 + EDR A2DP stereo Bluetooth</p>				
Mobile network settings	<ul style="list-style-type: none"> • Select data roaming capability. • Select to connect only to 2G (slower) networks to save battery power. • Select a wireless operator network - Scan for all available networks, or select a network automatically. • Add or edit network Access Point Names (APNs) - Do not change this setting unless advised to do so by your wireless operator! 				

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps																																				
	<div>Notification and connection status icons</div> <p>Along the top of your phone screen is the status bar. On the left side, icons will appear, notifying you of a new message, upcoming calendar event, alarm, or something else you should notice. On the right side of the status bar, you'll see connection status icons.</p> <table><tr><td> New email message</td><td> Call in progress</td><td> GSM signal, roaming, no signal</td></tr><tr><td> New SMS or MMS</td><td> Missed call</td><td> GPRS service connected, data flowing</td></tr><tr><td> Problem with SMS or MMS delivery</td><td> Call on hold</td><td> Edge service connected, data flowing</td></tr><tr><td> New instant message</td><td> Call forwarding is on</td><td> 3G service connected, data flowing</td></tr><tr><td> New voicemail</td><td> Speakerphone is on</td><td> Wi-Fi service connected, network available</td></tr><tr><td> Upcoming event</td><td> Ringer is off (Silent mode)</td><td> Battery charge indicators: full, half-full, low, very low!</td></tr><tr><td> Alarm is set</td><td> Ringer on vibrate only</td><td> Battery is charging</td></tr><tr><td> Song is playing</td><td> Phone on mute</td><td> Wireless services are off (Airplane mode)</td></tr><tr><td> Data is syncing</td><td> GPS is enabled and working</td><td> Bluetooth® is on, Bluetooth device connected</td></tr><tr><td> SD card full!</td><td> Uploading/downloading</td><td> No SIM card in phone</td></tr><tr><td></td><td> Content downloaded</td><td></td></tr><tr><td> More (undisplayed) notifications</td><td> Sign-in/sync error</td><td></td></tr></table> <div>Samsung GT-I7500 Galaxy</div> <p>SAMSUNG_PRIORART0005494 at pg. PDF 21:</p>	New email message	Call in progress	GSM signal, roaming, no signal	New SMS or MMS	Missed call	GPRS service connected, data flowing	Problem with SMS or MMS delivery	Call on hold	Edge service connected, data flowing	New instant message	Call forwarding is on	3G service connected, data flowing	New voicemail	Speakerphone is on	Wi-Fi service connected, network available	Upcoming event	Ringer is off (Silent mode)	Battery charge indicators: full, half-full, low, very low!	Alarm is set	Ringer on vibrate only	Battery is charging	Song is playing	Phone on mute	Wireless services are off (Airplane mode)	Data is syncing	GPS is enabled and working	Bluetooth® is on, Bluetooth device connected	SD card full!	Uploading/downloading	No SIM card in phone		Content downloaded		More (undisplayed) notifications	Sign-in/sync error	
New email message	Call in progress	GSM signal, roaming, no signal																																			
New SMS or MMS	Missed call	GPRS service connected, data flowing																																			
Problem with SMS or MMS delivery	Call on hold	Edge service connected, data flowing																																			
New instant message	Call forwarding is on	3G service connected, data flowing																																			
New voicemail	Speakerphone is on	Wi-Fi service connected, network available																																			
Upcoming event	Ringer is off (Silent mode)	Battery charge indicators: full, half-full, low, very low!																																			
Alarm is set	Ringer on vibrate only	Battery is charging																																			
Song is playing	Phone on mute	Wireless services are off (Airplane mode)																																			
Data is syncing	GPS is enabled and working	Bluetooth® is on, Bluetooth device connected																																			
SD card full!	Uploading/downloading	No SIM card in phone																																			
	Content downloaded																																				
More (undisplayed) notifications	Sign-in/sync error																																				

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433





























































'433 Claims	Android Device with One or More Apps																																												
	<div> <div> <h3>Icons</h3> <p>Learn about the icons that appear on your screen.</p> <table> <tr> <th>Icon</th><th>Definition</th></tr> <tr> <td></td><td>Signal strength</td></tr> <tr> <td></td><td>GPRS network connected</td></tr> <tr> <td></td><td>EDGE network connected</td></tr> <tr> <td></td><td>UMTS network connected</td></tr> <tr> <td></td><td>Roaming (outside of normal service area)</td></tr> <tr> <td></td><td>GPS activated</td></tr> <tr> <td></td><td>More status icons are available (touch the icon to see them)</td></tr> <tr> <td></td><td>Call in progress</td></tr> <tr> <td></td><td>Missed call</td></tr> </table> </div> <div> <table> <tr> <th>Icon</th><th>Definition</th></tr> <tr> <td></td><td>Call diverting activated</td></tr> <tr> <td></td><td>Connected to PC</td></tr> <tr> <td></td><td>Bluetooth activated</td></tr> <tr> <td></td><td>Bluetooth device connected</td></tr> <tr> <td></td><td>Wi-Fi activated</td></tr> <tr> <td></td><td>Synchronised with the web</td></tr> <tr> <td></td><td>No SIM card</td></tr> <tr> <td></td><td>New text message (SMS) or multimedia message (MMS)</td></tr> <tr> <td></td><td>New email message</td></tr> <tr> <td></td><td>New voice mail message</td></tr> <tr> <td></td><td>Instant message</td></tr> </table> </div> </div> <div> <h3><u>JuiceDefender App</u></h3> <p>SAMSUNG_PRIORART0000379 (Latedroid) (“JuiceDefender saves battery power (lots of it!) by controlling the device data connection and/or WiFi ... You can schedule regular APN/WiFi activation to let background data sync occur and have APN/WiFi enabled while the screen is on. It also helps in minimizing distractions.”).</p> <p>SAMSUNG_PRIORART0000351 (Configuration-Translated) (“APN: activates / deactivates the APN connection, in its submenu we find the MMS button that activated configures the reception of MMS in the same way that we have the APN and Prefer Wifi that activated will try to connect first to this and if to five seconds does not find an available network will activate the APN. WIFI: activates / deactivates the WIFI connection, in its submenu we find the following buttons, Auto Disable turns off the wifi in the case of not finding a network available to save battery, in case it is deactivated we will have to</p> </div>	Icon	Definition		Signal strength		GPRS network connected		EDGE network connected		UMTS network connected		Roaming (outside of normal service area)		GPS activated		More status icons are available (touch the icon to see them)		Call in progress		Missed call	Icon	Definition		Call diverting activated		Connected to PC		Bluetooth activated		Bluetooth device connected		Wi-Fi activated		Synchronised with the web		No SIM card		New text message (SMS) or multimedia message (MMS)		New email message		New voice mail message		Instant message
Icon	Definition																																												
	Signal strength																																												
	GPRS network connected																																												
	EDGE network connected																																												
	UMTS network connected																																												
	Roaming (outside of normal service area)																																												
	GPS activated																																												
	More status icons are available (touch the icon to see them)																																												
	Call in progress																																												
	Missed call																																												
Icon	Definition																																												
	Call diverting activated																																												
	Connected to PC																																												
	Bluetooth activated																																												
	Bluetooth device connected																																												
	Wi-Fi activated																																												
	Synchronised with the web																																												
	No SIM card																																												
	New text message (SMS) or multimedia message (MMS)																																												
	New email message																																												
	New voice mail message																																												
	Instant message																																												

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>activate it manually; Enable on Schedule / Peak / Screen will activate the wifi as we have configured those buttons that we will see below.”)</p> <p>SAMSUNG_PRIORART0000361 (Purdy) (“Android: Most phones don't make it easy to switch cellular data connection on and off, even if doing so really helps save your battery. JuiceDefender toggles wireless data and Wi-Fi on and off every so often to preserve power.”).</p> <p>SAMSUNG_PRIORART0000335 (Ruddock) (“Juice Defender is a battery conservation app. It uses various triggers, rules, and timers to control how often your device utilizes 3G/EDGE APN’s (data connections) as well as WiFi. These data connections are the number one drainers of battery life when your phone is idle, so Juice Defender allows you to decide when, where, and how often you want them to be active.”).</p> <p><u>GreenPower App</u></p> <p>POUZERATE0000196 (GreenPower User Guide) (“Manage Mobile Network If this setting is selected, then Green Power will regularly turn on and off the Mobile Network connection, based on the durations specified in the settings below.</p> <p>If this setting is not selected, then Green Power will leave the Mobile Network as it is, never turning it on or off.</p> <p>Please note that in order for Green Power to turn on / off Mobile Network, this one has to be manually enabled by the user first in the phone settings (Wireless & networks → Mobile Network) or in Green Power settings (Global wireless settings → Mobile Network). Green Power can't itself turn on Mobile Network as this is a limitation of the Android system for security and cost reasons.”).</p> <p><u>Android 1.0</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p><u>GOOG-HEADWATER-00000040, SAMSUNG PRIORART0005487, ConnectivityManager</u></p> <pre> /** * Class that answers queries about the state of network connectivity. It also * notifies applications when network connectivity changes. Get an instance * of this class by calling * { @link android.content.Context#getSystemService(String) Context.getSystemService(Context.CONNECTIVITY_SERVICE)}. * <p> * The primary responsibilities of this class are to: * * Monitor network connections (Wi-Fi, GPRS, UMTS, etc.) * Send broadcast intents when network connectivity changes * Attempt to "fail over" to another network when connectivity to a network * is lost * Provide an API that allows applications to query the coarse-grained or fine-grained * state of the available networks * */ public static final int TYPE_MOBILE = 0; public static final int TYPE_WIFI = 1; public static final int DEFAULT_NETWORK_PREFERENCE = TYPE_WIFI; static public boolean isNetworkTypeValid(int networkType) { return networkType == TYPE_WIFI networkType == TYPE_MOBILE; } /** {@hide} */ </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public boolean setRadios(boolean turnOn) { try { return mService.setRadios(turnOn); } catch (RemoteException e) { return false; } } /** {@hide} */ public boolean setRadio(int networkType, boolean turnOn) { try { return mService.setRadio(networkType, turnOn); } catch (RemoteException e) { return false; } } </pre> <p><u>SAMSUNG PRIORART0005487, NetworkInfo</u></p> <pre> /** * Indicates whether network connectivity exists or is in the process * of being established. This is good for applications that need to * do anything related to the network other than read or write data. * For the latter, call {@link #isConnected()} instead, which guarantees * that the network is fully usable. * @return {@code true} if network connectivity exists or is in the process * of being established, {@code false} otherwise. */ public boolean isConnectedOrConnecting() { return mState == State.CONNECTED mState == State.CONNECTING; } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Indicates whether network connectivity exists and it is possible to establish * connections and pass data. * @return { @code true } if network connectivity exists, { @code false } otherwise. */ public boolean isConnected() { return mState == State.CONNECTED; } /** * Indicates whether network connectivity is possible. A network is unavailable * when a persistent or semi-persistent condition prevents the possibility * of connecting to that network. Examples include * * The device is out of the coverage area for any network of this type. * The device is on a network other than the home network (i.e., roaming), and * data roaming has been disabled. * The device's radio is turned off, e.g., because airplane mode is enabled. * * @return { @code true } if the network is available, { @code false } otherwise */ public boolean isAvailable() { return mIsAvailable; } /** * Sets if the network is available, ie, if the connectivity is possible. * @param isAvailable the new availability value. * </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * { @hide } */ public void setIsAvailable(boolean isAvailable) { mIsAvailable = isAvailable; } public String getTypeName() { switch (mNetworkType) { case ConnectivityManager.TYPE_WIFI: return "WIFI"; case ConnectivityManager.TYPE_MOBILE: return "MOBILE"; default: return "<invalid>"; } } </pre> <p><u>SAMSUNG PRIORART0005487, NetworkStateTracker</u></p> <pre> /** * Turn the wireless radio off for a network. * @param turnOn { @code true } to turn the radio on, { @code false } */ public abstract boolean setRadio(boolean turnOn); /** * Returns an indication of whether this network is available for * connections. A value of { @code false } means that some quasi-permanent * condition prevents connectivity to this network. */ </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public abstract boolean isAvailable(); <u>SAMSUNG PRIORART0005487, ConnectivityService</u> /* * Create the network state trackers for Wi-Fi and mobile * data. Maybe this could be done with a factory class, * but it's not clear that it's worth it, given that * the number of different network types is not going * to change very often. */ if (DBG) Log.v(TAG, "Starting Wifi Service."); mWifiStateTracker = new WifiStateTracker(context, handler); WifiService wifiService = new WifiService(context, mWifiStateTracker); ServiceManager.addService(Context.WIFI_SERVICE, wifiService); // The WifiStateTracker should appear first in the list mNetTrackers[ConnectivityManager.TYPE_WIFI] = mWifiStateTracker; mMobileDataStateTracker = new MobileDataStateTracker(context, handler); mNetTrackers[ConnectivityManager.TYPE_MOBILE] = mMobileDataStateTracker; mActiveNetwork = null; mNumDnsEntries = 0; mTestMode = SystemProperties.get("cm.test.mode").equals("true") && SystemProperties.get("ro.build.type").equals("eng"); for (NetworkStateTracker t : mNetTrackers) t.startMonitoring(); // Constructing this starts it too mWifiWatchdogService = new WifiWatchdogService(context, mWifiStateTracker); } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Make the state of network connectivity conform to the preference settings. * In this method, we only tear down a non-preferred network. Establishing * a connection to the preferred network is taken care of when we handle * the disconnect event from the non-preferred network * (see { @link #handleDisconnect(NetworkInfo)}). */ /** * Ensure that a network route exists to deliver traffic to the specified * host via the specified network interface. * @param networkType the type of the network over which traffic to the specified * host is to be routed * @param hostAddress the IP address of the host to which the route is desired * @return { @code true } on success, { @code false } on failure */ </pre> <p><u>Android 1.6</u></p> <p><u>SAMSUNG PRIORART0005350, ConnectivityManager</u></p> <pre> /** * Class that answers queries about the state of network connectivity. It also </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* notifies applications when network connectivity changes. Get an instance</p> <p>* of this class by calling</p> <p>* {@link android.content.Context#getSystemService(String) Context.getSystemService(Context.CONNECTIVITY_SERVICE)}.</p> <p>* <p></p> <p>* The primary responsibilities of this class are to:</p> <p>* </p> <p>* Monitor network connections (Wi-Fi, GPRS, UMTS, etc.)</p> <p>* Send broadcast intents when network connectivity changes</p> <p>* Attempt to "fail over" to another network when connectivity to a network</p> <p>* is lost</p> <p>* Provide an API that allows applications to query the coarse-grained or fine-grained</p> <p>* state of the available networks</p> <p>* </p> <p>*/</p> <p>@SdkConstant(SdkConstantType.BROADCAST_INTENT_ACTION)</p> <p>public static final String ACTION_BACKGROUND_DATA_SETTING_CHANGED =</p> <p>"android.net.conn.BACKGROUND_DATA_SETTING_CHANGED";</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int TYPE_MOBILE = 0; public static final int TYPE_WIFI = 1; public static final int DEFAULT_NETWORK_PREFERENCE = TYPE_WIFI; static public boolean isNetworkTypeValid(int networkType) { return networkType == TYPE_WIFI networkType == TYPE_MOBILE; } public void setNetworkPreference(int preference) { try { mService.setNetworkPreference(preference); } catch (RemoteException e) { } } /** {@hide} */</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public boolean setRadio(int networkType, boolean turnOn) { try { return mService.setRadio(networkType, turnOn); } catch (RemoteException e) { return false; } } </pre> <p>/**</p> <ul style="list-style-type: none"> * Returns the value of the setting for background data usage. If false, * applications should not use the network if the application is not in the * foreground. Developers should respect this setting, and check the value * of this before performing any background data operations. * <p> * All applications that have background services that use the network * should listen to {@link #ACTION_BACKGROUND_DATA_SETTING_CHANGED}. * * @return Whether background data usage is allowed.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> */ public boolean getBackgroundDataSetting() { try { return mService.getBackgroundDataSetting(); } catch (RemoteException e) { // Err on the side of safety return false; } } /** * Sets the value of the setting for background data usage. * * @param allowBackgroundData Whether an application should use data while * it is in the background. * * @attr ref android.Manifest.permission#CHANGE_BACKGROUND_DATA_SETTING * @see #getBackgroundDataSetting() </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * @hide */ public void setBackgroundDataSeting(boolean allowBackgroundData) { try { mService.setBackgroundDataSeting(allowBackgroundData); } catch (RemoteException e) { } } </pre> <p><u>SAMSUNG_PRIORART0005350, NetworkInfo</u></p> <pre> /** * Indicates whether network connectivity is possible: */ private boolean mIsAvailable; /** * Return a human-readable name describe the type of the network, </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* for example "WIFI" or "MOBILE".</p> <p>* @return the name of the network type</p> <p>*/</p> <pre>public String getTypeName() { return mTypeName; }</pre> <p>/**</p> <p>* Indicates whether network connectivity exists or is in the process</p> <p>* of being established. This is good for applications that need to</p> <p>* do anything related to the network other than read or write data.</p> <p>* For the latter, call {@link #isConnected()} instead, which guarantees</p> <p>* that the network is fully usable.</p> <p>* @return {@code true} if network connectivity exists or is in the process</p> <p>* of being established, {@code false} otherwise.</p> <p>*/</p> <pre>public boolean isConnectedOrConnecting() { return mState == State.CONNECTED mState == State.CONNECTING;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> } /** * Indicates whether network connectivity is possible. A network is unavailable * when a persistent or semi-persistent condition prevents the possibility * of connecting to that network. Examples include * * The device is out of the coverage area for any network of this type. * The device is on a network other than the home network (i.e., roaming), and * data roaming has been disabled. * The device's radio is turned off, e.g., because airplane mode is enabled. * * @return {@code true} if the network is available, {@code false} otherwise */ public boolean isAvailable() { return mIsAvailable; } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Indicates whether the device is currently roaming on this network. * When {@code true}, it suggests that use of data on this network * may incur extra costs. * @return {@code true} if roaming is in effect, {@code false} otherwise. */ public boolean isRoaming() { return mIsRoaming; } SAMSUNG_PRIORART0005350, ConnectivityService /* * Create the network state trackers for Wi-Fi and mobile * data. Maybe this could be done with a factory class, * but it's not clear that it's worth it, given that * the number of different network types is not going * to change very often. </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> */ if (DBG) Log.v(TAG, "Starting Wifi Service."); mWifiStateTracker = new WifiStateTracker(context, handler); WifiService wifiService = new WifiService(context, mWifiStateTracker); ServiceManager.addService(Context.WIFI_SERVICE, wifiService); mNetTrackers[ConnectivityManager.TYPE_WIFI] = mWifiStateTracker; mMobileDataStateTracker = new MobileDataStateTracker(context, handler); mNetTrackers[ConnectivityManager.TYPE_MOBILE] = mMobileDataStateTracker; /** * Make the state of network connectivity conform to the preference settings. * In this method, we only tear down a non-preferred network. Establishing * a connection to the preferred network is taken care of when we handle * the disconnect event from the non-preferred network * (see {@link #handleDisconnect(NetworkInfo)}). */ </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> private void enforcePreference() { if (mActiveNetwork == null) return; for (NetworkStateTracker t : mNetTrackers) { if (t == mActiveNetwork) { int netType = t.getNetworkInfo().getType(); int otherNetType = ((netType == ConnectivityManager.TYPE_WIFI) ? ConnectivityManager.TYPE_MOBILE : ConnectivityManager.TYPE_WIFI); if (t.getNetworkInfo().getType() != mNetworkPreference) { NetworkStateTracker otherTracker = mNetTrackers[otherNetType]; if (otherTracker.isAvailable()) { teardown(t); } } } } } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> } } /** * @see ConnectivityManager#getBackgroundDataSetting() */ public boolean getBackgroundDataSetting() { return Settings.Secure.getInt(mContext.getContentResolver(), Settings.Secure.BACKGROUND_DATA, 1) == 1; } /** * @see ConnectivityManager#setBackgroundDataSetting(boolean) */ public void setBackgroundDataSetting(boolean allowBackgroundDataUsage) { mContext.enforceCallingOrSelfPermission(android.Manifest.permission.CHANGE_BACKGROUND_DATA_SETTING, "ConnectivityService"); } }</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>if (getBackgroundDataSetting() == allowBackgroundDataUsage) return; Settings.Secure.putInt(mContext.getContentResolver(), Settings.Secure.BACKGROUND_DATA, allowBackgroundDataUsage ? 1 : 0); Intent broadcast = new Intent(ConnectivityManager.ACTION_BACKGROUND_DATA_SETTING_CHANGED); mContext.sendBroadcast(broadcast); }</pre> <p>/**</p> <ul style="list-style-type: none">* See if the other network is available to fail over to.* If is not available, we enable it anyway, so that it* will be able to connect when it does become available,* but we report a total loss of connectivity rather than* report that we are attempting to fail over.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> */ NetworkInfo switchTo = null; if (newNet.isAvailable()) { mActiveNetwork = newNet; switchTo = newNet.getNetworkInfo(); switchTo.setFailover(true); if (!switchTo.isConnectedOrConnecting()) { newNet.reconnect(); } } else { newNet.reconnect(); } if (info.getType() == ConnectivityManager.TYPE_MOBILE) { otherNet = mWifiStateTracker; } else /* info().getType() == TYPE_WIFI */ { otherNet = mMobileDataStateTracker; } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>int incrValue = ConnectivityManager.TYPE_MOBILE - ConnectivityManager.TYPE_WIFI; int stopValue = ConnectivityManager.TYPE_MOBILE + incrValue;</pre> <p><u>SAMSUNG PRIORART0005350, BatteryStats</u></p> <pre>/** * A constant indicating a a wifi turn on timer * * {@hide} */ public static final int WIFI_TURNED_ON = 4; /** * A constant indicating a full wifi lock timer * * {@hide}</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>*/ public static final int FULL_WIFI_LOCK = 5; /** * A constant indicating a scan wifi lock timer * * {@hide} */ public static final int SCAN_WIFI_LOCK = 6; /** * A constant indicating a wifi multicast timer * * {@hide} */ public static final int WIFI_MULTICAST_ENABLED = 7; /**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* A constant indicating an audio turn on timer * * {@hide} */ public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8; /** * Include all of the data in the stats, including previously saved data. */ public static final int STATS_TOTAL = 0;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Include only the last run in the stats. */ public static final int STATS_LAST = 1; /** * Include only the current run in the stats. */ public static final int STATS_CURRENT = 2; /** * Include only the run since the last time the device was unplugged in the stats. */ public static final int STATS_UNPLUGGED = 3; public abstract void noteWifiTurnedOnLocked(); public abstract void noteWifiTurnedOffLocked();</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public abstract void noteFullWifiLockAcquiredLocked(); public abstract void noteFullWifiLockReleasedLocked(); public abstract void noteScanWifiLockAcquiredLocked(); public abstract void noteScanWifiLockReleasedLocked(); public abstract void noteWifiMulticastEnabledLocked(); public abstract void noteWifiMulticastDisabledLocked(); /** * Returns the time in microseconds that the screen has been on while the device was * running on battery. * * {@hide} */ public abstract long getScreenOnTime(long batteryRealtime, int which); public static final int SCREEN_BRIGHTNESS_DARK = 0; public static final int SCREEN_BRIGHTNESS_DIM = 1; public static final int SCREEN_BRIGHTNESS_MEDIUM = 2; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public static final int SCREEN_BRIGHTNESS_LIGHT = 3; public static final int SCREEN_BRIGHTNESS_BRIGHT = 4; public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4; /** * Returns the time in microseconds that wifi has been on while the device was * running on battery. * * {@hide} */ public abstract long getWifiOnTime(long batteryRealtime, int which); /** </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * Returns the time in microseconds that bluetooth has been on while the device was * running on battery. * * {@hide} */ public abstract long getBluetoothOnTime(long batteryRealtime, int which); /** * Return whether we are currently running on battery. */ public abstract boolean getIsOnBattery(); /** * Returns the time that the radio was on for data transfers. * @return the uptime in microseconds while unplugged */ public abstract long getRadioDataUptime(); </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Returns the current battery realtime in microseconds. * * @param curTime the amount of elapsed realtime in microseconds. */ public abstract long getBatteryRealtime(long curTime); /** * Returns the battery percentage level at the last time the device was unplugged from power, or * the last time it booted on battery power. */ public abstract int getDischargeStartLevel();</pre> <p><u>Android 2.2</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p><u>GOOG-HEADWATER-00000029, SAMSUNG PRIORART0005353, ConnectivityManager</u></p> <p>/**</p> <ul style="list-style-type: none"> * Class that answers queries about the state of network connectivity. It also * notifies applications when network connectivity changes. Get an instance * of this class by calling * {@link android.content.Context#getService(String) Context.getSystemService(Context.CONNECTIVITY_SERVICE)}. * <p> * The primary responsibilities of this class are to: * * Monitor network connections (Wi-Fi, GPRS, UMTS, etc.) * Send broadcast intents when network connectivity changes * Attempt to "fail over" to another network when connectivity to a network * is lost * Provide an API that allows applications to query the coarse-grained or fine-grained * state of the available networks * * /

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* A change in network connectivity has occurred. A connection has either</p> <p>* been established or lost. The NetworkInfo for the affected network is</p> <p>* sent as an extra; it should be consulted to see what kind of</p> <p>* connectivity event occurred.</p> <p>/**</p> <p>* Broadcast Action: The setting for background data usage has changed</p> <p>* values. Use {@link #getBackgroundDataSetting()} to get the current value.</p> <p>* <p></p> <p>* If an application uses the network in the background, it should listen</p> <p>* for this broadcast and stop using the background data if the value is</p> <p>* false.</p> <p>*/</p> <p>@SdkConstant(SdkConstantType.BROADCAST_INTENT_ACTION)</p> <p>public static final String ACTION_BACKGROUND_DATA_SETTING_CHANGED =</p> <p> "android.net.conn.BACKGROUND_DATA_SETTING_CHANGED";</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * The Default Mobile data connection. When active, all data traffic * will use this connection by default. Should not coexist with other * default connections. */ public static final int TYPE_MOBILE = 0; /** * The Default WIFI data connection. When active, all data traffic * will use this connection by default. Should not coexist with other * default connections. */ public static final int TYPE_WIFI = 1; /**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* Returns the value of the setting for background data usage. If false,</p> <p>* applications should not use the network if the application is not in the</p> <p>* foreground. Developers should respect this setting, and check the value</p> <p>* of this before performing any background data operations.</p> <p>* <p></p> <p>* All applications that have background services that use the network</p> <p>* should listen to {@link #ACTION_BACKGROUND_DATA_SETTING_CHANGED}.</p> <p>*</p> <p>* @return Whether background data usage is allowed.</p> <p>*/</p> <pre> public boolean getBackgroundDataSetting() { try { return mService.getBackgroundDataSetting(); } catch (RemoteException e) { // Err on the side of safety return false; } } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Sets the value of the setting for background data usage. * * @param allowBackgroundData Whether an application should use data while * it is in the background. * * @attr ref android.Manifest.permission#CHANGE_BACKGROUND_DATA_SETTING * @see #getBackgroundDataSetting() * @hide */ public void setBackgroundDataSetting(boolean allowBackgroundData) { try { mService.setBackgroundDataSetting(allowBackgroundData); } catch (RemoteException e) { } }</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Sets the persisted value for enabling/disabling Mobile data. * * @param enabled Whether the mobile data connection should be * used or not. * @hide */ public void setMobileDataEnabled(boolean enabled) { try { mService.setMobileDataEnabled(enabled); } catch (RemoteException e) { } }</pre> <p><u>SAMSUNG_PRIORART0005353, NetworkStateTracker</u></p> <pre>/**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * Record the roaming status of the device, and if it is a change from the previous * status, send a notification to any listeners. * @param isRoaming {@code true} if the device is now roaming, {@code false} * if it is no longer roaming. */ protected void setRoamingStatus(boolean isRoaming) { if (isRoaming != mNetworkInfo.isRoaming()) { mNetworkInfo.setRoaming(isRoaming); Message msg = mTarget.obtainMessage(EVENT_ROAMING_CHANGED, mNetworkInfo); msg.sendToTarget(); } } public static final int EVENT_ROAMING_CHANGED = 5; <u>SAMSUNG_PRIORART0005353, ThrottleManager</u> /** * Class that handles throttling. It provides read/write numbers per interface </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* and methods to apply throttled rates.</p> <p>* {@hide}</p> <p>*/</p> <p>/**</p> <p>* returns a long of the byte count either read or written on the named interface</p> <p>* for the period described. Direction is either DIRECTION_RX or DIRECTION_TX and</p> <p>* period may only be PERIOD_CYCLE for the current cycle (other periods may be supported</p> <p>* in the future). Ago indicates the number of periods in the past to lookup - 0 means</p> <p>* the current period, 1 is the last one, 2 was two periods ago..</p> <p>* {@hide}</p> <p>*/</p> <p>public long getByteCount(String iface, int direction, int period, int ago) {</p> <p> try {</p> <p> return mService.getByteCount(iface, direction, period, ago);</p> <p> } catch (RemoteException e) {</p> <p> return -1;</p> <p> }</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> } /** * returns the number of bytes read+written after which a particular cliff * takes effect on the named iface. Currently only cliff #1 is supported (1 step) * {@hide} */ public long getCliffThreshold(String iface, int cliff) { try { return mService.getCliffThreshold(iface, cliff); } catch (RemoteException e) { return -1; } } <u>SAMSUNG_PRIORART0005353, ConnectivityManagerMobileTest</u> // help function to verify 3G connection public void verifyCellularConnection() { </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> NetworkInfo extraNetInfo = cmActivity.mNetworkInfo; assertEquals("network type is not MOBILE", ConnectivityManager.TYPE_MOBILE, extraNetInfo.getType()); assertTrue("not connected to cellular network", extraNetInfo.isConnected()); assertTrue("no data connection", cmActivity.mState.equals(State.CONNECTED)); } // Wait for the Wifi state to be DISABLED waitForWifiState(WifiManager.WIFI_STATE_DISABLED, STATE_TRANSITION_LONG_TIMEOUT); waitForNetworkState(ConnectivityManager.TYPE_WIFI, State.DISCONNECTED, STATE_TRANSITION_LONG_TIMEOUT); waitForNetworkState(ConnectivityManager.TYPE_MOBILE, State.CONNECTED, STATE_TRANSITION_LONG_TIMEOUT); //Prepare for connectivity state verification NetworkInfo networkInfo = cmActivity.mCM.getNetworkInfo(ConnectivityManager.TYPE_MOBILE); cmActivity.setStateTransitionCriteria(ConnectivityManager.TYPE_MOBILE, </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> networkInfo.getState(), NetworkState.DO_NOTHING, State.DISCONNECTED); networkInfo = cmActivity.mCM.getNetworkInfo(ConnectivityManager.TYPE_WIFI); cmActivity.setStateTransitionCriteria(ConnectivityManager.TYPE_WIFI, networkInfo.getState(), NetworkState.TO_CONNECTION, State.CONNECTED); // Wait for Wifi to be connected and mobile to be disconnected waitForNetworkState(ConnectivityManager.TYPE_WIFI, State.CONNECTED, STATE_TRANSITION_LONG_TIMEOUT); waitForNetworkState(ConnectivityManager.TYPE_MOBILE, State.DISCONNECTED, STATE_TRANSITION_LONG_TIMEOUT); // Test case 5: test connectivity from 3G to airplane mode, then to 3G again // Test case 6: test connectivity with airplane mode Wifi connected </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p><u>SAMSUNG PRIORART0005353, ConnectivityService</u></p> <pre> /* * Create the network state trackers for Wi-Fi and mobile * data. Maybe this could be done with a factory class, * but it's not clear that it's worth it, given that * the number of different network types is not going * to change very often. */ boolean noMobileData = !getMobileDataEnabled(); for (int netType : mPriorityList) { switch (mNetAttributes[netType].mRadio) { case ConnectivityManager.TYPE_WIFI: if (DBG) Slog.v(TAG, "Starting Wifi Service."); WifiStateTracker wst = new WifiStateTracker(context, mHandler); WifiService wifiService = new WifiService(context, wst); ServiceManager.addService(Context.WIFI_SERVICE, wifiService); wifiService.startWifi(); </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>mNetTrackers[ConnectivityManager.TYPE_WIFI] = wst; wst.startMonitoring(); break; case ConnectivityManager.TYPE_MOBILE: mNetTrackers[netType] = new MobileDataStateTracker(context, mHandler, netType, mNetAttributes[netType].mName); mNetTrackers[netType].startMonitoring(); if (noMobileData) { if (DBG) Slog.d(TAG, "tearing down Mobile networks due to setting"); mNetTrackers[netType].teardown(); } break; default: Slog.e(TAG, "Trying to create a DataStateTracker for an unknown radio type " + mNetAttributes[netType].mRadio); continue; }</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> } /** * Sets the preferred network. * @param preference the new preference */ public synchronized void setNetworkPreference(int preference) { enforceChangePermission(); if (ConnectivityManager.isNetworkTypeValid(preference) && mNetAttributes[preference] != null && mNetAttributes[preference].isDefault()) { if (mNetworkPreference != preference) { persistNetworkPreference(preference); mNetworkPreference = preference; enforcePreference(); } } } } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Return NetworkInfo for the active (i.e., connected) network interface. * It is assumed that at most one network is active at a time. If more * than one is active, it is indeterminate which will be returned. * @return the info for the active network, or {@code null} if none is * active */ public NetworkInfo getActiveNetworkInfo() { enforceAccessPermission(); for (int type=0; type <= ConnectivityManager.MAX_NETWORK_TYPE; type++) { if (mNetAttributes[type] == null !mNetAttributes[type].isDefault()) { continue; } NetworkStateTracker t = mNetTrackers[type]; NetworkInfo info = t.getNetworkInfo(); if (info.isConnected()) { if (DBG && type != mActiveDefaultNetwork) Slog.e(TAG, </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> "connected default network is not " + "mActiveDefaultNetwork!"); return info; } } return null; } // TODO - move this into the MobileDataStateTracker int usedNetworkType = networkType; if(networkType == ConnectivityManager.TYPE_MOBILE) { if (!getMobileDataEnabled()) { if (DBG) Slog.d(TAG, "requested special network with data disabled - rejected"); return Phone.APN_TYPE_NOT_AVAILABLE; } if (TextUtils.equals(feature, Phone.FEATURE_ENABLE_MMS)) { usedNetworkType = ConnectivityManager.TYPE_MOBILE_MMS; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> } else if (TextUtils.equals(feature, Phone.FEATURE_ENABLE_SUPL)) { usedNetworkType = ConnectivityManager.TYPE_MOBILE_SUPL; } else if (TextUtils.equals(feature, Phone.FEATURE_ENABLE_DUN)) { usedNetworkType = ConnectivityManager.TYPE_MOBILE_DUN; } else if (TextUtils.equals(feature, Phone.FEATURE_ENABLE_HIPRI)) { usedNetworkType = ConnectivityManager.TYPE_MOBILE_HIPRI; } } int usedNetworkType = networkType; if (networkType == ConnectivityManager.TYPE_MOBILE) { if (TextUtils.equals(feature, Phone.FEATURE_ENABLE_MMS)) { usedNetworkType = ConnectivityManager.TYPE_MOBILE_MMS; } else if (TextUtils.equals(feature, Phone.FEATURE_ENABLE_SUPL)) { usedNetworkType = ConnectivityManager.TYPE_MOBILE_SUPL; } else if (TextUtils.equals(feature, Phone.FEATURE_ENABLE_DUN)) { usedNetworkType = ConnectivityManager.TYPE_MOBILE_DUN; } else if (TextUtils.equals(feature, Phone.FEATURE_ENABLE_HIPRI)) { </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> usedNetworkType = ConnectivityManager.TYPE_MOBILE_HIPRI; } } /** * @see ConnectivityManager#getBackgroundDataSetting() */ public boolean getBackgroundDataSetting() { return Settings.Secure.getInt(mContext.getContentResolver(), Settings.Secure.BACKGROUND_DATA, 1) == 1; } /** * @see ConnectivityManager#setBackgroundDataSetting(boolean) */ public void setBackgroundDataSetting(boolean allowBackgroundDataUsage) { mContext.enforceCallingOrSelfPermission(</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> android.Manifest.permission.CHANGE_BACKGROUND_DATA_SETTING, "ConnectivityService"); if (getBackgroundDataSetting() == allowBackgroundDataUsage) return; Settings.Secure.putInt(mContext.getContentResolver(), Settings.Secure.BACKGROUND_DATA, allowBackgroundDataUsage ? 1 : 0); Intent broadcast = new Intent(ConnectivityManager.ACTION_BACKGROUND_DATA_SETTING_CHANGED); mContext.sendBroadcast(broadcast); } /** * @see ConnectivityManager#getMobileDataEnabled() */ </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public boolean getMobileDataEnabled() { enforceAccessPermission(); boolean retVal = Settings.Secure.getInt(mContext.getContentResolver(), Settings.Secure.MOBILE_DATA, 1) == 1; if (DBG) Slog.d(TAG, "getMobileDataEnabled returning " + retVal); return retVal; } </pre> <p><u>SAMSUNG_PRIORART0005353, BatteryStats</u></p> <pre> /** * A class providing access to battery usage statistics, including information on * wakelocks, processes, packages, and services. All times are represented in microseconds * except where indicated otherwise. * @hide */ </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * A constant indicating a a wifi turn on timer * * {@hide} */ public static final int WIFI_TURNED_ON = 4; /** * A constant indicating an audio turn on timer * * {@hide} */ public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide}</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> */ public static final int VIDEO_TURNED_ON = 8; public static final int SIGNAL_STRENGTH_NONE_OR_UNKNOWN = 0; public static final int SIGNAL_STRENGTH_POOR = 1; public static final int SIGNAL_STRENGTH_MODERATE = 2; public static final int SIGNAL_STRENGTH_GOOD = 3; public static final int SIGNAL_STRENGTH_GREAT = 4; static final String[] SIGNAL_STRENGTH_NAMES = { "none", "poor", "moderate", "good", "great" }; public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><u>GOOG-HEADWATER-00000092, Google I/O 2009 - Coding for Life -- Battery Life, That Is (June 2, 2009)</u></p> <p><u>Google I/O, 2009</u></p> <p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 2:</p> <p>Coding for Life--Battery Life, That Is</p> <p>Jeff Sharkey May 27, 2009</p> <p>Post your questions for this talk on Google Moderator: code.google.com/events/io/questions</p> <p>Google </p> <p>GOOG-HEADWATER-00000093</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 3:</p> <h3>Why does this matter?</h3> <ul style="list-style-type: none">• Phones primarily run on battery power, and each device has a "battery budget"<ul style="list-style-type: none">○ When it's gone, it's gone○ Apps need to work together to be good citizens of that shared resource○ Current measured in mA, battery capacity in mAh• HTC Dream: 1150mAh• HTC Magic: 1350mAh• Samsung I7500: 1500mAh• Asus Eee PC: 5800mAh <div></div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 9:</p> <h2>How can we do better?</h2> <h3>Networking</h3> <ul style="list-style-type: none">● Check network connection, wait for 3G or WiFi <pre>ConnectivityManager mConnectivity; TelephonyManager mTelephony; // Skip if no connection, or background data disabled NetworkInfo info = mConnectivity.getActiveNetworkInfo(); if (info == null !mConnectivity.getBackgroundDataSetting()) { return false; }</pre>  <div>Google 09 I/O</div> <div>GOOG-HEADWATER-00000100</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 11:</p> <p>How can we do better? Networking</p> <p>● Check network connection, wait for 3G or WiFi</p> <pre>// Only update if WiFi or 3G is connected and not roaming int netType = info.getType(); int netSubtype = info.getSubtype(); if (netType == ConnectivityManager.TYPE_WIFI) { return info.isConnected(); } else if (netType == ConnectivityManager.TYPE_MOBILE && netSubtype == TelephonyManager.NETWORK_TYPE_UMTS && !mTelephony.isNetworkRoaming()) { return info.isConnected(); } else { return false; }</pre> <div data-bbox="1556 1227 1766 1289">  </div> <div data-bbox="1512 1346 1780 1369"> <p>GOOG-HEADWATER-00000101</p> </div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<i>See, e.g.</i> , GOOG-HEADWATER-000000092 at 16:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>How can we do better? Foreground apps</p> <ul style="list-style-type: none">● Wakelocks are costly if forgotten<ul style="list-style-type: none">○ Pick the lowest level possible, and use specific timeouts to work around unforeseen bugs○ Consider using <code>android:keepScreenOn</code> to ensure correctness <pre><LinearLayout android:orientation="vertical" android:layout_width="fill_parent" android:layout_height="fill_parent" android:keepScreenOn="true"></pre> <p>Google 09 </p> <hr/> <p>GOOG-HEADWATER-00000107</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 18:</p> <h2>How can we do better?</h2> <p>Foreground apps</p> <ul style="list-style-type: none">● Use coarse network location, it's much cheaper<ul style="list-style-type: none">○ GPS: 25 seconds * 140mA = 1mAh○ Network: 2 seconds * 180mA = 0.1mAh● 1.5 uses AGPS when network available● GPS time-to-fix varies wildly based on environment, and desired accuracy, and might outright fail<ul style="list-style-type: none">○ Just like wake-locks, location updates can continue after onPause(), so make sure to unregister○ If all apps unregister correctly, user can leave GPS enabled in Settings <div></div> <div><p>GOOG-HEADWATER-00000109</p></div> <p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 20:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Foreground apps</p> <ul style="list-style-type: none">● Accelerometer/magnetic sensors<ul style="list-style-type: none">○ Normal: 10mA (used for orientation detection)○ UI: 15mA (about 1 per second)○ Game: 80mA○ Fastest: 90mA● Same cost for accelerometer, magnetic, orientation sensors on HTC Dream <div>  GOOG-HEADWATER-00000111</div> <p>See, e.g., GOOG-HEADWATER-00000092 at 22:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p data-bbox="590 316 1119 362">How can we do better?</p> <p data-bbox="590 373 884 412">Background apps</p> <ul data-bbox="577 451 1690 966" style="list-style-type: none"><li data-bbox="577 451 1690 597">● Services should be short-lived; these aren't daemons<ul data-bbox="625 505 1690 597" style="list-style-type: none"><li data-bbox="625 505 1690 597">○ Each process costs 2MB and risks being killed/restarted as foreground apps need memory<li data-bbox="625 716 1690 808">○ Otherwise, keep memory usage low so you're not the first target<li data-bbox="577 820 1690 966">● Trigger wake-up through AlarmManager or with <receiver> manifest elements<ul data-bbox="625 922 1087 966" style="list-style-type: none"><li data-bbox="625 922 1087 966">○ stopSelf() when finished <div data-bbox="1570 1114 1770 1174"></div> <div data-bbox="1522 1232 1780 1252"> GOOG-HEADWATER-00000113</div> <p data-bbox="556 1284 1108 1312"><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 26:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Background apps</p> <ul style="list-style-type: none">●Dynamically enabling/disabling <receiver> components in manifest, especially when no-ops <pre><receiver android:name=".ConnectivityReceiver" android:enabled="false"> ... </receiver></pre> <pre>ComponentName receiver = new ComponentName(context, ConnectivityReceiver.class); PackageManager pm = context.getPackageManager(); pm.setComponentEnabledSetting(receiver, PackageManager.COMPONENT_ENABLED_STATE_ENABLED, PackageManager.DONT_KILL_APP);</pre> <div>Google 09 O</div> <div>GOOG-HEADWATER-00000117</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 27:</p> <h2>How can we do better?</h2> <h3>Background apps</h3> <ul style="list-style-type: none"> • Checking current battery and network state before running a full update <pre> public void onCreate() { // Register for sticky broadcast and send default registerReceiver(mReceiver, mFilter); mHandler.sendMessageDelayed(MSG_BATT, 1000); } IntentFilter mFilter = new IntentFilter(Intent.ACTION_BATTERY_CHANGED); BroadcastReceiver mReceiver = new BroadcastReceiver() { public void onReceive(Context context, Intent intent) { // Found sticky broadcast, so trigger update unregisterReceiver(mReceiver); mHandler.removeMessages(MSG_BATT); mHandler.obtainMessage(MSG_BATT, intent).sendToTarget(); } }; </pre>  <p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 29:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
	<p data-bbox="575 321 1100 375">Users will be watching!</p> <div data-bbox="552 440 947 1029">  </div> <ul data-bbox="995 461 1680 1133" style="list-style-type: none"> ● SpareParts has "Battery history" <ul style="list-style-type: none"> ○ 1.5 is already keeping stats on which apps are using CPU, network, wakelocks ○ Simplified version coming in future, and users will uninstall apps that abuse battery ● Consider giving users options for battery usage, like update intervals, and check the "no background data" flag <div data-bbox="1654 427 1730 521">  </div> <div data-bbox="1556 1127 1759 1187">  </div> <p data-bbox="1514 1247 1766 1263">GOOG-HEADWATER-00000120</p> <p data-bbox="554 1295 1108 1321">See, e.g., GOOG-HEADWATER-00000092 at 30:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>Takeaways</p> <ul style="list-style-type: none">● Use an efficient parser and GZIP to make best use of network and CPU resources● Services that sleep or poll are bad, use <receiver> and AlarmManager instead<ul style="list-style-type: none">○ Disable manifest elements when no-op○ Wake up along with everyone else (inexact alarms)● Wait for better network/battery for bulk transfers● Give users choices about background behavior <p>Google 09 </p> <p>GOOG-HEADWATER-00000121</p>
[1b] a non-transitory memory to store a	Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
<p>network service activity control policy set, the policy set including at least a first differential traffic control policy element associating one or more Internet activity access controls with at least a first end-user application; and</p>	<p><u>Nexus One</u></p> <p><i>See, e.g.,</i> SAMSUNG_PRIORART0000001 (Nexus) at 115-117:</p> <p>Configuring account sync and display options</p> <p>You can configure background data use and synchronization options for all of the applications on your phone. You can also configure what kinds of data you synchronize for each account. Some applications, such as Gmail and Calendar, have their own synchronization settings.</p> <p>Some applications, such as Contacts and Gmail, can sync data from multiple applications. Others, such as Calendar, sync data only from the first Google Account you sign into on your phone, or from an account associated specifically with that application.</p> <p>For some accounts, syncing is two-directional; changes that you make to the information on your phone are made to the copy of that information on the web. Your Google Account works this way. Other accounts support only one-way sync; the information on your phone is read-only.</p> <p>You can use the Contacts display options to configure the kinds of contacts that are displayed, as described in "Changing which contacts are displayed" on page 106.</p> <p>To configure general sync settings</p> <p>1 Open the Accounts & Sync Settings screen.</p> <p>You can do this in Contacts by pressing Menu  and touching Accounts, or directly in the Settings application (press Home , press Menu , and touch Settings).</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>The screen displays your current sync settings and a list of your current accounts.</p>  <p>Touch the account to configure.</p> <p>Some or all information from this account is configured to sync automatically with your phone.</p> <p>No information from this account syncs automatically with your phone.</p> <p> indicates that some or all of an account's information is configured to sync automatically with your phone.</p> <p> indicates that none of an account's information is configured to sync automatically with your phone.</p> <p>2 Check or uncheck Background data to control whether applications and services can transmit data when you are not working with them directly (that is, when they are running in the background).</p> <p>If you uncheck this option, Gmail stops receiving new mail, Calendar stops syncing events, and so on, until you touch the Refresh menu item or send an email.</p> <p>3 Check or uncheck Auto-sync to control whether changes you make to information on the phone or on the web are automatically synced with each other.</p> <p>For example, when this option is checked, changes that you make in Contacts on the phone are automatically made in Google Contacts on the web.</p> <p>If you uncheck this option, you may be able to use an application's tools to sync data manually. See "To sync information manually" on page 117.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p>To sync information manually</p> <ol style="list-style-type: none"> 1 Open the Accounts & Sync Settings screen. 2 Touch the account whose data you want to sync. 3 Press Menu  and touch Sync now. <p>To change an account's sync settings</p> <ol style="list-style-type: none"> 1 Open the Accounts & Sync Settings screen. 2 Touch the account whose sync settings you want to change. <p>The Data and Synchronization screen opens, displaying a list of the kinds of information the account can sync.</p> <p>Checked items are configured to sync to your phone.</p>  <ol style="list-style-type: none"> 3 Check or uncheck the kinds of information you want to sync to the phone. <p>Unchecking an option does not remove the information from your phone; it simply stops it from syncing automatically. To remove the information previously synced for the account, you must remove the account.</p> <p><i>See, e.g., SAMSUNG_PRIORART0000001 (Nexus) at 218:</i></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>Open in background Check to open new windows in the background when you touch & hold a link and touch Open in new window. This is useful when you are working with windows that take a long time to download and display. Press Menu ☰, touch Windows, and then touch the new window to view it. Uncheck if you prefer new windows that you open in this way to open in place of the current window. See "To switch Browser windows" on page 213.</p> <p>Set home page Opens a dialog where you can enter the URL of a page that you want to open whenever you open a new Browser window. If you prefer to open new Browser windows more quickly, by not opening any page by default, leave the dialog blank.</p> <p><i>See, e.g., SAMSUNG_PRIORART0000001 (Nexus) at 286:</i></p> <p>Refresh settings</p> <p>These settings control how frequently the information on the News & Weather widget is updated. In addition to using these settings, adding or removing the News & Weather widget from the Home screen also turns Auto-refresh on or off. For more about working with widgets, see "Customizing the Home screen" on page 58.</p> <p>Auto-refresh Check to have News & Weather update information automatically, at the frequency you set with Refresh interval. Uncheck to update the news and weather only when you press Menu ☰ and touch Refresh. For automatic refresh to work, you must also have Background Data turned on in the Settings application. See "Accounts & sync settings" on page 320.</p> <p><i>See, e.g., SAMSUNG_PRIORART0000001 (Nexus) at 320:</i></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>Accounts & sync settings</p> <p>Use the Accounts & Sync settings to add, remove, and manage your Google and other supported accounts. You also use these settings to control how and whether all applications send, receive, and sync data on their own schedules, and whether all applications can synchronize user data automatically.</p> <p>Gmail, Calendar, and other applications may also have their own settings to control how they synchronize data; see the sections on those applications for details.</p> <p>Accounts & sync settings screen</p> <p>Background data Check to permit applications to synchronize data in the background, whether or not you are actively working in them. Unchecking this setting can save battery power and lowers (but does not eliminate) data use.</p> <p>Auto-sync Check to permit applications to synchronize data on their own schedule. If you uncheck this setting, you must touch an account in the list on this screen, press Menu , and touch Sync now to synchronize data for that account. Synchronizing data automatically is disabled if Background data is unchecked. In that case, the Auto-sync checkbox is dimmed.</p> <p>Manage accounts The rest of this screen lists the Google Accounts and other accounts you've added to the phone. Adding accounts is described in "Accounts" on page 111.</p> <p>If you touch an account in this screen, its account screen opens.</p> <p><u>HTC Dream / T-Mobile G1</u></p> <p>SAMSUNG_PRIORART0005207-09</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p data-bbox="604 316 955 354">Data synchronization</p> <p data-bbox="604 402 1711 597">Some Google applications on your phone (Gmail, Calendar, and Contacts) give you access to the same personal information that you can add, view, and edit on your computer using Google Web applications. This means that when you add, change, or delete your information in any of these applications on the Web, the updated information also appears on your phone, and vice versa. Also, if you lose your phone or if your phone is destroyed, your personal information is not lost and will appear, as before, on a replacement phone.</p> <p data-bbox="604 621 1711 719">This mirroring of information happens through over-the-air data synchronization, or data "syncing". Data syncing occurs in the background and shouldn't ever get in your way. You'll know your data is being synchronized when you see this icon in the status bar: .</p> <p data-bbox="604 743 1711 808">Because sending large amounts of data back and forth over the air can take time and require considerable bandwidth, there are some settings on the phone that allow you to control data sync.</p>


Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

Sync by application

To control synchronization for Gmail, Calendar, and Contacts, do the following:

- 1 Press **HOME**, then press **MENU** and select **Settings**.
- 2 Select **Data synchronization**.

When any of the applications are synchronizing, you will see the "sync" icon: . You will also see the last time your data was synchronized.



↑
Date & time
of last sync

↑
Data is syncing

- 3 By default, the personal information in Gmail, Calendar, and Contacts will sync whenever you make a change or receive a new message. You can change this behavior:

Auto-sync

When selected, Auto-sync will sync Gmail, Calendar, and Contacts automatically, as you make changes or receive new messages. When OFF, information will not be synced automatically, although you can force a sync by using the individual application check boxes described below.

Gmail

Clear this check box to exclude Gmail from auto-sync. To force a sync, either clear the check box then select it, or press **MENU** and select **Sync now**. To control sync by Gmail label, you must do so from the Gmail settings screen. Read more in "Select labels to synchronize" on page 46.

Calendar

Clear this check box to exclude Calendar from auto-sync. To force a sync, either clear the check box then select it, or press **MENU** and select **Sync now**.

Contacts

Clear this check box to exclude Contacts from auto-sync. To force a sync, either clear the check box then select it, or press **MENU** and select **Sync now**.

Cancel sync

During a sync you can stop it by pressing **MENU** and selecting **Cancel sync**.

Sync problems


If you see this icon  to the left of the sync check box, then there was a temporary problem with the data synchronization. Check your data connection and try again later.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p data-bbox="604 337 886 370">Sync by Gmail label</p> <p data-bbox="604 394 1696 456">You can select to sync only Gmail messages with certain labels from the Gmail application settings screen. Read more in "Select labels to synchronize" on page 46.</p> <p data-bbox="556 527 997 560">SAMSUNG_PRIORART0005245</p> <p data-bbox="594 592 1661 654"> Open in background Select if you want links to new pages to open in a new window in the background. </p> <p data-bbox="556 727 928 760"><u>Samsung GT-I7500 Galaxy</u></p> <p data-bbox="556 800 1293 833">SAMSUNG_PRIORART0005494 at pgs. PDF 38-39, 72:</p> <div data-bbox="583 898 1102 1320"> <p data-bbox="583 898 835 930">Synchronise data</p> <p data-bbox="583 946 1102 1027">You can synchronise data (Google messages, calendar, and contacts) with the Google web server and back up or restore your data.</p> <p data-bbox="583 1044 1102 1174">Once the synchronisation is completed, your device stays connected to the web. If any change is made on the web, the updated information will appear on your device and automatically will begin synchronisation, and vice versa.</p> <p data-bbox="583 1190 1102 1320">  To synchronise with the Google web server, you must have a Google account. If you do not have a Google account, sign up for a Google account by selecting Create on the first setup screen. </p> </div> <div data-bbox="1144 898 1661 1271"> <p data-bbox="1144 898 1455 930">Activate automatic sync</p> <p data-bbox="1144 946 1661 1044">If you add or edit data in any of the applications (Google Mail, Calendar, and Contacts) on the web, the updated information will appear on your device, and vice versa.</p> <ol data-bbox="1144 1060 1661 1190" style="list-style-type: none"> 1. From the Home screen, open the application list and select Settings → Data synchronization. 2. Select Auto-sync. 3. Select the applications you want to synchronise. <p data-bbox="1144 1190 1661 1271">To exclude applications from automatic synchronisation, clear the check box next to the application you want.</p> </div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>Synchronise data manually</p> <ol style="list-style-type: none"> 1. From the Home screen, open the application list and select Settings → Data synchronization. 2. Press [] → Sync now. Your device will start synchronising the data you set for synchronisation. <div> <div> <p>Wi-Fi settings</p> <ul style="list-style-type: none"> • Wi-Fi: Turn the WLAN feature on or off. • Network notification: Set the device to notify you when an open network is available. • Add Wi-Fi network: Add WLAN networks. <p>Bluetooth</p> <p>Turn the Bluetooth wireless feature on or off.</p> <p>Bluetooth settings</p> <ul style="list-style-type: none"> • Bluetooth: Turn the Bluetooth wireless feature on or off. • Device name: Set a Bluetooth name for your device. • Discoverable: Set your device to be visible to other Bluetooth devices. • Scan for devices: Search for available Bluetooth devices. <p><u>JuiceDefender App</u></p> </div> <div> <p>Mobile networks</p> <ul style="list-style-type: none"> • Data roaming: Set the device to connect another network when you are roaming or your home network is not available. • Use only 2G networks: Set the device to connect only to a 2G network. • Network operators: Search for available networks and select a network for roaming. • Access Point Names: Set up access point names (APNs). <p>Airplane mode</p> <p>Disable all wireless functions on your device.</p> </div> </div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>SAMSUNG_PRIORART0000379 (Latedroid):</p> <div data-bbox="646 418 1008 479" data-label="Section-Header"> <h2>JuiceDefender</h2> </div> <div data-bbox="646 500 1129 1214" data-label="Image"> </div> <div data-bbox="1129 500 1717 592" data-label="Text"> <p>JuiceDefender saves battery power (<i>lots of it!</i>) by controlling the device data connection and/or WiFi.</p> </div> <div data-bbox="1129 625 1390 928" data-label="Text"> <p>You can schedule regular APN/WiFi activation to let background data sync occur and have APN/WiFi enabled while the screen is on. It also helps in minimizing distractions ;)</p> </div> <div data-bbox="1411 625 1717 922" data-label="Image"> </div> <div data-bbox="1129 1019 1717 1144" data-label="Text"> <p>The <i>Easy Mode</i> is a no-fuss one-click way to let your battery last longer - much longer. Just enable JuiceDefender by clicking on the big button and you're ready to go!</p> </div> <div data-bbox="1129 1172 1684 1234" data-label="Text"> <p>If you want more fine-grained control, try <i>Advanced Mode</i>, where you can configure all</p> </div> <p data-bbox="646 1230 1102 1263">JuiceDefender features to your liking.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>There are 5 <i>triggers</i> for the enable/disable behaviour:</p> <p>Battery - when battery level gets low (less than 15%), disable APN/WiFi, and re-enable them when battery level is restored. APN/WiFi will also be enabled while the device is being recharged.</p> <p>Schedule - regularly enable APN/WiFi for a short period of time, to <i>let background data sync</i> occur (email, Twitter, Facebook, stock quotes...). If <i>Quick</i> is disabled APN/WiFi stays enabled for a longer period, useful if your data connection is very slow or you need to sync lots of data.</p> <p>Night schedule (requires <i>UltimateJuice</i>) - disable APN/WiFi during night time; you can also optionally put the phone in Silent Mode.</p> <p>Screen - enable APN/WiFi <i>while the screen is on</i> to allow browsing, tweeting, procrastination and general internet-powered enjoyment, regardless of scheduled events and battery level.</p> <p>Location (requires <i>UltimateJuice</i>) - this trigger controlled by the <i>'AutoWiFi'</i> button. It disables WiFi when the device is not in range of any known WiFi network. The location is determined via the cellular network, so it's usually quite coarse. It's a fully automatic set-it-and-forget-it WiFi manager!</p> <p>The <i>priority order</i> of the triggers is 1) location (WiFi only), 2) screen, 3) battery, 4) night schedule, 5) schedule - this means, for example, that when the screen is on APN/WiFi will be enabled even when the battery is low, or that the regular schedule won't occur during the night period.</p> <p>SAMSUNG_PRIORART0000361 (Purdy):</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<div data-bbox="577 321 1186 938"> </div> <p data-bbox="1207 326 1785 459">Android: Most phones don't make it easy to switch cellular data connection on and off, even if doing so really helps save your battery. JuiceDefender toggles wireless data and Wi-Fi on and off every so often to preserve power.</p> <p data-bbox="1207 505 1785 963">The whole point of a smartphone with Google apps baked in is constant connectivity, of course, and you don't want to shut off access to your email, Google Voice messages, and other online services. But when you're walking around, at your office desk, and generally not actively using your phone, you probably don't need your phone to check in every minute with the mothership. JuiceDefender lets you set a time interval—5 minutes, 15, 30, an hour, two hours—at which its background process will re-enable your carrier APN, see if there are new messages or data coming in, and then shut off again. You can also set similar Wi-Fi connectivity rules, or only have web data enabled when you've got your screen on. Besides the battery savings,</p> <p data-bbox="577 976 1680 1000">those who like to parse out their email checks and avoid minute-by-minute distractions see some benefit here, too.</p> <p data-bbox="577 1068 1495 1101"><i>See, e.g.,</i> SAMSUNG_PRIORART0000351 (Configuration-Translated):</p> <div data-bbox="577 1138 1381 1183"> <p>Schedule Enable APN for 5m every 30m</p> </div> <p data-bbox="556 1227 1864 1334">“• Schedule: used to configure how often Juice Defender will activate the APN / WIFI to synchronize emails, social networks, etc ..., we select the interval in the bar of your submenu for example 5 minutes every half hour also has the Quick button to minimize the connection time for the previous example</p>

Exhibit G-10 to Defendants’ Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>would be 2 minutes every half hour, I recommend not using this option if the selected time period is too short, it may not give you time to connect.”</p> <p><i>See, e.g., SAMSUNG_PRIORART0000361 (Purdy):</i></p> <p>Schedule Enable APN+MMS 2m every 15m</p> <p>“JuiceDefender lets you set a time interval—5 minutes, 15, 30, an hour, two hours— at which its background process will re-enable your carrier APN, see if there are new messages or data coming in, and then shut off again.”</p> <p><i>See, e.g., SAMSUNG_PRIORART0000335 (Ruddock):</i></p> <p>Schedule Enable Data/WiFi for 1m every 15m</p> <p><u>GreenPower App</u></p> <p>POUZERATE0000196 (GreenPower User Guide) (“Manage Wifi</p> <p>If this setting is selected, then Green Power will regularly turn on and off the Wifi connection, based on the durations specified in the settings below.</p> <p>If this setting is not selected, then Green Power will leave the Wifi as it is, never turning it on or off.</p> <p>Please note that if you manually switches off the Wifi, then Green Power will unselect the “Manage Wifi” setting in order not to automatically switch on the Wifi again despite your manual action. Then, if you switch back on the Wifi or reselect “Manage Wifi” setting, Green Power will resume managing Wifi connection.</p> <p>Manage Mobile Network</p>

Exhibit G-10 to Defendants’ Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>If this setting is selected, then Green Power will regularly turn on and off the Mobile Network connection, based on the durations specified in the settings below.</p> <p>If this setting is not selected, then Green Power will leave the Mobile Network as it is, never turning it on or off.</p> <p>Please note that in order for Green Power to turn on / off Mobile Network, this one has to be manually enabled by the user first in the phone settings (Wireless & networks → Mobile Network) or in Green Power settings (Global wireless settings → Mobile Network) . Green Power can't itself turn on Mobile Network as this is a limitation of the Android system for security and cost reasons.”).</p> <p>POUZERATE0000196 (GreenPower User Guide) (“Global Wireless settings This is a shortcut to the phone system wireless settings where the user can find the setting “Mobile Network”. That one should be checked or Green Power won't be able to properly manage Mobile Network.</p> <p>Screen off wireless delay This setting defines how long Green Power should wait before switching off wireless when the screen is turned off. Delaying turning off wireless is useful for instance if the user is reading something on the screen, not touching it. At some point the screen might turns off and you will touch it or press some buttons to switch it on again. Therefore, the wireless shouldn't be interrupted here. So, instead of switching off the wireless at once when the screen turns off, Green Power will wait that this delay elapses before switching off the wireless.</p> <p>Wireless on delay This setting defines how long Green Power keeps the wireless on before turning it off again. This applies to the Wifi is the setting “Manage Wifi” is selected, and this applies to the Mobile Network if the setting “Manage Mobile Network” is selected.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>Wireless off delay This setting defines how long Green Power keeps the wireless off before turning it on again. This applies to the Wifi is the setting “Manage Wifi” is selected, and this applies to the Mobile Network if the setting “Manage Mobile Network” is selected.</p> <p>Screen on setting If this is selected, the wireless will be kept on when the screen is on. This applies to the Wifi is the setting “Manage Wifi” is selected, and this applies to the Mobile Network if the setting “Manage Mobile Network” is selected.</p> <p>If this is not selected, then Green Power will not make any difference whether the screen is on or off:: It will regularly switch on and off wireless if needed even if the screen is on. This can be useful if the you are using the phone for anything else than using wireless data (calling, playing local game, etc). In such a case you don't need the wireless to be always on.</p> <p>Power on setting If this is selected, the wireless will be kept on when the phone is connected to a power source. This applies to the Wifi is the setting “Manage Wifi” is selected, and this applies to the Mobile Network if the setting “Manage Mobile Network” is selected.</p> <p>This overrides the “Screen on setting”: If this is selected and the power is connected, then wireless will be kept on whatever the screen state is.</p> <p>If this is not selected, then Green Power will not make any difference whether the phone is connected to the power or not:: It will regularly switch on and off wireless if needed.</p> <p>Check Traffic If this is selected, then prior to turning off wireless, Green Power will check that there is no network traffic. If there is, it will wait a few seconds and checks again until there is no traffic anymore.”)</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
<p>[1c] one or more processors configured to access the network service activity control policy set, determine whether to apply the one or more Internet activity access controls with respect to a first Internet access request by or on behalf of the first end-user application, based at least on which of the plurality of wireless network types is to provide data communication for Internet access requests, and when the one or more Internet activity access controls are to be applied, apply the one or more Internet activity access controls to aggregate network activity for the first Internet access request with network activity for one or more other data</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1b].</p> <p><u>HTC Dream / T-Mobile G1</u></p> <p>SAMSUNG_PRIORART0005202</p> <div style="display: flex; align-items: flex-start;"> <div style="flex: 1;"> <p>Mobile network settings</p> </div> <div style="flex: 2;"> <ul style="list-style-type: none"> • Select data roaming capability. • Select to connect only to 2G (slower) networks to save battery power. • Select a wireless operator network - Scan for all available networks, or select a network automatically. • Add or edit network Access Point Names (APNs) - Do not change this setting unless advised to do so by your wireless operator! </div> </div> <p><i>See also</i> GOOG-HEADWATER-000000001-123.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
communication requests, which are otherwise not associated with the first end-user application, before allowing network activity in association with the first Internet access request.	
[2a] The wireless end-user device of claim 1, wherein the first end-user application is capable of both interacting with a user in a user interface foreground of the device, and at least some Internet service activities when not interacting with a user in the device user interface foreground,	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c].</p> <p><u>HTC Dream / T-Mobile G1</u></p> <p>SAMSUNG_PRIORART0005260</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p data-bbox="575 370 814 428">Answer incoming, hold call in progress</p> <p data-bbox="850 370 1381 396">The incoming call will display in the foreground.</p> <div data-bbox="850 407 1115 776">  </div> <p data-bbox="850 789 1654 886">Press CALL to answer the incoming call and place the call in progress on hold. You can also press MENU and select Hold call in progress & answer.</p> <p data-bbox="850 899 1566 925">To switch calls at any time, press MENU and select Switch calls.</p> <p data-bbox="554 980 1877 1045"><i>See also</i> Android Developers Blog_Multitasking the Android Way, GOOG-HEADWATER-00000025-27</p> <p data-bbox="592 1104 1587 1263">A key to how Android handles applications in this way is that processes don't shut down cleanly. When the user leaves an application, its process is kept around in the background, allowing it to continue working (for example downloading web pages) if needed, and come immediately to the foreground if the user returns to it. If a device never runs out of memory, then Android will keep all of these processes around, truly leaving all applications "running" all of the time.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>Explicitly running in the background</p> <p>So far, we have a way for applications to implicitly do work in the background, as long as the process doesn't get killed by Android as part of its regular memory management. This is fine for things like loading web pages in the background, but what about features with harder requirements? Background music playback, data synchronization, location tracking, alarm clocks, etc.</p> <p>For these tasks, the application needs a way to tell Android "I would explicitly like to run at this point." There are two main facilities available to applications for this, represented by two kinds of components they can publish in their manifest: <i>broadcast receivers</i> and <i>services</i>.</p> <p>Broadcast Receivers</p> <p>A BroadcastReceiver allows an application to run, for a brief amount of time, in the background as a result of something else happening. It can be used in many ways to build higher-level facilities: for example the AlarmManager allows an application to have a broadcast sent at a certain time in the future, and the LocationManager can send a broadcast when it detects interesting changes in location. Because information about the receiver is part of an application's manifest, Android can find and launch the application even if it isn't running; of course if it already has its process available in the background, the broadcast can very efficiently be directly dispatched to it.</p> <p>When handling a broadcast, the application is given a fixed set of time (currently 10 seconds) in which to do its work. If it doesn't complete in that time, the application is considered to be misbehaving, and its process immediately tossed into the background state to be killed for memory if needed.</p> <p>Broadcast receivers are great for doing small pieces of work in response to an external stimulus, such as posting a notification to the user after being sent a new GPS location report. They are very lightweight, since the application's process only needs to be around while actively receiving the broadcast. Because they are active for a deterministic amount of time, fairly strong guarantees can be made about not killing their process while running. However they are not appropriate for anything of indeterminate length, such as networking.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p data-bbox="562 313 699 345">Services</p> <p data-bbox="562 391 1514 521">A Service allows an application to implement longer-running background operations. There are actually a lot of other functions that services provide, but for the discussion here their fundamental purpose is for an application to say "hey I would like to continue running even while in the background, until I say I am done." An application controls when its service runs by explicitly starting and stopping the service.</p> <p data-bbox="562 548 1524 727">While services do provide a rich client-server model, its use is optional. Upon starting an application's services, Android simply instantiates the component in the application's process to provide its context. How it is used after that is up to the application: it can put all of the needed code inside of the service itself without interacting with other parts of the application, make calls on other singleton objects shared with other parts of the app, directly retrieve the Service instance from elsewhere if needed, or run it in another process and do a full-blown RPC protocol if that is desired.</p> <p data-bbox="562 755 1518 857">Process management for services is different than broadcast receivers, because an unbounded number of services can ask to be running for an unknown amount of time. There may not be enough RAM to have all of the requesting services run, so as a result no strong guarantees are made about being able to keep them running.</p> <p data-bbox="562 885 1514 1040">If there is too little RAM, processes hosting services will be immediately killed like background processes are. However, if appropriate, Android will remember that these services wish to remain running, and restart their process at a later time when more RAM is available. For example, if the user goes to a web page that requires large amounts of RAM, Android may kill background service processes like sync until the browser's memory needs go down.</p> <p data-bbox="562 1068 1509 1247">Services can further negotiate this behavior by requesting they be considered "foreground." This places the service in a "please don't kill" state, but requires that it include a notification to the user about it actively running. This is useful for services such as background music playback or car navigation, which the user is actively aware of; when you're playing music and using the browser, you can always see the music-playing glyph in the status bar. Android won't try to kill these services, but as a trade-off, ensures the user knows about them and is able to explicitly stop them when desired.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>The value of generic components</p> <p>Android's generic broadcast receiver and service components allow developers to create a wide variety of efficient background operations, including things that were never originally considered. In Android 1.0 they were used to implement nearly all of the background behavior that the built-in and proprietary Google apps provided:</p> <ul style="list-style-type: none">• Music playback runs in a service to allow it to continue operating after the user leaves the music application.• The alarm clock schedules a broadcast receiver with the alarm manager, to go off at the next set alarm time.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> • The calendar application likewise schedules an alarm to display or update its notification at the appropriate time for the next calendar event. • Background file download is implemented a service that runs when there are any downloads to process. • The e-mail application schedules an alarm to wake up a service at regular intervals that looks for and retrieves any new mail. • The Google applications maintain a service to receive push notifications from the network; it in turn sends broadcasts to individual apps when it is told that they need to do things like synchronize contacts. <p>As the platform has evolved, these same basic components have been used to implement many of the major new developer features:</p> <ul style="list-style-type: none"> • Input methods are implemented by developers as a Service component that Android manages and works with to display as the current IME. • Application widgets are broadcast receivers that Android sends broadcasts to when it needs to interact with them. This allows app widgets to be quite lightweight, by not needing their application's process remain running. • Accessibility features are implemented as services that Android keeps running while in use and sends appropriate information to about user interactions. • Sync adapters introduced in Android 2.0 are services that are run in the background when a particular data sync needs to be performed. • Live wallpapers are a service started by Android when selected by the user. <p><u>Android 1.0</u></p> <p><u>SAMSUNG PRIORART0005487, Activity</u></p> <p>* <p>Activities in the system are managed as an activity stack.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* When a new activity is started, it is placed on the top of the stack</p> <p>* and becomes the running activity -- the previous activity always remains</p> <p>* below it in the stack, and will not come to the foreground again until</p> <p>* the new activity exits.</p></p> <p>* <p>An activity has essentially four states:</p></p> <p>* </p> <p>* If an activity in the foreground of the screen (at the top of</p> <p>* the stack),</p> <p>* it is active or running. </p> <p>* If an activity has lost focus but is still visible (that is, a new non-full-sized</p> <p>* or transparent activity has focus on top of your activity), it</p> <p>* is paused. A paused activity is completely alive (it</p> <p>* maintains all state and member information and remains attached to</p> <p>* the window manager), but can be killed by the system in extreme</p> <p>* low memory situations.</p> <p>* If an activity is completely obscured by another activity,</p> <p>* it is stopped. It still retains all state and member information,</p> <p>* however, it is no longer visible to the user so its window is hidden</p> <p>* and it will often be killed by the system when memory is needed</p> <p>* elsewhere.</p> <p>* If an activity is paused or stopped, the system can drop the activity</p> <p>* from memory by either asking it to finish, or simply killing its</p> <p>* process. When it is displayed again to the user, it must be</p> <p>* completely restarted and restored to its previous state.</p> <p>* </p> <p>* <p>The following diagram shows the important state paths of an Activity.</p> <p>* The square rectangles represent callback methods you can implement to</p> <p>* perform operations when the Activity moves between states. The colored</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* ovals are major states the Activity can be in.</p> * * <p></p> <p></p> <p>* The entire lifetime of an activity happens between the first call</p> <p>* to { @link android.app.Activity#onCreate } through to a single final call</p> <p>* to { @link android.app.Activity#onDestroy }. An activity will do all setup</p> <p>* of "global" state in onCreate(), and release all remaining resources in</p> <p>* onDestroy(). For example, if it has a thread running in the background</p> <p>* to download data from the network, it may create that thread in onCreate()</p> <p>* and then stop the thread in onDestroy().</p> <p>*</p> <p>* The visible lifetime of an activity happens between a call to</p> <p>* { @link android.app.Activity#onStart } until a corresponding call to</p> <p>* { @link android.app.Activity#onStop }. During this time the user can see the</p> <p>* activity on-screen, though it may not be in the foreground and interacting</p> <p>* with the user. Between these two methods you can maintain resources that</p> <p>* are needed to show the activity to the user. For example, you can register</p> <p>* a { @link android.content.BroadcastReceiver } in onStart() to monitor for changes</p> <p>* that impact your UI, and unregister it in onStop() when the user an no</p> <p>* longer see what you are displaying. The onStart() and onStop() methods</p> <p>* can be called multiple times, as the activity becomes visible and hidden</p> <p>* to the user.</p> <p>*</p> <p>* The foreground lifetime of an activity happens between a call to</p> <p>* { @link android.app.Activity#onResume } until a corresponding call to</p> <p>* { @link android.app.Activity#onPause }. During this time the activity is</p> <p>* in front of all other activities and interacting with the user. An activity</p> <p>* can frequently go between the resumed and paused states -- for example when</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps												
	<ul style="list-style-type: none"> * the device goes to sleep, when an activity result is delivered, when a new intent is delivered -- so the code in these methods should be fairly lightweight. <p>The entire lifecycle of an activity is defined by the following Activity methods. All of these are hooks that you can override to do appropriate work when the activity changes state. All activities will implement { @link android.app.Activity#onCreate } to do their initial setup; many will also implement { @link android.app.Activity#onPause } to commit changes to data and otherwise prepare to stop interacting with the user. You should always call up to your superclass when implementing these methods.</p> <table border="1"> <thead> <tr> <th colspan="2">{ @link android.app.Activity#onStop onStop() }</th> </tr> </thead> <tbody> <tr> <td>* Called when the activity is no longer visible to the user, because another activity has been resumed and is covering this one. This may happen either because a new activity is being started, an existing one is being brought in front of this one, or this one is being destroyed.</td> <td></td> </tr> <tr> <td>* Followed by either <code>onRestart()</code> if this activity is coming back to interact with the user, or <code>onDestroy()</code> if this activity is going away.</td> <td></td> </tr> <tr> <td>* Yes</td> <td></td> </tr> <tr> <td>* <code>onRestart()</code> or</td> <td></td> </tr> <tr> <td>* <code>onDestroy()</code></td> <td></td> </tr> </tbody> </table>	{ @link android.app.Activity#onStop onStop() }		* Called when the activity is no longer visible to the user, because another activity has been resumed and is covering this one. This may happen either because a new activity is being started, an existing one is being brought in front of this one, or this one is being destroyed.		* Followed by either <code>onRestart()</code> if this activity is coming back to interact with the user, or <code>onDestroy()</code> if this activity is going away.		* Yes		* <code>onRestart()</code> or		* <code>onDestroy()</code>	
{ @link android.app.Activity#onStop onStop() }													
* Called when the activity is no longer visible to the user, because another activity has been resumed and is covering this one. This may happen either because a new activity is being started, an existing one is being brought in front of this one, or this one is being destroyed.													
* Followed by either <code>onRestart()</code> if this activity is coming back to interact with the user, or <code>onDestroy()</code> if this activity is going away.													
* Yes													
* <code>onRestart()</code> or													
* <code>onDestroy()</code>													

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* <p>The Android system attempts to keep application process around for as * long as possible, but eventually will need to remove old processes when * memory runs low. As described in Activity * Lifecycle, the decision about which process to remove is intimately * tied to the state of the user's interaction with it. In general, there * are four states a process can be in based on the activities running in it, * listed here in order of importance. The system will kill less important * processes (the last ones) before it resorts to killing more important * processes (the first ones).</p> <p>* * * <p>The foreground activity (the activity at the top of the screen * that the user is currently interacting with) is considered the most important. * Its process will only be killed as a last resort, if it uses more memory * than is available on the device. Generally at this point the device has * reached a memory paging state, so this is required in order to keep the user * interface responsive.</p> * <p>A visible activity (an activity that is visible to the user * but not in the foreground, such as one sitting behind a foreground dialog) * is considered extremely important and will not be killed unless that is * required to keep the foreground activity running. * <p>A background activity (an activity that is not visible to * the user and has been paused) is no longer critical, so the system may * safely kill its process to reclaim memory for other foreground or * visible processes. If its process needs to be killed, when the user navigates * back to the activity (making it visible on the screen again), its * { @link #onCreate } method will be called with the savedInstanceState it had previously * supplied in { @link #onSaveInstanceState } so that it can restart itself in the same

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* state as the user last left it.</p> <p>* <p>An empty process is one hosting no activities or other</p> <p>* application components (such as { @link Service } or</p> <p>* { @link android.content.BroadcastReceiver } classes). These are killed very</p> <p>* quickly by the system as memory becomes low. For this reason, any</p> <p>* background operation you do outside of an activity must be executed in the</p> <p>* context of an activity BroadcastReceiver or Service to ensure that the system</p> <p>* knows it needs to keep your process around.</p> <p>* </p> <p>*</p> <p> </p> <p>/**</p> <p>* Called as part of the activity lifecycle when an activity is going into</p> <p>* the background, but has not (yet) been killed. The counterpart to</p> <p>* { @link #onResume }.</p> <p>*</p> <p>* <p>When activity B is launched in front of activity A, this callback will</p> <p>* be invoked on A. B will not be created until A's { @link #onPause } returns,</p> <p>* so be sure to not do anything lengthy here.</p> <p>*</p> <p>* <p>This callback is mostly used for saving any persistent state the</p> <p>* activity is editing, to present a "edit in place" model to the user and</p> <p>* making sure nothing is lost if there are not enough resources to start</p> <p>* the new activity without first killing this one. This is also a good</p> <p>* place to do things like stop animations and other things that consume a</p> <p>* noticeable mount of CPU in order to make the switch to the next activity</p> <p>* as fast as possible, or to close resources that are exclusive access</p> <p>* such as the camera.</p> <p>*</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* <p>In situations where the system needs more memory it may kill paused * processes to reclaim resources. Because of this, you should be sure * that all of your state is saved by the time you return from * this function. In general { @link #onSaveInstanceState } is used to save * per-instance state in the activity and this method is used to store * global persistent data (in content providers, files, etc.) * * <p>After receiving this call you will usually receive a following call * to { @link #onStop } (after the next activity has been resumed and * displayed), however in some cases there will be a direct call back to * { @link #onResume } without going through the stopped state. * * <p>Derived classes must call through to the super class's * implementation of this method. If they do not, an exception will be * thrown.</p> * * @see #onResume * @see #onSaveInstanceState * @see #onStop * /</p> <p><u>SAMSUNG PRIORART0005487, ActivityManager</u></p> <p>/** * Return a list of the tasks that are currently running, with * the most recent being first and older ones after in order. Note that * "running" does not mean any of the task's code is currently loaded or * activity -- the task may have been frozen by the system, so that it * can be restarted in its previous state when next brought to the * foreground.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * * @param maxNum The maximum number of entries to return in the list. The * actual number returned may be smaller, depending on how many tasks the * user has started. * * @return Returns a list of RunningTaskInfo records describing each of * the running tasks. * * @throws SecurityException Throws SecurityException if the caller does * not hold the { @link android.Manifest.permission#GET_TASKS} permission. */ public List<RunningTaskInfo> getRunningTasks(int maxNum) throws SecurityException { try { return (List<RunningTaskInfo>)ActivityManagerNative.getDefault() .getTasks(maxNum, 0, null); } catch (RemoteException e) { // System dead, we will be dead too soon! return null; } } /** * Set to true if the service has asked to run as a foreground process. */ public boolean foreground; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p data-bbox="554 316 701 345"><u>Android 1.6</u></p> <p data-bbox="554 435 1144 464"><u>SAMSUNG_PRIORART0005350, Fundamentals.jd</u></p> <p data-bbox="554 532 669 561">Activities</p> <p data-bbox="653 591 1881 850">An <i>activity</i> presents a visual user interface for one focused endeavor the user can undertake. For example, an activity might present a list of menu items users can choose from or it might display photographs along with their captions. A text messaging application might have one activity that shows a list of contacts to send messages to, a second activity to write the message to the chosen contact, and other activities to review old messages or change settings. Though they work together to form a cohesive user interface, each activity is independent of the others. Each one is implemented as a subclass of the {@link android.app.Activity} base class.</p> <p data-bbox="653 880 1892 1058">An application might consist of just one activity or, like the text messaging application just mentioned, it may contain several. What the activities are, and how many there are depends, of course, on the application and its design. Typically, one of the activities is marked as the first one that should be presented to the user when the application is launched. Moving from one activity to another is accomplished by having the current activity start the next one.</p> <p data-bbox="653 1065 1871 1243">Each activity is given a default window to draw in. Typically, the window fills the screen, but it might be smaller than the screen and float on top of other windows. An activity can also make use of additional windows — for example, a pop-up dialog that calls for a user response in the midst of the activity, or a window that presents users with vital information when they select a particular item on-screen.</p> <p data-bbox="653 1250 1881 1422">The visual content of the window is provided by a hierarchy of views — objects derived from the base {@link android.view.View} class. Each view controls a particular rectangular space within the window. Parent views contain and organize the layout of their children. Leaf views (those at the bottom of the hierarchy) draw in the rectangles they control and respond to user actions directed at that space. Thus, views are where the activity's interaction with the user takes</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>place. For example, a view might display a small image and initiate an action when the user taps that image. Android has a number of ready-made views that you can use — including buttons, text fields, scroll bars, menu items, check boxes, and more.</p> <p>A view hierarchy is placed within an activity's window by the <code>{@link android.app.Activity#setContentView Activity.setContentView() }</code> method. The <i>content view</i> is the View object at the root of the hierarchy. (See the separate User Interface document for more information on views and the hierarchy.)</p> <p>Services</p> <p>A <i>service</i> doesn't have a visual user interface, but rather runs in the background for an indefinite period of time. For example, a service might play background music as the user attends to other matters, or it might fetch data over the network or calculate something and provide the result to activities that need it. Each service extends the <code>{@link android.app.Service}</code> base class.</p> <p>A prime example is a media player playing songs from a play list. The player application would probably have one or more activities that allow the user to choose songs and start playing them. However, the music playback itself would not be handled by an activity because users will expect the music to keep playing even after they leave the player and begin something different. To keep the music going, the media player activity could start a service to run in the background. The system would then keep the music playback service running even after the activity that started it leaves the screen.</p> <p>It's possible to connect to (bind to) an ongoing service (and start the service if it's not already running). While connected, you can communicate with the service through an interface that the service exposes. For the music service, this interface might allow users to pause, rewind, stop, and restart the playback.</p> <p>Like activities and the other components, services run in the main thread of the application process. So that they won't block other components or the user interface, they often spawn another thread for time-consuming tasks (like music playback). See Processes and Threads, later.</p> <p>All the activities in a task move together as a unit. The entire task (the entire activity stack) can be brought to the foreground or sent to the background. Suppose, for instance, that the current task has</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>four activities in its stack — three under the current activity. The user presses the HOME key, goes to the application launcher, and selects a new application (actually, a new <i>task</i>). The current task goes into the background and the root activity for the new task is displayed. Then, after a short period, the user goes back to the home screen and again selects the previous application (the previous task). That task, with all four activities in the stack, comes forward. When the user presses the BACK key, the screen does not display the activity the user just left (the root activity of the previous task). Rather, the activity on the top of the stack is removed and the previous activity in the same task is displayed.</p> <p>As noted above, there's never more than one instance of a "{ @code singleTask}" or "{ @code singleInstance}" activity, so that instance is expected to handle all new intents. A "{ @code singleInstance}" activity is always at the top of the stack (since it is the only activity in the task), so it is always in position to handle the intent. However, a "{ @code singleTask}" activity may or may not have other activities above it in the stack. If it does, it is not in position to handle the intent, and the intent is dropped. (Even though the intent is dropped, its arrival would have caused the task to come to the foreground, where it would remain.)</p> <p>An activity has essentially three states:</p> <ul style="list-style-type: none"> • It is <i>active</i> or <i>running</i> when it is in the foreground of the screen (at the top of the activity stack for the current task). This is the activity that is the focus for the user's actions. • It is <i>paused</i> if it has lost focus but is still visible to the user. That is, another activity lies on top of it and that activity either is transparent or doesn't cover the full screen, so some of the paused activity can show through. A paused activity is completely alive (it maintains all state and member information and remains attached to the window manager), but can be killed by the system in extreme low memory situations. • It is <i>stopped</i> if it is completely obscured by another activity. It still retains all state and member information. However, it is no longer visible to the user so its window is hidden and it will often be killed by the system when memory is needed elsewhere. <p>Taken together, these seven methods define the entire lifecycle of an activity. There are three nested loops that you can monitor by implementing them:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps					
	<ul style="list-style-type: none">The entire lifetime of an activity happens between the first call to { @link android.app.Activity#onCreate onCreate() } through to a single final call to { @link android.app.Activity#onDestroy }. An activity does all its initial setup of "global" state in { @code onCreate() }, and releases all remaining resources in { @code onDestroy() }. For example, if it has a thread running in the background to download data from the network, it may create that thread in { @code onCreate() } and then stop the thread in { @code onDestroy() }.The visible lifetime of an activity happens between a call to { @link android.app.Activity#onStart onStart() } until a corresponding call to { @link android.app.Activity#onStop onStop() }. During this time, the user can see the activity on-screen, though it may not be in the foreground and interacting with the user. Between these two methods, you can maintain resources that are needed to show the activity to the user. For example, you can register a { @link android.content.BroadcastReceiver } in { @code onStart() } to monitor for changes that impact your UI, and unregister it in { @code onStop() } when the user can no longer see what you are displaying. The { @code onStart() } and { @code onStop() } methods can be called multiple times, as the activity alternates between being visible and hidden to the user.The foreground lifetime of an activity happens between a call to { @link android.app.Activity#onResume onResume() } until a corresponding call to { @link android.app.Activity#onPause onPause() }. During this time, the activity is in front of all other activities on screen and is interacting with the user. An activity can frequently transition between the resumed and paused states — for example, { @code onPause() } is called when the device goes to sleep or when a new activity is started, { @code onResume() } is called when an activity result or a new intent is delivered. Therefore, the code in these two methods should be fairly lightweight. <table><tr><td rowspan="2">{ @link android.app.Activity#onStart onStart() }</td><td>Called just before the activity becomes visible to the user.</td><td rowspan="2">No</td><td rowspan="2">{ @code onResume() } or { @code onStop() }</td></tr><tr><td>Followed by { @code onResume() } if the activity comes to the foreground, or { @code onStop() } if it becomes hidden.</td></tr></table>	{ @link android.app.Activity#onStart onStart() }	Called just before the activity becomes visible to the user.	No	{ @code onResume() } or { @code onStop() }	Followed by { @code onResume() } if the activity comes to the foreground, or { @code onStop() } if it becomes hidden.
{ @link android.app.Activity#onStart onStart() }	Called just before the activity becomes visible to the user.		No			{ @code onResume() } or { @code onStop() }
	Followed by { @code onResume() } if the activity comes to the foreground, or { @code onStop() } if it becomes hidden.					

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>Processes and lifecycles</p> <p>The Android system tries to maintain an application process for as long as possible, but eventually it will need to remove old processes when memory runs low. To determine which processes to keep and which to kill, Android places each process into an "importance hierarchy" based on the components running in it and the state of those components. Processes with the lowest importance are eliminated first, then those with the next lowest, and so on. There are five levels in the hierarchy. The following list presents them in order of importance:</p> <ol style="list-style-type: none"> 1. A foreground process is one that is required for what the user is currently doing. A process is considered to be in the foreground if any of the following conditions hold: <ul style="list-style-type: none"> ○ It is running an activity that the user is interacting with (the Activity object's { @link android.app.Activity#onResume onResume() } method has been called). ○ It hosts a service that's bound to the activity that the user is interacting with. ○ It has a { @link android.app.Service } object that's executing one of its lifecycle callbacks ({@link android.app.Service#onCreate onCreate()}, {@link android.app.Service#onStart onStart()}, or {@link android.app.Service#onDestroy onDestroy()}). ○ It has a { @link android.content.BroadcastReceiver } object that's executing its {@link android.content.BroadcastReceiver#onReceive onReceive()} method. <p>Only a few foreground processes will exist at any given time. They are killed only as a last resort — if memory is so low that they cannot all continue to run. Generally, at that point, the device has reached a memory paging state, so killing some foreground processes is required to keep the user interface responsive.</p> 2. A visible process is one that doesn't have any foreground components, but still can affect what the user sees on screen. A process is considered to be visible if either of the following conditions holds: <ul style="list-style-type: none"> ○ It hosts an activity that is not in the foreground, but is still visible to the user (its { @link android.app.Activity#onPause onPause() } method has been called). This may occur, for example, if the foreground activity is a dialog that allows the previous activity to be seen behind it.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>○ It hosts a service that's bound to a visible activity. A visible process is considered extremely important and will not be killed unless doing so is required to keep all foreground processes running.</p> <p>3. A service process is one that is running a service that has been started with the <code>{@link android.content.Context#startService startService() }</code> method and that does not fall into either of the two higher categories. Although service processes are not directly tied to anything the user sees, they are generally doing things that the user cares about (such as playing an mp3 in the background or downloading data on the network), so the system keeps them running unless there's not enough memory to retain them along with all foreground and visible processes.</p> <p>4. A background process is one holding an activity that's not currently visible to the user (the Activity object's <code>{@link android.app.Activity#onStop onStop() }</code> method has been called). These processes have no direct impact on the user experience, and can be killed at any time to reclaim memory for a foreground, visible, or service process. Usually there are many background processes running, so they are kept in an LRU (least recently used) list to ensure that the process with the activity that was most recently seen by the user is the last to be killed. If an activity implements its lifecycle methods correctly, and captures its current state, killing its process will not have a deleterious effect on the user experience.</p> <p>5. An empty process is one that doesn't hold any active application components. The only reason to keep such a process around is as a cache to improve startup time the next time a component needs to run in it. The system often kills these processes in order to balance overall system resources between process caches and the underlying kernel caches.</p> <p><u>SAMSUNG PRIORART0005487, Activity</u></p> <p>* <p>An activity has essentially four states:</p> * * If an activity in the foreground of the screen (at the top of the stack), it is active or running. * If an activity has lost focus but is still visible (that is, a new non-full-sized</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> * or transparent activity has focus on top of your activity), it * is paused. A paused activity is completely alive (it * maintains all state and member information and remains attached to * the window manager), but can be killed by the system in extreme * low memory situations. * If an activity is completely obscured by another activity, * it is stopped. It still retains all state and member information, * however, it is no longer visible to the user so its window is hidden * and it will often be killed by the system when memory is needed * elsewhere. * If an activity is paused or stopped, the system can drop the activity * from memory by either asking it to finish, or simply killing its * process. When it is displayed again to the user, it must be * completely restarted and restored to its previous state. * The visible lifetime of an activity happens between a call to * { @link android.app.Activity#onStart } until a corresponding call to * { @link android.app.Activity#onStop }. During this time the user can see the * activity on-screen, though it may not be in the foreground and interacting * with the user. Between these two methods you can maintain resources that * are needed to show the activity to the user. For example, you can register * a { @link android.content.BroadcastReceiver } in onStart() to monitor for changes * that impact your UI, and unregister it in onStop() when the user no * longer see what you are displaying. The onStart() and onStop() methods * can be called multiple times, as the activity becomes visible and hidden * to the user. * * The foreground lifetime of an activity happens between a call to * { @link android.app.Activity#onResume } until a corresponding call to

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* { @link android.app.Activity#onPause}. During this time the activity is</p> <p>* in front of all other activities and interacting with the user. An activity</p> <p>* can frequently go between the resumed and paused states -- for example when</p> <p>* the device goes to sleep, when an activity result is delivered, when a new</p> <p>* intent is delivered -- so the code in these methods should be fairly</p> <p>* lightweight.</p> <p>* </p> <p>* <p>Here is an excerpt from a calendar activity that stores the user's</p> <p>* preferred view mode in its persistent settings:</p></p> <p>* <pre class="prettyprint"></p> <p>* public class CalendarActivity extends Activity {</p> <p>* ...</p> <p>* static final int DAY_VIEW_MODE = 0;</p> <p>* static final int WEEK_VIEW_MODE = 1;</p> <p></p> <p>* <p>The foreground activity (the activity at the top of the screen</p> <p>* that the user is currently interacting with) is considered the most important.</p> <p>* Its process will only be killed as a last resort, if it uses more memory</p> <p>* than is available on the device. Generally at this point the device has</p> <p>* reached a memory paging state, so this is required in order to keep the user</p> <p>* interface responsive.</p> <p>* <p>A visible activity (an activity that is visible to the user</p> <p>* but not in the foreground, such as one sitting behind a foreground dialog)</p> <p>* is considered extremely important and will not be killed unless that is</p> <p>* required to keep the foreground activity running.</p> <p>* <p>A background activity (an activity that is not visible to</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* the user and has been paused) is no longer critical, so the system may</p> <p>* safely kill its process to reclaim memory for other foreground or</p> <p>* visible processes. If its process needs to be killed, when the user navigates</p> <p>* back to the activity (making it visible on the screen again), its</p> <p>* { @link #onCreate } method will be called with the savedInstanceState it had previously</p> <p>* supplied in { @link #onSaveInstanceState } so that it can restart itself in the same</p> <p>* state as the user last left it.</p> <p>* <p>An empty process is one hosting no activities or other</p> <p>* application components (such as { @link Service } or</p> <p>* { @link android.content.BroadcastReceiver } classes). These are killed very</p> <p>* quickly by the system as memory becomes low. For this reason, any</p> <p>* background operation you do outside of an activity must be executed in the</p> <p>* context of an activity BroadcastReceiver or Service to ensure that the system</p> <p>* knows it needs to keep your process around.</p> <p>* </p> <p>* <p>Sometimes an Activity may need to do a long-running operation that exists</p> <p>* independently of the activity lifecycle itself. An example may be a camera</p> <p>* application that allows you to upload a picture to a web site. The upload</p> <p>* may take a long time, and the application should allow the user to leave</p> <p>* the application while it is executing. To accomplish this, your Activity</p> <p>* should start a { @link Service } in which the upload takes place. This allows</p> <p>* the system to properly prioritize your process (considering it to be more</p> <p>* important than other non-visible applications) for the duration of the</p> <p>* upload, independent of whether the original activity is paused, stopped,</p> <p>* or finished.</p> <p>* /</p> <p><u>SAMSUNG PRIORART0005350, ActivityManager</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Return a list of the tasks that the user has recently launched, with * the most recent being first and older ones after in order. * * @param maxNum The maximum number of entries to return in the list. The * actual number returned may be smaller, depending on how many tasks the * user has started and the maximum number the system can remember. * * @return Returns a list of RecentTaskInfo records describing each of * the recent tasks. * * @throws SecurityException Throws SecurityException if the caller does * not hold the {@link android.Manifest.permission#GET_TASKS} permission. */ public List<RecentTaskInfo> getRecentTasks(int maxNum, int flags) throws SecurityException { try { </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> return ActivityManagerNative.getDefault().getRecentTasks(maxNum, flags); } catch (RemoteException e) { // System dead, we will be dead too soon! return null; } }</pre> <p>/**</p> <ul style="list-style-type: none">* Return a list of the tasks that are currently running, with* the most recent being first and older ones after in order. Note that* "running" does not mean any of the task's code is currently loaded or* activity -- the task may have been frozen by the system, so that it* can be restarted in its previous state when next brought to the* foreground.** @param maxNum The maximum number of entries to return in the list. The* actual number returned may be smaller, depending on how many tasks the

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * user has started. * * @return Returns a list of RunningTaskInfo records describing each of * the running tasks. * * @throws SecurityException Throws SecurityException if the caller does * not hold the {@link android.Manifest.permission#GET_TASKS} permission. */ public List<RunningTaskInfo> getRunningTasks(int maxNum) throws SecurityException { try { return (List<RunningTaskInfo>)ActivityManagerNative.getDefault() .getTasks(maxNum, 0, null); } catch (RemoteException e) { // System dead, we will be dead too soon! return null; } } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Set to true if the service has asked to run as a foreground process. */ public boolean foreground; /** * Return a list of the services that are currently running. * * @param maxNum The maximum number of entries to return in the list. The * actual number returned may be smaller, depending on how many services * are running. * * @return Returns a list of RunningServiceInfo records describing each of * the running tasks. */ public List<RunningServiceInfo> getRunningServices(int maxNum)</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>throws SecurityException { try { return (List<RunningServiceInfo>)ActivityManagerNative.getDefault() .getServices(maxNum, 0); } catch (RemoteException e) { // System dead, we will be dead too soon! return null; } }</pre> <pre>/** * Constant for {@link #importance}: this process is running the * foreground UI. */ public static final int IMPORTANCE_FOREGROUND = 100; /** * Constant for {@link #importance}: this process is running something</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* that is considered to be actively visible to the user. */ public static final int IMPORTANCE_VISIBLE = 200; /** * Constant for {@link #importance}: this process is contains services * that should remain running. */ public static final int IMPORTANCE_SERVICE = 300; /** * Constant for {@link #importance}: this process process contains * background code that is expendable. */ public static final int IMPORTANCE_BACKGROUND = 400; /** * The relative importance level that the system places on this</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* process. May be one of {@link #IMPORTANCE_FOREGROUND}, * {@link #IMPORTANCE_VISIBLE}, {@link #IMPORTANCE_SERVICE}, * {@link #IMPORTANCE_BACKGROUND}, or {@link #IMPORTANCE_EMPTY}. These * constants are numbered so that "more important" values are always * smaller than "less important" values. * / public int importance; /** * An additional ordering within a particular {@link #importance} * category, providing finer-grained information about the relative * utility of processes within a category. This number means nothing * except that a smaller values are more recently used (and thus * more important). Currently an LRU value is only maintained for * the {@link #IMPORTANCE_BACKGROUND} category, though others may * be maintained in the future. * / public int lru;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public RunningAppProcessInfo() { importance = IMPORTANCE_FOREGROUND; } /** * Returns a list of application processes that are running on the device. * * @return Returns a list of RunningAppProcessInfo records, or null if there are no * running processes (it will not return an empty list). This list ordering is not * specified. */ public List<RunningAppProcessInfo> getRunningAppProcesses() { try { return ActivityManagerNative.getDefault().getRunningAppProcesses(); } catch (RemoteException e) { return null; } }</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p data-bbox="583 321 604 345">}</p> <p data-bbox="556 435 1201 459"><u>SAMSUNG_PRIORART0005350, ConnectivityManager</u></p> <p data-bbox="556 553 598 578">/**</p> <p data-bbox="556 613 1459 638">* Class that answers queries about the state of network connectivity. It also</p> <p data-bbox="556 673 1453 698">* notifies applications when network connectivity changes. Get an instance</p> <p data-bbox="556 734 837 758">* of this class by calling</p> <p data-bbox="556 794 1285 818">* {@link android.content.Context#getService(String)</p> <p data-bbox="556 834 1285 859">Context.getService(Context.CONNECTIVITY_SERVICE)}.</p> <p data-bbox="556 894 630 919">* <p></p> <p data-bbox="556 954 1140 979">* The primary responsibilities of this class are to:</p> <p data-bbox="556 1015 636 1039">* </p> <p data-bbox="556 1075 1339 1099">* Monitor network connections (Wi-Fi, GPRS, UMTS, etc.)</p> <p data-bbox="556 1135 1383 1159">* Send broadcast intents when network connectivity changes</p> <p data-bbox="556 1195 1505 1219">* Attempt to "fail over" to another network when connectivity to a network</p> <p data-bbox="556 1255 705 1279">* is lost</p> <p data-bbox="556 1315 1604 1339">* Provide an API that allows applications to query the coarse-grained or fine-grained</p> <p data-bbox="556 1375 1003 1399">* state of the available networks</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* */ @SdkConstant(SdkConstantType.BROADCAST_INTENT_ACTION) public static final String ACTION_BACKGROUND_DATA_SETTING_CHANGED = "android.net.conn.BACKGROUND_DATA_SETTING_CHANGED"; public static final int TYPE_MOBILE = 0; public static final int TYPE_WIFI = 1; public static final int DEFAULT_NETWORK_PREFERENCE = TYPE_WIFI; static public boolean isNetworkTypeValid(int networkType) { return networkType == TYPE_WIFI networkType == TYPE_MOBILE; } public void setNetworkPreference(int preference) { try {</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>mService.setNetworkPreference(preference); } catch (RemoteException e) { } } /** {@hide} */ public boolean setRadio(int networkType, boolean turnOn) { try { return mService.setRadio(networkType, turnOn); } catch (RemoteException e) { return false; } } /** * Returns the value of the setting for background data usage. If false, * applications should not use the network if the application is not in the * foreground. Developers should respect this setting, and check the value</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* of this before performing any background data operations.</p> <p>* <p></p> <p>* All applications that have background services that use the network</p> <p>* should listen to {@link #ACTION_BACKGROUND_DATA_SETTING_CHANGED}.</p> <p>*</p> <p>* @return Whether background data usage is allowed.</p> <p>*/</p> <pre>public boolean getBackgroundDataSetting() { try { return mService.getBackgroundDataSetting(); } catch (RemoteException e) { // Err on the side of safety return false; } }</pre> <p>/**</p> <p>* Sets the value of the setting for background data usage.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* * @param allowBackgroundData Whether an application should use data while * it is in the background. * * @attr ref android.Manifest.permission#CHANGE_BACKGROUND_DATA_SETTING * @see #getBackgroundDataSetting() * @hide */ public void setBackgroundDataSetting(boolean allowBackgroundData) { try { mService.setBackgroundDataSetting(allowBackgroundData); } catch (RemoteException e) { } }</pre> <p><u>SAMSUNG_PRIORART0005350, ConnectivityService</u></p> <p>/*</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * Create the network state trackers for Wi-Fi and mobile * data. Maybe this could be done with a factory class, * but it's not clear that it's worth it, given that * the number of different network types is not going * to change very often. */ if (DBG) Log.v(TAG, "Starting Wifi Service."); mWifiStateTracker = new WifiStateTracker(context, handler); WifiService wifiService = new WifiService(context, mWifiStateTracker); ServiceManager.addService(Context.WIFI_SERVICE, wifiService); mNetTrackers[ConnectivityManager.TYPE_WIFI] = mWifiStateTracker; mMobileDataStateTracker = new MobileDataStateTracker(context, handler); mNetTrackers[ConnectivityManager.TYPE_MOBILE] = mMobileDataStateTracker; /** * Make the state of network connectivity conform to the preference settings. </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * In this method, we only tear down a non-preferred network. Establishing * a connection to the preferred network is taken care of when we handle * the disconnect event from the non-preferred network * (see {@link #handleDisconnect(NetworkInfo)}). */ private void enforcePreference() { if (mActiveNetwork == null) return; for (NetworkStateTracker t : mNetTrackers) { if (t == mActiveNetwork) { int netType = t.getNetworkInfo().getType(); int otherNetType = ((netType == ConnectivityManager.TYPE_WIFI) ? ConnectivityManager.TYPE_MOBILE : ConnectivityManager.TYPE_WIFI); if (t.getNetworkInfo().getType() != mNetworkPreference) { NetworkStateTracker otherTracker = mNetTrackers[otherNetType]; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> if (otherTracker.isAvailable()) { teardown(t); } } } } } } } /** * @see ConnectivityManager#getBackgroundDataSetting() */ public boolean getBackgroundDataSetting() { return Settings.Secure.getInt(mContext.getContentResolver(), Settings.Secure.BACKGROUND_DATA, 1) == 1; } /** * @see ConnectivityManager#setBackgroundDataSetting(boolean)</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>*/ public void setBackgroundDataSeting(boolean allowBackgroundDataUsage) { mContext.enforceCallingOrSelfPermission(android.Manifest.permission.CHANGE_BACKGROUND_DATA_SETTING, "ConnectivityService"); if (getBackgroundDataSeting() == allowBackgroundDataUsage) return; Settings.Secure.putInt(mContext.getContentResolver(), Settings.Secure.BACKGROUND_DATA, allowBackgroundDataUsage ? 1 : 0); Intent broadcast = new Intent(ConnectivityManager.ACTION_BACKGROUND_DATA_SETTING_CHANGED); mContext.sendBroadcast(broadcast); } /**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none">* See if the other network is available to fail over to.* If is not available, we enable it anyway, so that it* will be able to connect when it does become available,* but we report a total loss of connectivity rather than* report that we are attempting to fail over.*/ <pre>NetworkInfo switchTo = null; if (newNet.isAvailable()) { mActiveNetwork = newNet; switchTo = newNet.getNetworkInfo(); switchTo.setFailover(true); if (!switchTo.isConnectedOrConnecting()) { newNet.reconnect(); } } else { newNet.reconnect(); }</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> if (info.getType() == ConnectivityManager.TYPE_MOBILE) { otherNet = mWifiStateTracker; } else /* info().getType() == TYPE_WIFI */ { otherNet = mMobileDataStateTracker; } int incrValue = ConnectivityManager.TYPE_MOBILE - ConnectivityManager.TYPE_WIFI; int stopValue = ConnectivityManager.TYPE_MOBILE + incrValue; </pre> <p><u>Android 2.2</u></p> <p><u>SAMSUNG PRIORART0005350, Fundamentals.jd</u></p> <p>Activities</p> <p>An <i>activity</i> presents a visual user interface for one focused endeavor the user can undertake. For example, an activity might present a list of menu items users can choose from or it might display photographs along with their captions. A text messaging application might have one activity that shows a list of contacts to send messages to, a second activity to write the message to the chosen contact, and other activities to review old messages or change settings. Though they work together to form a</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>cohesive user interface, each activity is independent of the others. Each one is implemented as a subclass of the {@link android.app.Activity} base class.</p> <p>An application might consist of just one activity or, like the text messaging application just mentioned, it may contain several. What the activities are, and how many there are depends, of course, on the application and its design. Typically, one of the activities is marked as the first one that should be presented to the user when the application is launched. Moving from one activity to another is accomplished by having the current activity start the next one.</p> <p>Each activity is given a default window to draw in. Typically, the window fills the screen, but it might be smaller than the screen and float on top of other windows. An activity can also make use of additional windows — for example, a pop-up dialog that calls for a user response in the midst of the activity, or a window that presents users with vital information when they select a particular item on-screen.</p> <p>The visual content of the window is provided by a hierarchy of views — objects derived from the base {@link android.view.View} class. Each view controls a particular rectangular space within the window. Parent views contain and organize the layout of their children. Leaf views (those at the bottom of the hierarchy) draw in the rectangles they control and respond to user actions directed at that space. Thus, views are where the activity's interaction with the user takes place. For example, a view might display a small image and initiate an action when the user taps that image. Android has a number of ready-made views that you can use — including buttons, text fields, scroll bars, menu items, check boxes, and more.</p> <p>A view hierarchy is placed within an activity's window by the {@link android.app.Activity#setContentView Activity.setContentView()} method.</p> <p>The <i>content view</i> is the View object at the root of the hierarchy. (See the separate User Interface document for more information on views and the hierarchy.)</p> <p>Services</p> <p>A <i>service</i> doesn't have a visual user interface, but rather runs in the background for an indefinite period of time. For example, a service might play background music as the user attends to other matters, or it</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>might fetch data over the network or calculate something and provide the result to activities that need it. Each service extends the {@link android.app.Service} base class.</p> <p>A prime example is a media player playing songs from a play list. The player application would probably have one or more activities that allow the user to choose songs and start playing them. However, the music playback itself would not be handled by an activity because users will expect the music to keep playing even after they leave the player and begin something different. To keep the music going, the media player activity could start a service to run in the background. The system would then keep the music playback service running even after the activity that started it leaves the screen.</p> <p>It's possible to connect to (bind to) an ongoing service (and start the service if it's not already running). While connected, you can communicate with the service through an interface that the service exposes. For the music service, this interface might allow users to pause, rewind, stop, and restart the playback.</p> <p>Like activities and the other components, services run in the main thread of the application process. So that they won't block other components or the user interface, they often spawn another thread for time-consuming tasks (like music playback). See Processes and Threads, later.</p> <p>All the activities in a task move together as a unit. The entire task (the entire activity stack) can be brought to the foreground or sent to the background. Suppose, for instance, that the current task has four activities in its stack — three under the current activity. The user presses the HOME key, goes to the application launcher, and selects a new application (actually, a new <i>task</i>). The current task goes into the background and the root activity for the new task is displayed. Then, after a short period, the user goes back to the home screen and again selects the previous application (the previous task). That task, with all four activities in the stack, comes forward. When the user presses the BACK key, the screen does not display the activity the user just left (the root activity of the previous task). Rather, the activity on the top of the stack is removed and the previous activity in the same task is displayed.</p> <p>As noted above, there's never more than one instance of a "{@code singleTask}" or "{@code singleInstance}" activity, so that instance is expected to handle all new intents. A "{@code</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>singleInstance}" activity is always at the top of the stack (since it is the only activity in the task), so it is always in position to handle the intent. However, a "{ @code singleTask}" activity may or may not have other activities above it in the stack. If it does, it is not in position to handle the intent, and the intent is dropped. (Even though the intent is dropped, its arrival would have caused the task to come to the foreground, where it would remain.)</p> <p>An activity has essentially three states:</p> <ul style="list-style-type: none"> • It is <i>active</i> or <i>running</i> when it is in the foreground of the screen (at the top of the activity stack for the current task). This is the activity that is the focus for the user's actions. • It is <i>paused</i> if it has lost focus but is still visible to the user. That is, another activity lies on top of it and that activity either is transparent or doesn't cover the full screen, so some of the paused activity can show through. A paused activity is completely alive (it maintains all state and member information and remains attached to the window manager), but can be killed by the system in extreme low memory situations. • It is <i>stopped</i> if it is completely obscured by another activity. It still retains all state and member information. However, it is no longer visible to the user so its window is hidden and it will often be killed by the system when memory is needed elsewhere. <p>Taken together, these seven methods define the entire lifecycle of an activity. There are three nested loops that you can monitor by implementing them:</p> <ul style="list-style-type: none"> • The entire lifetime of an activity happens between the first call to { @link android.app.Activity#onCreate onCreate()} through to a single final call to { @link android.app.Activity#onDestroy }. An activity does all its initial setup of "global" state in {@code onCreate()}, and releases all remaining resources in {@code onDestroy()}. For example, if it has a thread running in the background to download data from the network, it may create that thread in {@code onCreate()} and then stop the thread in {@code onDestroy()}. • The visible lifetime of an activity happens between a call to { @link android.app.Activity#onStart onStart()} until a corresponding call to { @link android.app.Activity#onStop onStop()}. During this time, the user can see the activity on-screen, though it may not be in the foreground and interacting with the user. Between these two

Exhibit G-10 to Defendants’ Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps								
	<p>methods, you can maintain resources that are needed to show the activity to the user. For example, you can register a { @link android.content.BroadcastReceiver} in { @code onStart()} to monitor for changes that impact your UI, and unregister it in { @code onStop()} when the user can no longer see what you are displaying. The { @code onStart()} and { @code onStop()} methods can be called multiple times, as the activity alternates between being visible and hidden to the user.</p> <ul style="list-style-type: none">• The foreground lifetime of an activity happens between a call to { @link android.app.Activity#onResume onResume() } until a corresponding call to { @link android.app.Activity#onPause onPause() }. During this time, the activity is in front of all other activities on screen and is interacting with the user. An activity can frequently transition between the resumed and paused states — for example, { @code onPause()} is called when the device goes to sleep or when a new activity is started, { @code onResume()} is called when an activity result or a new intent is delivered. Therefore, the code in these two methods should be fairly lightweight. <table><tr><td>{ @link android.app.Activity#onStart onStart() }</td><td>Called just before the activity becomes visible to the user.</td><td></td><td>{ @code onResume() }</td></tr><tr><td></td><td>Followed by { @code onResume() } if the activity comes to the foreground, or { @code onStop() } if it becomes hidden.</td><td>No</td><td>or { @code onStop() }</td></tr></table> <p>Processes and lifecycles</p> <p>The Android system tries to maintain an application process for as long as possible, but eventually it will need to remove old processes when memory runs low. To determine which processes to keep and which to kill, Android places each process into an "importance hierarchy" based on the components running in it and the state of those components. Processes with the lowest importance are eliminated first, then those with the next lowest, and so on. There are five levels in the hierarchy. The following list presents them in order of importance:</p> <ol style="list-style-type: none">6. A foreground process is one that is required for what the user is currently doing. A process is considered to be in the foreground if any of the following conditions hold:	{ @link android.app.Activity#onStart onStart() }	Called just before the activity becomes visible to the user.		{ @code onResume() }		Followed by { @code onResume() } if the activity comes to the foreground, or { @code onStop() } if it becomes hidden.	No	or { @code onStop() }
{ @link android.app.Activity#onStart onStart() }	Called just before the activity becomes visible to the user.		{ @code onResume() }						
	Followed by { @code onResume() } if the activity comes to the foreground, or { @code onStop() } if it becomes hidden.	No	or { @code onStop() }						

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> ○ It is running an activity that the user is interacting with (the Activity object's { @link android.app.Activity#onResume onResume() } method has been called). ○ It hosts a service that's bound to the activity that the user is interacting with. ○ It has a { @link android.app.Service } object that's executing one of its lifecycle callbacks ({@link android.app.Service#onCreate onCreate()}, {@link android.app.Service#onStart onStart()}, or {@link android.app.Service#onDestroy onDestroy()}). ○ It has a { @link android.content.BroadcastReceiver } object that's executing its {@link android.content.BroadcastReceiver#onReceive onReceive() } method. <p>Only a few foreground processes will exist at any given time. They are killed only as a last resort — if memory is so low that they cannot all continue to run. Generally, at that point, the device has reached a memory paging state, so killing some foreground processes is required to keep the user interface responsive.</p> <p>7. A visible process is one that doesn't have any foreground components, but still can affect what the user sees on screen. A process is considered to be visible if either of the following conditions holds:</p> <ul style="list-style-type: none"> ○ It hosts an activity that is not in the foreground, but is still visible to the user (its { @link android.app.Activity#onPause onPause() } method has been called). This may occur, for example, if the foreground activity is a dialog that allows the previous activity to be seen behind it. ○ It hosts a service that's bound to a visible activity. <p>A visible process is considered extremely important and will not be killed unless doing so is required to keep all foreground processes running.</p> <p>8. A service process is one that is running a service that has been started with the {@link android.content.Context#startService startService() } method and that does not fall into either of the two higher categories. Although service processes are not directly tied to anything the user sees, they are generally doing things that the user cares about (such as playing an mp3 in the background or downloading data on the network), so the system keeps them running unless there's not enough memory to retain them along with all foreground and visible processes.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>9. A background process is one holding an activity that's not currently visible to the user (the Activity object's {@link android.app.Activity#onStop <code>onStop()</code>} method has been called). These processes have no direct impact on the user experience, and can be killed at any time to reclaim memory for a foreground, visible, or service process. Usually there are many background processes running, so they are kept in an LRU (least recently used) list to ensure that the process with the activity that was most recently seen by the user is the last to be killed. If an activity implements its lifecycle methods correctly, and captures its current state, killing its process will not have a deleterious effect on the user experience.</p> <p>10. An empty process is one that doesn't hold any active application components. The only reason to keep such a process around is as a cache to improve startup time the next time a component needs to run in it. The system often kills these processes in order to balance overall system resources between process caches and the underlying kernel caches.</p> <p><u>SAMSUNG PRIORART0005487, Activity</u></p> <p>* <code><p></code>Activities in the system are managed as an <code>activity stack</code>. * When a new activity is started, it is placed on the top of the stack * and becomes the running activity -- the previous activity always remains * below it in the stack, and will not come to the foreground again until * the new activity exits.<code></p></code> * * <code><p></code>An activity has essentially four states:<code></p></code> * <code></code> * <code></code> If an activity in the foreground of the screen (at the top of * the stack), * it is <code>active</code> or <code>running</code>. <code></code> * <code></code> If an activity has lost focus but is still visible (that is, a new non-full-sized * or transparent activity has focus on top of your activity), it</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> * is paused. A paused activity is completely alive (it * maintains all state and member information and remains attached to * the window manager), but can be killed by the system in extreme * low memory situations. * If an activity is completely obscured by another activity, * it is stopped. It still retains all state and member information, * however, it is no longer visible to the user so its window is hidden * and it will often be killed by the system when memory is needed * elsewhere. * If an activity is paused or stopped, the system can drop the activity * from memory by either asking it to finish, or simply killing its * process. When it is displayed again to the user, it must be * completely restarted and restored to its previous state. * <p>The following diagram shows the important state paths of an Activity.</p> <p>The square rectangles represent callback methods you can implement to perform operations when the Activity moves between states. The colored ovals are major states the Activity can be in.</p> <p> alt="State diagram for an Android Activity Lifecycle." data-bbox="315 665 795 685"/></p> <p>There are three key loops you may be interested in monitoring within your activity:</p> <ul style="list-style-type: none"> * * The entire lifetime of an activity happens between the first call * to { @link android.app.Activity#onCreate } through to a single final call * to { @link android.app.Activity#onDestroy }. An activity will do all setup

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> * of "global" state in onCreate(), and release all remaining resources in * onDestroy(). For example, if it has a thread running in the background * to download data from the network, it may create that thread in onCreate() * and then stop the thread in onDestroy(). * * The visible lifetime of an activity happens between a call to { @link android.app.Activity#onStart} until a corresponding call to { @link android.app.Activity#onStop}. During this time the user can see the activity on-screen, though it may not be in the foreground and interacting with the user. Between these two methods you can maintain resources that are needed to show the activity to the user. For example, you can register a { @link android.content.BroadcastReceiver} in onStart() to monitor for changes that impact your UI, and unregister it in onStop() when the user no longer see what you are displaying. The onStart() and onStop() methods can be called multiple times, as the activity becomes visible and hidden to the user. * * The foreground lifetime of an activity happens between a call to { @link android.app.Activity#onResume} until a corresponding call to { @link android.app.Activity#onPause}. During this time the activity is in front of all other activities and interacting with the user. An activity can frequently go between the resumed and paused states -- for example when the device goes to sleep, when an activity result is delivered, when a new intent is delivered -- so the code in these methods should be fairly lightweight. * * * <tr><th colspan="2" align="left" border="0">{ @link android.app.Activity#onStart onStart()}</th>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

[illegible]

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> * that the user is currently interacting with) is considered the most important. * Its process will only be killed as a last resort, if it uses more memory * than is available on the device. Generally at this point the device has * reached a memory paging state, so this is required in order to keep the user * interface responsive. * <p>A visible activity (an activity that is visible to the user * but not in the foreground, such as one sitting behind a foreground dialog) * is considered extremely important and will not be killed unless that is * required to keep the foreground activity running. * <p>A background activity (an activity that is not visible to * the user and has been paused) is no longer critical, so the system may * safely kill its process to reclaim memory for other foreground or * visible processes. If its process needs to be killed, when the user navigates * back to the activity (making it visible on the screen again), its * { @link #onCreate } method will be called with the savedInstanceState it had previously * supplied in { @link #onSaveInstanceState } so that it can restart itself in the same * state as the user last left it. * <p>An empty process is one hosting no activities or other * application components (such as { @link Service } or * { @link android.content.BroadcastReceiver } classes). These are killed very * quickly by the system as memory becomes low. For this reason, any * background operation you do outside of an activity must be executed in the * context of an activity BroadcastReceiver or Service to ensure that the system * knows it needs to keep your process around. * * * <p>Sometimes an Activity may need to do a long-running operation that exists * independently of the activity lifecycle itself. An example may be a camera * application that allows you to upload a picture to a web site. The upload * may take a long time, and the application should allow the user to leave

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* the application will it is executing. To accomplish this, your Activity * should start a { @link Service } in which the upload takes place. This allows * the system to properly prioritize your process (considering it to be more * important than other non-visible applications) for the duration of the * upload, independent of whether the original activity is paused, stopped, * or finished. */</p> <p>/**</p> <p>* Called as part of the activity lifecycle when an activity is about to go * into the background as the result of user choice. For example, when the * user presses the Home key, { @link #onUserLeaveHint } will be called, but * when an incoming phone call causes the in-call Activity to be automatically * brought to the foreground, { @link #onUserLeaveHint } will not be called on * the activity being interrupted. In cases when it is invoked, this method * is called right before the activity's { @link #onPause } callback. *</p> <p>* <p>This callback and { @link #onUserInteraction } are intended to help * activities manage status bar notifications intelligently; specifically, * for helping activities determine the proper time to cancel a notification. *</p> <p>* @see #onUserInteraction() */</p> <p>protected void onUserLeaveHint() { } }</p> <p>* <p>As a general rule, however, a resumed activity will have window * focus... unless it has displayed other dialogs or popups that take * input focus, in which case the activity itself will not have focus * when the other windows have it. Likewise, the system may display</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* system-level windows (such as the status bar notification panel or * a system alert) which will temporarily take window input focus without * pausing the foreground activity. * * @param hasFocus Whether the window of this activity has focus. * * @see #hasWindowFocus()</p> <p>/** * Change the desired orientation of this activity. If the activity * is currently in the foreground or otherwise impacting the screen * orientation, the screen will immediately be changed (possibly causing * the activity to be restarted). Otherwise, this will be used the next * time the activity is visible. * * @param requestedOrientation An orientation constant as used in * { @link ActivityInfo#screenOrientation ActivityInfo.screenOrientation}. */ public void setRequestedOrientation(int requestedOrientation) {</p> <p><u>GOOG-HEADWATER-00000029, SAMSUNG PRIORART0005353, ConnectivityManager</u></p> <p>/** * Class that answers queries about the state of network connectivity. It also * notifies applications when network connectivity changes. Get an instance</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> * of this class by calling * {@link android.content.Context#getSystemService(String) Context.getSystemService(Context.CONNECTIVITY_SERVICE)}. * <p> * The primary responsibilities of this class are to: * * Monitor network connections (Wi-Fi, GPRS, UMTS, etc.) * Send broadcast intents when network connectivity changes * Attempt to "fail over" to another network when connectivity to a network * is lost * Provide an API that allows applications to query the coarse-grained or fine-grained * state of the available networks * * / * A change in network connectivity has occurred. A connection has either * been established or lost. The NetworkInfo for the affected network is * sent as an extra; it should be consulted to see what kind of * connectivity event occurred.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Broadcast Action: The setting for background data usage has changed * values. Use {@link #getBackgroundDataSetting()} to get the current value. * <p> * If an application uses the network in the background, it should listen * for this broadcast and stop using the background data if the value is * false. */ @SdkConstant(SdkConstantType.BROADCAST_INTENT_ACTION) public static final String ACTION_BACKGROUND_DATA_SETTING_CHANGED = "android.net.conn.BACKGROUND_DATA_SETTING_CHANGED"; /** * The Default Mobile data connection. When active, all data traffic * will use this connection by default. Should not coexist with other</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* default connections.</p> <p>*/</p> <p>public static final int TYPE_MOBILE = 0;</p> <p>/**</p> <p>* The Default WIFI data connection. When active, all data traffic</p> <p>* will use this connection by default. Should not coexist with other</p> <p>* default connections.</p> <p>*/</p> <p>public static final int TYPE_WIFI = 1;</p> <p>/**</p> <p>* Returns the value of the setting for background data usage. If false,</p> <p>* applications should not use the network if the application is not in the</p> <p>* foreground. Developers should respect this setting, and check the value</p> <p>* of this before performing any background data operations.</p> <p>* <p></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * All applications that have background services that use the network * should listen to {@link #ACTION_BACKGROUND_DATA_SETTING_CHANGED}. * * @return Whether background data usage is allowed. */ public boolean getBackgroundDataSetting() { try { return mService.getBackgroundDataSetting(); } catch (RemoteException e) { // Err on the side of safety return false; } } /** * Sets the value of the setting for background data usage. * * @param allowBackgroundData Whether an application should use data while * it is in the background. </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * * @attr ref android.Manifest.permission#CHANGE_BACKGROUND_DATA_SETTING * @see #getBackgroundDataSetting() * @hide */ public void setBackgroundDataSetting(boolean allowBackgroundData) { try { mService.setBackgroundDataSetting(allowBackgroundData); } catch (RemoteException e) { } } /** * Sets the persisted value for enabling/disabling Mobile data. * * @param enabled Whether the mobile data connection should be </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* used or not.</p> <p>* @hide</p> <p>*/</p> <pre>public void setMobileDataEnabled(boolean enabled) { try { mService.setMobileDataEnabled(enabled); } catch (RemoteException e) { } }</pre> <p><i>See also</i> Android Developers Blog_Multitasking the Android Way, GOOG-HEADWATER-00000025-27</p> <p>A key to how Android handles applications in this way is that processes don't shut down cleanly. When the user leaves an application, its process is kept around in the background, allowing it to continue working (for example downloading web pages) if needed, and come immediately to the foreground if the user returns to it. If a device never runs out of memory, then Android will keep all of these processes around, truly leaving all applications "running" all of the time.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>Explicitly running in the background</p> <p>So far, we have a way for applications to implicitly do work in the background, as long as the process doesn't get killed by Android as part of its regular memory management. This is fine for things like loading web pages in the background, but what about features with harder requirements? Background music playback, data synchronization, location tracking, alarm clocks, etc.</p> <p>For these tasks, the application needs a way to tell Android "I would explicitly like to run at this point." There are two main facilities available to applications for this, represented by two kinds of components they can publish in their manifest: <i>broadcast receivers</i> and <i>services</i>.</p> <h3>Broadcast Receivers</h3> <p>A BroadcastReceiver allows an application to run, for a brief amount of time, in the background as a result of something else happening. It can be used in many ways to build higher-level facilities: for example the AlarmManager allows an application to have a broadcast sent at a certain time in the future, and the LocationManager can send a broadcast when it detects interesting changes in location. Because information about the receiver is part of an application's manifest, Android can find and launch the application even if it isn't running; of course if it already has its process available in the background, the broadcast can very efficiently be directly dispatched to it.</p> <p>When handling a broadcast, the application is given a fixed set of time (currently 10 seconds) in which to do its work. If it doesn't complete in that time, the application is considered to be misbehaving, and its process immediately tossed into the background state to be killed for memory if needed.</p> <p>Broadcast receivers are great for doing small pieces of work in response to an external stimulus, such as posting a notification to the user after being sent a new GPS location report. They are very lightweight, since the application's process only needs to be around while actively receiving the broadcast. Because they are active for a deterministic amount of time, fairly strong guarantees can be made about not killing their process while running. However they are not appropriate for anything of indeterminate length, such as networking.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p data-bbox="562 316 699 345">Services</p> <p data-bbox="562 394 1514 524">A Service allows an application to implement longer-running background operations. There are actually a lot of other functions that services provide, but for the discussion here their fundamental purpose is for an application to say "hey I would like to continue running even while in the background, until I say I am done." An application controls when its service runs by explicitly starting and stopping the service.</p> <p data-bbox="562 548 1524 730">While services do provide a rich client-server model, its use is optional. Upon starting an application's services, Android simply instantiates the component in the application's process to provide its context. How it is used after that is up to the application: it can put all of the needed code inside of the service itself without interacting with other parts of the application, make calls on other singleton objects shared with other parts of the app, directly retrieve the Service instance from elsewhere if needed, or run it in another process and do a full-blown RPC protocol if that is desired.</p> <p data-bbox="562 755 1518 860">Process management for services is different than broadcast receivers, because an unbounded number of services can ask to be running for an unknown amount of time. There may not be enough RAM to have all of the requesting services run, so as a result no strong guarantees are made about being able to keep them running.</p> <p data-bbox="562 885 1512 1040">If there is too little RAM, processes hosting services will be immediately killed like background processes are. However, if appropriate, Android will remember that these services wish to remain running, and restart their process at a later time when more RAM is available. For example, if the user goes to a web page that requires large amounts of RAM, Android may kill background service processes like sync until the browser's memory needs go down.</p> <p data-bbox="562 1065 1509 1250">Services can further negotiate this behavior by requesting they be considered "foreground." This places the service in a "please don't kill" state, but requires that it include a notification to the user about it actively running. This is useful for services such as background music playback or car navigation, which the user is actively aware of; when you're playing music and using the browser, you can always see the music-playing glyph in the status bar. Android won't try to kill these services, but as a trade-off, ensures the user knows about them and is able to explicitly stop them when desired.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>The value of generic components</p> <p>Android's generic broadcast receiver and service components allow developers to create a wide variety of efficient background operations, including things that were never originally considered. In Android 1.0 they were used to implement nearly all of the background behavior that the built-in and proprietary Google apps provided:</p> <ul style="list-style-type: none">• Music playback runs in a service to allow it to continue operating after the user leaves the music application.• The alarm clock schedules a broadcast receiver with the alarm manager, to go off at the next set alarm time.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> • The calendar application likewise schedules an alarm to display or update its notification at the appropriate time for the next calendar event. • Background file download is implemented a service that runs when there are any downloads to process. • The e-mail application schedules an alarm to wake up a service at regular intervals that looks for and retrieves any new mail. • The Google applications maintain a service to receive push notifications from the network; it in turn sends broadcasts to individual apps when it is told that they need to do things like synchronize contacts. <p>As the platform has evolved, these same basic components have been used to implement many of the major new developer features:</p> <ul style="list-style-type: none"> • Input methods are implemented by developers as a Service component that Android manages and works with to display as the current IME. • Application widgets are broadcast receivers that Android sends broadcasts to when it needs to interact with them. This allows app widgets to be quite lightweight, by not needing their application's process remain running. • Accessibility features are implemented as services that Android keeps running while in use and sends appropriate information to about user interactions. • Sync adapters introduced in Android 2.0 are services that are run in the background when a particular data sync needs to be performed. • Live wallpapers are a service started by Android when selected by the user. <p><i>See also</i> GOOG-HEADWATER-000000001-123.</p>
[2b] the one or more processors further	Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
<p>configured to classify whether the first end-user application is interacting with the user in the device user interface foreground, and determine whether to apply the one or more Internet activity access controls based also on the classification of whether the first end-user application is interacting with the user.</p>	<p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c].</p> <p><u>HTC Dream / T-Mobile G1</u></p> <p>SAMSUNG_PRIORART0005207</p> <p>Data synchronization</p> <p>Some Google applications on your phone (Gmail, Calendar, and Contacts) give you access to the same personal information that you can add, view, and edit on your computer using Google Web applications. This means that when you add, change, or delete your information in any of these applications on the Web, the updated information also appears on your phone, and vice versa. Also, if you lose your phone or if your phone is destroyed, your personal information is not lost and will appear, as before, on a replacement phone.</p> <p>This mirroring of information happens through over-the-air data synchronization, or data "syncing". Data syncing occurs in the background and shouldn't ever get in your way. You'll know your data is being synchronized when you see this icon in the status bar: .</p> <p>Because sending large amounts of data back and forth over the air can take time and require considerable bandwidth, there are some settings on the phone that allow you to control data sync.</p> <p>SAMSUNG_PRIORART0005245</p> <div> <div>Open in background</div> <div>Select if you want links to new pages to open in a new window in the background.</div> </div> <p>SAMSUNG_PRIORART0005260</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>Answer incoming, hold call in progress</p> <p>The incoming call will display in the foreground.</p>  <p>Press CALL to answer the incoming call and place the call in progress on hold. You can also press MENU and select Hold call in progress & answer.</p> <p>To switch calls at any time, press MENU and select Switch calls.</p> <p><i>See also</i> Android Developers Blog_Multitasking the Android Way, GOOG-HEADWATER-00000025-27</p> <p>A key to how Android handles applications in this way is that processes don't shut down cleanly. When the user leaves an application, its process is kept around in the background, allowing it to continue working (for example downloading web pages) if needed, and come immediately to the foreground if the user returns to it. If a device never runs out of memory, then Android will keep all of these processes around, truly leaving all applications "running" all of the time.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>Explicitly running in the background</p> <p>So far, we have a way for applications to implicitly do work in the background, as long as the process doesn't get killed by Android as part of its regular memory management. This is fine for things like loading web pages in the background, but what about features with harder requirements? Background music playback, data synchronization, location tracking, alarm clocks, etc.</p> <p>For these tasks, the application needs a way to tell Android "I would explicitly like to run at this point." There are two main facilities available to applications for this, represented by two kinds of components they can publish in their manifest: <i>broadcast receivers</i> and <i>services</i>.</p> <p>Broadcast Receivers</p> <p>A BroadcastReceiver allows an application to run, for a brief amount of time, in the background as a result of something else happening. It can be used in many ways to build higher-level facilities: for example the AlarmManager allows an application to have a broadcast sent at a certain time in the future, and the LocationManager can send a broadcast when it detects interesting changes in location. Because information about the receiver is part of an application's manifest, Android can find and launch the application even if it isn't running; of course if it already has its process available in the background, the broadcast can very efficiently be directly dispatched to it.</p> <p>When handling a broadcast, the application is given a fixed set of time (currently 10 seconds) in which to do its work. If it doesn't complete in that time, the application is considered to be misbehaving, and its process immediately tossed into the background state to be killed for memory if needed.</p> <p>Broadcast receivers are great for doing small pieces of work in response to an external stimulus, such as posting a notification to the user after being sent a new GPS location report. They are very lightweight, since the application's process only needs to be around while actively receiving the broadcast. Because they are active for a deterministic amount of time, fairly strong guarantees can be made about not killing their process while running. However they are not appropriate for anything of indeterminate length, such as networking.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>Services</p> <p>A Service allows an application to implement longer-running background operations. There are actually a lot of other functions that services provide, but for the discussion here their fundamental purpose is for an application to say "hey I would like to continue running even while in the background, until I say I am done." An application controls when its service runs by explicitly starting and stopping the service.</p> <p>While services do provide a rich client-server model, its use is optional. Upon starting an application's services, Android simply instantiates the component in the application's process to provide its context. How it is used after that is up to the application: it can put all of the needed code inside of the service itself without interacting with other parts of the application, make calls on other singleton objects shared with other parts of the app, directly retrieve the Service instance from elsewhere if needed, or run it in another process and do a full-blown RPC protocol if that is desired.</p> <p>Process management for services is different than broadcast receivers, because an unbounded number of services can ask to be running for an unknown amount of time. There may not be enough RAM to have all of the requesting services run, so as a result no strong guarantees are made about being able to keep them running.</p> <p>If there is too little RAM, processes hosting services will be immediately killed like background processes are. However, if appropriate, Android will remember that these services wish to remain running, and restart their process at a later time when more RAM is available. For example, if the user goes to a web page that requires large amounts of RAM, Android may kill background service processes like sync until the browser's memory needs go down.</p> <p>Services can further negotiate this behavior by requesting they be considered "foreground." This places the service in a "please don't kill" state, but requires that it include a notification to the user about it actively running. This is useful for services such as background music playback or car navigation, which the user is actively aware of; when you're playing music and using the browser, you can always see the music-playing glyph in the status bar. Android won't try to kill these services, but as a trade-off, ensures the user knows about them and is able to explicitly stop them when desired.</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p data-bbox="585 326 1077 358">The value of generic components</p> <p data-bbox="585 402 1604 513">Android's generic broadcast receiver and service components allow developers to create a wide variety of efficient background operations, including things that were never originally considered. In Android 1.0 they were used to implement nearly all of the background behavior that the built-in and proprietary Google apps provided:</p> <ul data-bbox="585 548 1619 678" style="list-style-type: none"><li data-bbox="585 548 1619 605">• Music playback runs in a service to allow it to continue operating after the user leaves the music application.<li data-bbox="585 621 1619 678">• The alarm clock schedules a broadcast receiver with the alarm manager, to go off at the next set alarm time.

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none"> • The calendar application likewise schedules an alarm to display or update its notification at the appropriate time for the next calendar event. • Background file download is implemented a service that runs when there are any downloads to process. • The e-mail application schedules an alarm to wake up a service at regular intervals that looks for and retrieves any new mail. • The Google applications maintain a service to receive push notifications from the network; it in turn sends broadcasts to individual apps when it is told that they need to do things like synchronize contacts. <p>As the platform has evolved, these same basic components have been used to implement many of the major new developer features:</p> <ul style="list-style-type: none"> • Input methods are implemented by developers as a Service component that Android manages and works with to display as the current IME. • Application widgets are broadcast receivers that Android sends broadcasts to when it needs to interact with them. This allows app widgets to be quite lightweight, by not needing their application's process remain running. • Accessibility features are implemented as services that Android keeps running while in use and sends appropriate information to about user interactions. • Sync adapters introduced in Android 2.0 are services that are run in the background when a particular data sync needs to be performed. • Live wallpapers are a service started by Android when selected by the user. <p><i>See also</i> GOOG-HEADWATER-0000000001-123.</p>
[3] The wireless end-user device of claim 2,	Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
<p>wherein the one or more processors are configured to classify that the first end-user application is interacting with the user in the device user interface foreground when the user of the device is directly interacting with that application or perceiving any benefit from that application.</p>	<p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c], [2].</p>
<p>[4] The wireless end-user device of claim 2, wherein the one or more processors are configured to classify that the first end-user application is interacting with the user in the device user interface foreground based on a state of user interface priority for the application.</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c], [2].</p>
<p>[5] The wireless end-user device of claim 2,</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
<p>wherein the one or more processors are configured to classify that the first end-user application is not interacting with the user in the device user interface foreground when the application is providing or utilizing a background data service.</p>	<p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c], [2].</p>
<p>[6] The wireless end-user device of claim 2, wherein the one or more processors are configured to apply the one or more Internet activity access controls such that, when the one or more Internet activity access controls are to be applied based on a classification that the first end-user application is not interacting with the user, network activity in association with the first Internet access request is delayed until a</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c], [2].</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
second Internet access request is received from or on behalf of an application that is classified as interacting with the user.	
[7] The wireless end-user device of claim 1, wherein the first differential traffic control policy element comprises an application list, and the one or more Internet activity access controls are associated with the first end-user application based on a determination as to whether the first end-user application is identified by the application list.	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c].</p>
[8] The wireless end-user device of claim 7, wherein the one or more Internet activity access controls are further associated with a second	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c].</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
end-user application based on a determination as to whether the second end-user application is identified by the application list.	
[9] The wireless end-user device of claim 1, further comprising a user interface, wherein the user interface is to inform the user of the device when there are options to set, control, override, or modify the one or more Internet activity access controls and/or the association of those access controls with the first end-user application.	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c].</p>
[10] The wireless end-user device of claim 1, wherein the one or more processors are further configured to select the first differential traffic control policy element	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c].</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
<p>from the network service activity control policy set based at least in part on which of the plurality of wireless network types is to provide data communication for Internet access requests.</p>	
<p>[11] The wireless end-user device of claim 10, further comprising a wireless local area network (WLAN) modem to communicate data for Internet service activities between the device and at least one WLAN, when configured for and connected to the at least one WLAN, wherein the one or more processors are further configured to, when the at least one WLAN is to provide data communication for Internet access requests, not apply the one or</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c].</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
more Internet activity access controls.	
<p>[12] The wireless end-user device of claim 1, wherein the plurality of network types include a home WWAN type and a roaming WWAN type, the one or more processors configured to determine to apply the one or more Internet activity access controls to the roaming WWAN type and not to the home WWAN type.</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g., the disclosures identified for claims [1 pre]-[1c]. E.g.:</i></p> <p><u>Android 2.2</u></p> <p><u>SAMSUNG PRIORART0005353, NetworkInfo</u></p> <pre> /** * Indicates whether network connectivity is possible. A network is unavailable * when a persistent or semi-persistent condition prevents the possibility * of connecting to that network. Examples include * * The device is out of the coverage area for any network of this type. * The device is on a network other than the home network (i.e., roaming), and * data roaming has been disabled. * The device's radio is turned off, e.g., because airplane mode is enabled. * * @return { @code true} if the network is available, { @code false} otherwise */ public boolean isAvailable() { return mIsAvailable; } </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * Indicates whether the device is currently roaming on this network. * When { @code true }, it suggests that use of data on this network * may incur extra costs. * @return { @code true } if roaming is in effect, { @code false } otherwise. */ public boolean isRoaming() { return mIsRoaming; } /** * Record the roaming status of the device, and if it is a change from the previous * status, send a notification to any listeners. * @param isRoaming { @code true } if the device is now roaming, { @code false } * if it is no longer roaming. */ protected void setRoamingStatus(boolean isRoaming) { if (isRoaming != mNetworkInfo.isRoaming()) { mNetworkInfo.setRoaming(isRoaming); Message msg = mTarget.obtainMessage(EVENT_ROAMING_CHANGED, mNetworkInfo); msg.sendToTarget(); } } public static final int EVENT_ROAMING_CHANGED = 5; </pre> <p><u>HTC Dream / T-Mobile G1</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>SAMSUNG_PRIORART0005202</p> <p>Mobile network settings</p> <ul style="list-style-type: none">• Select data roaming capability.• Select to connect only to 2G (slower) networks to save battery power.• Select a wireless operator network - Scan for all available networks, or select a network automatically.• Add or edit network Access Point Names (APNs) - Do not change this setting unless advised to do so by your wireless operator! <p><u>Samsung GT-I7500 Galaxy</u></p> <p>SAMSUNG_PRIORART0005494 at pg. PDF 72:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<div><div><div>Wi-Fi settings</div><ul style="list-style-type: none">• Wi-Fi: Turn the WLAN feature on or off.• Network notification: Set the device to notify you when an open network is available.• Add Wi-Fi network: Add WLAN networks.<div>Bluetooth</div><p>Turn the Bluetooth wireless feature on or off.</p><div>Bluetooth settings</div><ul style="list-style-type: none">• Bluetooth: Turn the Bluetooth wireless feature on or off.• Device name: Set a Bluetooth name for your device.• Discoverable: Set your device to be visible to other Bluetooth devices.• Scan for devices: Search for available Bluetooth devices.</div><div><div>Mobile networks</div><ul style="list-style-type: none">• Data roaming: Set the device to connect another network when you are roaming or your home network is not available.• Use only 2G networks: Set the device to connect only to a 2G network.• Network operators: Search for available networks and select a network for roaming.• Access Point Names: Set up access point names (APNs).<div>Airplane mode</div><p>Disable all wireless functions on your device.</p></div></div> <div><i>See also</i> Coding for Battery Life, GOOG-HEADWATER-00000092-123</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Networking</p> <ul style="list-style-type: none">• Check network connection, wait for 3G or WiFi <pre>ConnectivityManager mConnectivity; TelephonyManager mTelephony; // Skip if no connection, or background data disabled NetworkInfo info = mConnectivity.getActiveNetworkInfo(); if (info == null !mConnectivity.getBackgroundDataSetting()) { return false; }</pre>  

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Networking</p> <ul style="list-style-type: none"> • Check network connection, wait for 3G or WiFi <pre>// Only update if WiFi or 3G is connected and not roaming int netType = info.getType(); int netSubtype = info.getSubtype(); if (netType == ConnectivityManager.TYPE_WIFI) { return info.isConnected(); } else if (netType == ConnectivityManager.TYPE_MOBILE && netSubtype == TelephonyManager.NETWORK_TYPE_UMTS && !mTelephony.isNetworkRoaming()) { return info.isConnected(); } else { return false; }</pre> 
<p>[13] The wireless end-user device of claim 1, wherein the one or more processors are further configured to dynamically change the determination of whether to apply the one or more Internet activity access controls based on a power state of the device.</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c]. In addition, <i>see, e.g.:</i></p> <p><u>Android 1.0</u></p> <p><u>SAMSUNG PRIORART0005487, Power</u></p> <p>/**</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * Wake lock that ensures that the CPU is running. The screen might * not be on. */ public static final int PARTIAL_WAKE_LOCK = 1; /** * Wake lock that ensures that the screen is on. */ public static final int FULL_WAKE_LOCK = 2; * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; /** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; <u>SAMSUNG PRIORART0005487, BatteryManager</u> // values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values for "health" field in the ACTION_BATTERY_CHANGED Intent </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public static final int BATTERY_HEALTH_UNKNOWN = 1; public static final int BATTERY_HEALTH_GOOD = 2; public static final int BATTERY_HEALTH_OVERHEAT = 3; public static final int BATTERY_HEALTH_DEAD = 4; public static final int BATTERY_HEALTH_OVER_VOLTAGE = 5; public static final int BATTERY_HEALTH_UNSPECIFIED_FAILURE = 6; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent public static final int BATTERY_PLUGGED_AC = 1; public static final int BATTERY_PLUGGED_USB = 2; </pre> <p><u>Android 1.6</u></p> <p><u>SAMSUNG_PRIORART0005350, Power</u></p> <p><u>/**</u></p> <p><u>* Brightness value to use when battery is low</u></p> <p><u>*/</u></p> <p><u>public static final int BRIGHTNESS_LOW_BATTERY = 10;</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Threshold for BRIGHTNESS LOW BATTERY (percentage) * Screen will stay dim if battery level is <= LOW BATTERY THRESHOLD */ public static final int LOW BATTERY THRESHOLD = 10; SAMSUNG_PRIORART0005350, PowerManager /** * This class gives you control of the power state of the device. * * <p>Device battery life will be significantly affected by the use of this API. Do not * acquire WakeLocks unless you really need them, use the minimum levels possible, and be sure * to release it as soon as you can. * * <p>You can obtain an instance of this class by calling * {@link android.content.Context#getSystemService(java.lang.String) Context.getSystemService()}. </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* * <p>The primary API you'll use is {@link #newWakeLock(int, String) newWakeLock()}. This will * create a {@link PowerManager.WakeLock} object. You can then use methods on this object to * control the power state of the device. In practice it's quite simple: * * {@samplecode * PowerManager pm = (PowerManager) getSystemService(Context.POWER_SERVICE); * PowerManager.WakeLock wl = pm.newWakeLock(PowerManager.SCREEN_DIM_WAKE_LOCK, "My Tag"); * wl.acquire(); * ..screen will stay on during this section.. * wl.release(); * } * * <p>The following flags are defined, with varying effects on system power. <i>These flags are * mutually exclusive - you may only specify one of them.</i> * <table border="2" width="85%" align="center" frame="hsides" rules="rows"> * * <thead></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * <tr><th>Flag Value</th> * <th>CPU</th> <th>Screen</th> <th>Keyboard</th></tr> * </thead> * * <tbody> * <tr><th>{@link #PARTIAL_WAKE_LOCK}</th> * <td>On*</td> <td>Off</td> <td>Off</td> * </tr> * * <tr><th>{@link #SCREEN_DIM_WAKE_LOCK}</th> * <td>On</td> <td>Dim</td> <td>Off</td> * </tr> * * <tr><th>{@link #SCREEN_BRIGHT_WAKE_LOCK}</th> * <td>On</td> <td>Bright</td> <td>Off</td> * </tr> * * <tr><th>{@link #FULL_WAKE_LOCK}</th> </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* <td>On</td> <td>Bright</td> <td>Bright</td></p> <p>* </tr></p> <p>* </tbody></p> <p>* </table></p> <p>*</p> <p>* <p>*<i>If you hold a partial wakelock, the CPU will continue to run, irrespective of any timers</p> <p>* and even after the user presses the power button. In all other wakelocks, the CPU will run, but</p> <p>* the user can still put the device to sleep using the power button.</i></p></p> <p>*</p> <p>* <p>In addition, you can add two more flags, which affect behavior of the screen only. <i>These</p> <p>* flags have no effect when combined with a {@link #PARTIAL_WAKE_LOCK}.</i></p> <p>* <table border="2" width="85%" align="center" frame="hsides" rules="rows"></p> <p>*</p> <p>* <thead></p> <p>* <tr><th>Flag Value</th> <th>Description</th></tr></p> <p>* </thead></p> <p>*</p> <p>* <tbody></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* <tr><th>{@link #ACQUIRE_CAUSES_WAKEUP}</th></p> <p>* <td>Normal wake locks don't actually turn on the illumination. Instead, they cause</p> <p>* the illumination to remain on once it turns on (e.g. from user activity). This flag</p> <p>* will force the screen and/or keyboard to turn on immediately, when the WakeLock is</p> <p>* acquired. A typical use would be for notifications which are important for the user to</p> <p>* see immediately.</td></p> <p>* </tr></p> <p>* </p> <p>* <tr><th>{@link #ON_AFTER_RELEASE}</th></p> <p>* <td>If this flag is set, the user activity timer will be reset when the WakeLock is</p> <p>* released, causing the illumination to remain on a bit longer. This can be used to</p> <p>* reduce flicker if you are cycling between wake lock conditions.</td></p> <p>* </tr></p> <p>* </tbody></p> <p>* </table></p> <p>* </p> <p>* </p> <p>* /</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>private static final int WAKE_BIT_CPU_STRONG = 1; private static final int WAKE_BIT_CPU_WEAK = 2; private static final int WAKE_BIT_SCREEN_DIM = 4; private static final int WAKE_BIT_SCREEN_BRIGHT = 8; private static final int WAKE_BIT_KEYBOARD_BRIGHT = 16;</pre> <p><u>SAMSUNG PRIORART0005350, BatteryManager</u></p> <p><u>/**</u></p> <p>* The BatteryManager class contains strings and constants used for values</p> <p>* in the ACTION_BATTERY_CHANGED Intent.</p> <p>*/</p> <pre>public class BatteryManager { // values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values for "health" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_HEALTH_UNKNOWN = 1; public static final int BATTERY_HEALTH_GOOD = 2; public static final int BATTERY_HEALTH_OVERHEAT = 3; public static final int BATTERY_HEALTH_DEAD = 4; public static final int BATTERY_HEALTH_OVER_VOLTAGE = 5; public static final int BATTERY_HEALTH_UNSPECIFIED_FAILURE = 6; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent. // These must be powers of 2. /** Power source is an AC charger. */ public static final int BATTERY_PLUGGED_AC = 1; /** Power source is a USB port. */ </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int BATTERY_PLUGGED_USB = 2; }</pre> <p><u>SAMSUNG PRIORART0005350, BatteryStats</u></p> <pre>/** * A constant indicating a a wifi turn on timer * * {@hide} */ public static final int WIFI_TURNED_ON = 4; /** * A constant indicating a full wifi lock timer * * {@hide} */</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int FULL_WIFI_LOCK = 5; /** * A constant indicating a scan wifi lock timer * * {@hide} */ public static final int SCAN_WIFI_LOCK = 6; /** * A constant indicating a wifi multicast timer * * {@hide} */ public static final int WIFI_MULTICAST_ENABLED = 7; /** * A constant indicating an audio turn on timer</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* * {@hide} */ public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8; /** * Include all of the data in the stats, including previously saved data. */ public static final int STATS_TOTAL = 0; /**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* Include only the last run in the stats. */ public static final int STATS_LAST = 1; /** * Include only the current run in the stats. */ public static final int STATS_CURRENT = 2; /** * Include only the run since the last time the device was unplugged in the stats. */ public static final int STATS_UNPLUGGED = 3; public abstract void noteWifiTurnedOnLocked(); public abstract void noteWifiTurnedOffLocked(); public abstract void noteFullWifiLockAcquiredLocked(); public abstract void noteFullWifiLockReleasedLocked();</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public abstract void noteScanWifiLockAcquiredLocked(); public abstract void noteScanWifiLockReleasedLocked(); public abstract void noteWifiMulticastEnabledLocked(); public abstract void noteWifiMulticastDisabledLocked(); /** * Returns the time in microseconds that the screen has been on while the device was * running on battery. * * {@hide} */ public abstract long getScreenOnTime(long batteryRealtime, int which); public static final int SCREEN_BRIGHTNESS_DARK = 0; public static final int SCREEN_BRIGHTNESS_DIM = 1; public static final int SCREEN_BRIGHTNESS_MEDIUM = 2; public static final int SCREEN_BRIGHTNESS_LIGHT = 3; public static final int SCREEN_BRIGHTNESS_BRIGHT = 4; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4; /** * Returns the time in microseconds that wifi has been on while the device was * running on battery. * * {@hide} */ public abstract long getWifiOnTime(long batteryRealtime, int which); /** * Returns the time in microseconds that bluetooth has been on while the device was * running on battery.</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * * {@hide} */ public abstract long getBluetoothOnTime(long batteryRealtime, int which); /** * Return whether we are currently running on battery. */ public abstract boolean getIsOnBattery(); /** * Returns the time that the radio was on for data transfers. * @return the uptime in microseconds while unplugged */ public abstract long getRadioDataUptime(); /** * Returns the current battery realtime in microseconds. </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * * @param curTime the amount of elapsed realtime in microseconds. */ public abstract long getBatteryRealtime(long curTime); /** * Returns the battery percentage level at the last time the device was unplugged from power, or * the last time it booted on battery power. */ public abstract int getDischargeStartLevel(); <u>Android 2.2</u> <u>SAMSUNG PRIORART0005353, Power</u> /** * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; /** * Turn the screen on or off * * @param on Whether you want the screen on or off */ public static native int setScreenState(boolean on);</pre> <p><u>SAMSUNG PRIORART0005353, BatteryManager</u></p> <pre>/** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer indicating whether the device is plugged in to a power * source; 0 means it is on battery, other constants are different * types of power sources. */ public static final String EXTRA_PLUGGED = "plugged";</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer containing the current battery voltage level. */ public static final String EXTRA_VOLTAGE = "voltage"; /** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer containing the current battery temperature. */ public static final String EXTRA_TEMPERATURE = "temperature"; /** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * String describing the technology of the current battery. */ public static final String EXTRA_TECHNOLOGY = "technology";</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>// values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent. // These must be powers of 2. /** Power source is an AC charger. */ public static final int BATTERY_PLUGGED_AC = 1; /** Power source is a USB port. */ public static final int BATTERY_PLUGGED_USB = 2; <u>SAMSUNG_PRIORART0005353, BatteryStats</u> /**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none">* A class providing access to battery usage statistics, including information on<ul style="list-style-type: none">* wakelocks, processes, packages, and services. All times are represented in microseconds* except where indicated otherwise.* @hide*//**<ul style="list-style-type: none">* A constant indicating a a wifi turn on timer** {@hide}*/public static final int WIFI_TURNED_ON = 4;/**<ul style="list-style-type: none">* A constant indicating an audio turn on timer** {@hide}*/

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8; public static final int SIGNAL_STRENGTH_NONE_OR_UNKNOWN = 0; public static final int SIGNAL_STRENGTH_POOR = 1; public static final int SIGNAL_STRENGTH_MODERATE = 2; public static final int SIGNAL_STRENGTH_GOOD = 3; public static final int SIGNAL_STRENGTH_GREAT = 4; static final String[] SIGNAL_STRENGTH_NAMES = { "none", "poor", "moderate", "good", "great" };</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4;</pre> <p><u>GOOG-HEADWATER-00000092, Google I/O 2009 - Coding for Life -- Battery Life, That Is (June 2, 2009)</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 2:</p> <h2>Coding for Life--Battery Life, That Is</h2> <p>Jeff Sharkey May 27, 2009</p> <p>Post your questions for this talk on Google Moderator: code.google.com/events/io/questions</p> <p>Google </p> <hr/> <p>GOOG-HEADWATER-000000093</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 3:</p> <h2>Why does this matter?</h2> <ul style="list-style-type: none">● Phones primarily run on battery power, and each device has a "battery budget"<ul style="list-style-type: none">○ When it's gone, it's gone○ Apps need to work together to be good citizens of that shared resource○ Current measured in mA, battery capacity in mAh● HTC Dream: 1150mAh● HTC Magic: 1350mAh● Samsung I7500: 1500mAh● Asus Eee PC: 5800mAh <div></div> <p>GOOG-HEADWATER-000000094</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps																																																				
	<p>See, e.g., GOOG-HEADWATER-00000092 at 4:</p> <div><h3>Where does it all go?</h3><p>Source: Values measured using an industrial power monitor at 5kHz sampling rate, and taking average power with lowest standard deviation.</p><p>■ Baseline usage ■ Specific item</p><table border="1"><thead><tr><th>Category</th><th>Baseline usage (mA)</th><th>Specific item (mA)</th><th>Total (mA)</th></tr></thead><tbody><tr><td>Airplane</td><td>~10</td><td>~10</td><td>~20</td></tr><tr><td>3G idle</td><td>~10</td><td>~10</td><td>~20</td></tr><tr><td>EDGE idle</td><td>~10</td><td>~10</td><td>~20</td></tr><tr><td>WiFi idle</td><td>~10</td><td>~10</td><td>~20</td></tr><tr><td>LCD normal</td><td>~10</td><td>~80</td><td>~90</td></tr><tr><td>CPU 50%</td><td>~90</td><td>~50</td><td>~140</td></tr><tr><td>CPU full</td><td>~90</td><td>~110</td><td>~200</td></tr><tr><td>Game sensors</td><td>~140</td><td>~80</td><td>~220</td></tr><tr><td>GPS radio</td><td>~140</td><td>~90</td><td>~230</td></tr><tr><td>3G full</td><td>~140</td><td>~160</td><td>~300</td></tr><tr><td>EDGE full</td><td>~140</td><td>~250</td><td>~390</td></tr><tr><td>WiFi full</td><td>~140</td><td>~280</td><td>~420</td></tr></tbody></table><p>Google 09 O</p><p>GOOG-HEADWATER-00000095</p></div>	Category	Baseline usage (mA)	Specific item (mA)	Total (mA)	Airplane	~10	~10	~20	3G idle	~10	~10	~20	EDGE idle	~10	~10	~20	WiFi idle	~10	~10	~20	LCD normal	~10	~80	~90	CPU 50%	~90	~50	~140	CPU full	~90	~110	~200	Game sensors	~140	~80	~220	GPS radio	~140	~90	~230	3G full	~140	~160	~300	EDGE full	~140	~250	~390	WiFi full	~140	~280	~420
Category	Baseline usage (mA)	Specific item (mA)	Total (mA)																																																		
Airplane	~10	~10	~20																																																		
3G idle	~10	~10	~20																																																		
EDGE idle	~10	~10	~20																																																		
WiFi idle	~10	~10	~20																																																		
LCD normal	~10	~80	~90																																																		
CPU 50%	~90	~50	~140																																																		
CPU full	~90	~110	~200																																																		
Game sensors	~140	~80	~220																																																		
GPS radio	~140	~90	~230																																																		
3G full	~140	~160	~300																																																		
EDGE full	~140	~250	~390																																																		
WiFi full	~140	~280	~420																																																		

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
	<p data-bbox="556 316 1094 345"><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 9:</p> <h2 data-bbox="585 370 1115 418">How can we do better?</h2> <h3 data-bbox="585 430 777 472">Networking</h3> <ul data-bbox="573 509 1482 552" style="list-style-type: none">● Check network connection, wait for 3G or WiFi <pre data-bbox="585 662 1644 987">ConnectivityManager mConnectivity; TelephonyManager mTelephony; // Skip if no connection, or background data disabled NetworkInfo info = mConnectivity.getActiveNetworkInfo(); if (info == null !mConnectivity.getBackgroundDataSetting()) { return false; }</pre>  <div data-bbox="1577 1177 1772 1235"> 09 </div> <div data-bbox="1528 1295 1780 1315">GOOG-HEADWATER-00000100</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 11:</p> <p>How can we do better? Networking</p> <ul style="list-style-type: none">● Check network connection, wait for 3G or WiFi <pre>// Only update if WiFi or 3G is connected and not roaming int netType = info.getType(); int netSubtype = info.getSubtype(); if (netType == ConnectivityManager.TYPE_WIFI) { return info.isConnected(); } else if (netType == ConnectivityManager.TYPE_MOBILE && netSubtype == TelephonyManager.NETWORK_TYPE_UMTS && !mTelephony.isNetworkRoaming()) { return info.isConnected(); } else { return false; }</pre> <p>Google 09 O</p> <p>GOOG-HEADWATER-00000101</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 16:</p> <h2>How can we do better?</h2> <p>Foreground apps</p> <ul style="list-style-type: none">● Wakelocks are costly if forgotten<ul style="list-style-type: none">○ Pick the lowest level possible, and use specific timeouts to work around unforeseen bugs○ Consider using <code>android:keepScreenOn</code> to ensure correctness <pre><LinearLayout android:orientation="vertical" android:layout_width="fill_parent" android:layout_height="fill_parent" android:keepScreenOn="true"></pre> <div></div> <div></div> <p>GOOG-HEADWATER-00000107</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<i>See, e.g.</i> , GOOG-HEADWATER-000000092 at 18:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433





'433 Claims	Android Device with One or More Apps
	<p>How can we do better? Foreground apps</p> <ul style="list-style-type: none">● Use coarse network location, it's much cheaper<ul style="list-style-type: none">○ GPS: 25 seconds * 140mA = 1mAh○ Network: 2 seconds * 180mA = 0.1mAh● 1.5 uses AGPS when network available● GPS time-to-fix varies wildly based on environment, and desired accuracy, and might outright fail<ul style="list-style-type: none">○ Just like wake-locks, location updates can continue after onPause(), so make sure to unregister○ If all apps unregister correctly, user can leave GPS enabled in Settings <div></div> <div> GOOG-HEADWATER-00000109</div> <p>See, e.g., GOOG-HEADWATER-00000092 at 20:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Foreground apps</p> <ul style="list-style-type: none">● Accelerometer/magnetic sensors<ul style="list-style-type: none">○ Normal: 10mA (used for orientation detection)○ UI: 15mA (about 1 per second)○ Game: 80mA○ Fastest: 90mA● Same cost for accelerometer, magnetic, orientation sensors on HTC Dream <div>  GOOG-HEADWATER-00000111</div> <p>See, e.g., GOOG-HEADWATER-00000092 at 22:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
	<p>How can we do better? Background apps</p> <ul style="list-style-type: none">● Services should be short-lived; these aren't daemons<ul style="list-style-type: none">○ Each process costs 2MB and risks being killed/restarted as foreground apps need memory○ Otherwise, keep memory usage low so you're not the first target● Trigger wake-up through AlarmManager or with <receiver> manifest elements<ul style="list-style-type: none">○ stopSelf() when finished <div> </div> <div></div> <p>GOOG-HEADWATER-00000113</p> <p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 26:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Background apps</p> <ul style="list-style-type: none">●Dynamically enabling/disabling <receiver> components in manifest, especially when no-ops <pre><receiver android:name=".ConnectivityReceiver" android:enabled="false"> ... </receiver></pre> <pre>ComponentName receiver = new ComponentName(context, ConnectivityReceiver.class); PackageManager pm = context.getPackageManager(); pm.setComponentEnabledSetting(receiver, PackageManager.COMPONENT_ENABLED_STATE_ENABLED, PackageManager.DONT_KILL_APP);</pre> <div>Google 09 O</div> <div>GOOG-HEADWATER-00000117</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 27:</p> <h2>How can we do better?</h2> <h3>Background apps</h3> <ul style="list-style-type: none"> • Checking current battery and network state before running a full update <pre> public void onCreate() { // Register for sticky broadcast and send default registerReceiver(mReceiver, mFilter); mHandler.sendMessageDelayed(MSG_BATT, 1000); } IntentFilter mFilter = new IntentFilter(Intent.ACTION_BATTERY_CHANGED); BroadcastReceiver mReceiver = new BroadcastReceiver() { public void onReceive(Context context, Intent intent) { // Found sticky broadcast, so trigger update unregisterReceiver(mReceiver); mHandler.removeMessages(MSG_BATT); mHandler.obtainMessage(MSG_BATT, intent).sendToTarget(); } }; </pre>  <p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 29:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p data-bbox="575 326 1100 375">Users will be watching!</p> <div data-bbox="552 440 947 1029">  </div> <ul data-bbox="995 461 1680 1136" style="list-style-type: none"> ● SpareParts has "Battery history" <ul style="list-style-type: none"> ○ 1.5 is already keeping stats on which apps are using CPU, network, wakelocks ○ Simplified version coming in future, and users will uninstall apps that abuse battery ● Consider giving users options for battery usage, like update intervals, and check the "no background data" flag <div data-bbox="1562 1127 1759 1187">  </div> <p data-bbox="1520 1247 1766 1263">GOOG-HEADWATER-00000120</p> <p data-bbox="554 1295 1108 1328">See, e.g., GOOG-HEADWATER-00000092 at 30:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p data-bbox="583 329 846 381">Takeaways</p> <ul data-bbox="569 467 1587 878" style="list-style-type: none">● Use an efficient parser and GZIP to make best use of network and CPU resources● Services that sleep or poll are bad, use <receiver> and AlarmManager instead<ul data-bbox="617 678 1575 776" style="list-style-type: none">○ Disable manifest elements when no-op○ Wake up along with everyone else (inexact alarms)● Wait for better network/battery for bulk transfers● Give users choices about background behavior <div data-bbox="1570 1133 1766 1192"> 09 </div> <div data-bbox="1528 1252 1776 1268">GOOG-HEADWATER-00000121</div>
[14] The wireless end-user device of claim 1, wherein the one or more	Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
processors are further configured to dynamically change the determination of whether to apply the one or more Internet activity access controls based on a device usage state.	<p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c]. In addition:</p> <p><u>Android 1.0</u></p> <p><u>SAMSUNG PRIORART0005487, Power</u></p> <pre> /** * Wake lock that ensures that the CPU is running. The screen might * not be on. */ public static final int PARTIAL_WAKE_LOCK = 1; /** * Wake lock that ensures that the screen is on. */ public static final int FULL_WAKE_LOCK = 2; * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; /** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; </pre> <p><u>SAMSUNG PRIORART0005487, BatteryManager</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>// values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values for "health" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_HEALTH_UNKNOWN = 1; public static final int BATTERY_HEALTH_GOOD = 2; public static final int BATTERY_HEALTH_OVERHEAT = 3; public static final int BATTERY_HEALTH_DEAD = 4; public static final int BATTERY_HEALTH_OVER_VOLTAGE = 5; public static final int BATTERY_HEALTH_UNSPECIFIED_FAILURE = 6; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent public static final int BATTERY_PLUGGED_AC = 1; public static final int BATTERY_PLUGGED_USB = 2;</pre> <p><u>Android 1.6</u></p> <p><u>SAMSUNG PRIORART0005350, Power</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; /** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; SAMSUNG_PRIORART0005350, PowerManager /** * This class gives you control of the power state of the device. * </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* <p>Device battery life will be significantly affected by the use of this API. Do not</p> <p>* acquire WakeLocks unless you really need them, use the minimum levels possible, and be sure</p> <p>* to release it as soon as you can.</p> <p>*</p> <p>* <p>You can obtain an instance of this class by calling</p> <p>* {@link android.content.Context#getService(java.lang.String) Context.getService()}. *</p> <p>* <p>The primary API you'll use is {@link #newWakeLock(int, String) newWakeLock()}. This will</p> <p>* create a {@link PowerManager.WakeLock} object. You can then use methods on this object to</p> <p>* control the power state of the device. In practice it's quite simple:</p> <p>*</p> <p>* {@samplecode</p> <p>* PowerManager pm = (PowerManager) getService(Context.POWER_SERVICE);</p> <p>* PowerManager.WakeLock wl = pm.newWakeLock(PowerManager.SCREEN_DIM_WAKE_LOCK, "My Tag");</p> <p>* wl.acquire();</p> <p>* ..screen will stay on during this section..</p> <p>* wl.release();</p> <p>* }</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* * <p>The following flags are defined, with varying effects on system power. <i>These flags are * mutually exclusive - you may only specify one of them.</i> * <table border="2" width="85%" align="center" frame="hsides" rules="rows"> * * <thead> * <tr><th>Flag Value</th> * <th>CPU</th> <th>Screen</th> <th>Keyboard</th></tr> * </thead> * * <tbody> * <tr><th>{@link #PARTIAL_WAKE_LOCK}</th> * <td>On*</td> <td>Off</td> <td>Off</td> * </tr> * * <tr><th>{@link #SCREEN_DIM_WAKE_LOCK}</th> * <td>On</td> <td>Dim</td> <td>Off</td> * </tr></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* * <tr><th>{@link #SCREEN_BRIGHT_WAKE_LOCK}</th> * <td>On</td> <td>Bright</td> <td>Off</td> * </tr> * * <tr><th>{@link #FULL_WAKE_LOCK}</th> * <td>On</td> <td>Bright</td> <td>Bright</td> * </tr> * </tbody> * </table> * * <p>*<i>If you hold a partial wakelock, the CPU will continue to run, irrespective of any timers * and even after the user presses the power button. In all other wakelocks, the CPU will run, but * the user can still put the device to sleep using the power button.</i> * * <p>In addition, you can add two more flags, which affect behavior of the screen only. <i>These * flags have no effect when combined with a {@link #PARTIAL_WAKE_LOCK}</i>.</p> * <table border="2" width="85%" align="center" frame="hsides" rules="rows"></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>*</p> <p>* <thead></p> <p>* <tr><th>Flag Value</th> <th>Description</th></tr></p> <p>* </thead></p> <p>*</p> <p>* <tbody></p> <p>* <tr><th>{@link #ACQUIRE_CAUSES_WAKEUP}</th></p> <p>* <td>Normal wake locks don't actually turn on the illumination. Instead, they cause</p> <p>* the illumination to remain on once it turns on (e.g. from user activity). This flag</p> <p>* will force the screen and/or keyboard to turn on immediately, when the WakeLock is</p> <p>* acquired. A typical use would be for notifications which are important for the user to</p> <p>* see immediately.</td></p> <p>* </tr></p> <p>*</p> <p>* <tr><th>{@link #ON_AFTER_RELEASE}</th></p> <p>* <td>If this flag is set, the user activity timer will be reset when the WakeLock is</p> <p>* released, causing the illumination to remain on a bit longer. This can be used to</p> <p>* reduce flicker if you are cycling between wake lock conditions.</td></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * </tr> * </tbody> * </table> * * */ private static final int WAKE_BIT_CPU_STRONG = 1; private static final int WAKE_BIT_CPU_WEAK = 2; private static final int WAKE_BIT_SCREEN_DIM = 4; private static final int WAKE_BIT_SCREEN_BRIGHT = 8; private static final int WAKE_BIT_KEYBOARD_BRIGHT = 16; <u>SAMSUNG_PRIORART0005350, BatteryManager</u> /** * The BatteryManager class contains strings and constants used for values </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * in the ACTION_BATTERY_CHANGED Intent. */ public class BatteryManager { // values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values for "health" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_HEALTH_UNKNOWN = 1; public static final int BATTERY_HEALTH_GOOD = 2; public static final int BATTERY_HEALTH_OVERHEAT = 3; public static final int BATTERY_HEALTH_DEAD = 4; public static final int BATTERY_HEALTH_OVER_VOLTAGE = 5; public static final int BATTERY_HEALTH_UNSPECIFIED_FAILURE = 6; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent. // These must be powers of 2. /** Power source is an AC charger. */ public static final int BATTERY_PLUGGED_AC = 1; /** Power source is a USB port. */ public static final int BATTERY_PLUGGED_USB = 2; } <u>SAMSUNG_PRIORART0005350, BatteryStats</u> /** * A constant indicating a a wifi turn on timer * * {@hide} */ public static final int WIFI_TURNED_ON = 4; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * A constant indicating a full wifi lock timer * * {@hide} */ public static final int FULL_WIFI_LOCK = 5; /** * A constant indicating a scan wifi lock timer * * {@hide} */ public static final int SCAN_WIFI_LOCK = 6; /** * A constant indicating a wifi multicast timer *</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* {@hide} */ public static final int WIFI_MULTICAST_ENABLED = 7; /** * A constant indicating an audio turn on timer * * {@hide} */ public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Include all of the data in the stats, including previously saved data. */ public static final int STATS_TOTAL = 0; /** * Include only the last run in the stats. */ public static final int STATS_LAST = 1; /** * Include only the current run in the stats. */ public static final int STATS_CURRENT = 2; /** * Include only the run since the last time the device was unplugged in the stats. */</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int STATS_UNPLUGGED = 3; public abstract void noteWifiTurnedOnLocked(); public abstract void noteWifiTurnedOffLocked(); public abstract void noteFullWifiLockAcquiredLocked(); public abstract void noteFullWifiLockReleasedLocked(); public abstract void noteScanWifiLockAcquiredLocked(); public abstract void noteScanWifiLockReleasedLocked(); public abstract void noteWifiMulticastEnabledLocked(); public abstract void noteWifiMulticastDisabledLocked(); /** * Returns the time in microseconds that the screen has been on while the device was * running on battery. * * {@hide} */ public abstract long getScreenOnTime(long batteryRealtime, int which);</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int SCREEN_BRIGHTNESS_DARK = 0; public static final int SCREEN_BRIGHTNESS_DIM = 1; public static final int SCREEN_BRIGHTNESS_MEDIUM = 2; public static final int SCREEN_BRIGHTNESS_LIGHT = 3; public static final int SCREEN_BRIGHTNESS_BRIGHT = 4; public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4; /** * Returns the time in microseconds that wifi has been on while the device was * running on battery. * * {@hide}</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>*/ public abstract long getWifiOnTime(long batteryRealtime, int which); /** * Returns the time in microseconds that bluetooth has been on while the device was * running on battery. * * {@hide} */ public abstract long getBluetoothOnTime(long batteryRealtime, int which); /** * Return whether we are currently running on battery. */ public abstract boolean getIsOnBattery(); /** * Returns the time that the radio was on for data transfers.</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* @return the uptime in microseconds while unplugged * / public abstract long getRadioDataUptime(); /** * Returns the current battery realtime in microseconds. * * @param curTime the amount of elapsed realtime in microseconds. * / public abstract long getBatteryRealtime(long curTime); /** * Returns the battery percentage level at the last time the device was unplugged from power, or * the last time it booted on battery power. * / public abstract int getDischargeStartLevel();</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p><u>Android 2.2</u></p> <p><u>SAMSUNG PRIORART0005353, Power</u></p> <pre>/** * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; /** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; /** * Turn the screen on or off * * @param on Whether you want the screen on or off */ public static native int setScreenState(boolean on);</pre> <p><u>SAMSUNG PRIORART0005353, BatteryManager</u></p> <pre>/** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED};</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* integer indicating whether the device is plugged in to a power * source; 0 means it is on battery, other constants are different * types of power sources. */ public static final String EXTRA_PLUGGED = "plugged"; /** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer containing the current battery voltage level. */ public static final String EXTRA_VOLTAGE = "voltage"; /** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer containing the current battery temperature. */ public static final String EXTRA_TEMPERATURE = "temperature";</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * String describing the technology of the current battery. */ public static final String EXTRA_TECHNOLOGY = "technology"; // values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent. // These must be powers of 2. /** Power source is an AC charger. */ public static final int BATTERY_PLUGGED_AC = 1; /** Power source is a USB port. */</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int BATTERY_PLUGGED_USB = 2;</pre> <p><u>SAMSUNG_PRIORART0005353, BatteryStats</u></p> <pre>/** * A class providing access to battery usage statistics, including information on * wakelocks, processes, packages, and services. All times are represented in microseconds * except where indicated otherwise. * @hide */ /** * A constant indicating a a wifi turn on timer * * {@hide} */ public static final int WIFI_TURNED_ON = 4;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * A constant indicating an audio turn on timer * * {@hide} */ public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8; public static final int SIGNAL_STRENGTH_NONE_OR_UNKNOWN = 0; public static final int SIGNAL_STRENGTH_POOR = 1; public static final int SIGNAL_STRENGTH_MODERATE = 2;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int SIGNAL_STRENGTH_GOOD = 3; public static final int SIGNAL_STRENGTH_GREAT = 4; static final String[] SIGNAL_STRENGTH_NAMES = { "none", "poor", "moderate", "good", "great" }; public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4;</pre> <p><u>GOOG-HEADWATER-00000092, Google I/O 2009 - Coding for Life -- Battery Life, That Is (June 2, 2009)</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 2:</p> <h2>Coding for Life--Battery Life, That Is</h2> <p>Jeff Sharkey May 27, 2009</p> <p>Post your questions for this talk on Google Moderator: code.google.com/events/io/questions</p> <p>Google </p> <hr/> <p>GOOG-HEADWATER-000000093</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 3:</p> <h2>Why does this matter?</h2> <ul style="list-style-type: none">● Phones primarily run on battery power, and each device has a "battery budget"<ul style="list-style-type: none">○ When it's gone, it's gone○ Apps need to work together to be good citizens of that shared resource○ Current measured in mA, battery capacity in mAh● HTC Dream: 1150mAh● HTC Magic: 1350mAh● Samsung I7500: 1500mAh● Asus Eee PC: 5800mAh <div><p>GOOG-HEADWATER-000000094</p></div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps																																																				
	<p>See, e.g., GOOG-HEADWATER-00000092 at 4:</p> <div><h3>Where does it all go?</h3><p>Source: Values measured using an industrial power monitor at 5kHz sampling rate, and taking average power with lowest standard deviation.</p><p>■ Baseline usage ■ Specific item</p><table border="1"><thead><tr><th>Device State / Activity</th><th>Baseline usage (mA)</th><th>Specific item (mA)</th><th>Total (mA)</th></tr></thead><tbody><tr><td>Airplane</td><td>~10</td><td>~10</td><td>~20</td></tr><tr><td>3G idle</td><td>~10</td><td>~10</td><td>~20</td></tr><tr><td>EDGE idle</td><td>~10</td><td>~10</td><td>~20</td></tr><tr><td>WiFi idle</td><td>~10</td><td>~10</td><td>~20</td></tr><tr><td>LCD normal</td><td>~10</td><td>~80</td><td>~90</td></tr><tr><td>CPU 50%</td><td>~90</td><td>~50</td><td>~140</td></tr><tr><td>CPU full</td><td>~90</td><td>~110</td><td>~200</td></tr><tr><td>Game sensors</td><td>~140</td><td>~80</td><td>~220</td></tr><tr><td>GPS radio</td><td>~140</td><td>~90</td><td>~230</td></tr><tr><td>3G full</td><td>~140</td><td>~160</td><td>~300</td></tr><tr><td>EDGE full</td><td>~140</td><td>~250</td><td>~390</td></tr><tr><td>WiFi full</td><td>~140</td><td>~280</td><td>~420</td></tr></tbody></table><p>Google 09 O</p><p>GOOG-HEADWATER-00000095</p></div>	Device State / Activity	Baseline usage (mA)	Specific item (mA)	Total (mA)	Airplane	~10	~10	~20	3G idle	~10	~10	~20	EDGE idle	~10	~10	~20	WiFi idle	~10	~10	~20	LCD normal	~10	~80	~90	CPU 50%	~90	~50	~140	CPU full	~90	~110	~200	Game sensors	~140	~80	~220	GPS radio	~140	~90	~230	3G full	~140	~160	~300	EDGE full	~140	~250	~390	WiFi full	~140	~280	~420
Device State / Activity	Baseline usage (mA)	Specific item (mA)	Total (mA)																																																		
Airplane	~10	~10	~20																																																		
3G idle	~10	~10	~20																																																		
EDGE idle	~10	~10	~20																																																		
WiFi idle	~10	~10	~20																																																		
LCD normal	~10	~80	~90																																																		
CPU 50%	~90	~50	~140																																																		
CPU full	~90	~110	~200																																																		
Game sensors	~140	~80	~220																																																		
GPS radio	~140	~90	~230																																																		
3G full	~140	~160	~300																																																		
EDGE full	~140	~250	~390																																																		
WiFi full	~140	~280	~420																																																		

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 9:</p> <h2 data-bbox="583 370 1117 423">How can we do better?</h2> <h3 data-bbox="583 431 777 475">Networking</h3> <ul style="list-style-type: none"> <li data-bbox="573 509 1482 553">● Check network connection, wait for 3G or WiFi <pre data-bbox="583 662 1644 992"> ConnectivityManager mConnectivity; TelephonyManager mTelephony; // Skip if no connection, or background data disabled NetworkInfo info = mConnectivity.getActiveNetworkInfo(); if (info == null !mConnectivity.getBackgroundDataSetting()) { return false; } </pre>  <div data-bbox="1570 1175 1770 1235"> Google 09 IO </div> <hr data-bbox="554 1284 1797 1295"/> <p data-bbox="1528 1295 1780 1317">GOOG-HEADWATER-00000100</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 11:</p> <p>How can we do better? Networking</p> <ul style="list-style-type: none"> ● Check network connection, wait for 3G or WiFi <pre>// Only update if WiFi or 3G is connected and not roaming int netType = info.getType(); int netSubtype = info.getSubtype(); if (netType == ConnectivityManager.TYPE_WIFI) { return info.isConnected(); } else if (netType == ConnectivityManager.TYPE_MOBILE && netSubtype == TelephonyManager.NETWORK_TYPE_UMTS && !mTelephony.isNetworkRoaming()) { return info.isConnected(); } else { return false; }</pre> <div data-bbox="1558 1192 1764 1252">  </div> <div data-bbox="1512 1310 1780 1333"> <p>GOOG-HEADWATER-00000101</p> </div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 16:</p> <h2>How can we do better?</h2> <p>Foreground apps</p> <ul style="list-style-type: none">● Wakelocks are costly if forgotten<ul style="list-style-type: none">○ Pick the lowest level possible, and use specific timeouts to work around unforeseen bugs○ Consider using <code>android:keepScreenOn</code> to ensure correctness <pre><LinearLayout android:orientation="vertical" android:layout_width="fill_parent" android:layout_height="fill_parent" android:keepScreenOn="true"></pre> <div></div> <div></div> <p>GOOG-HEADWATER-00000107</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<i>See, e.g.</i> , GOOG-HEADWATER-000000092 at 18:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433





'433 Claims	Android Device with One or More Apps
	<p>How can we do better? Foreground apps</p> <ul style="list-style-type: none">● Use coarse network location, it's much cheaper<ul style="list-style-type: none">○ GPS: 25 seconds * 140mA = 1mAh○ Network: 2 seconds * 180mA = 0.1mAh● 1.5 uses AGPS when network available● GPS time-to-fix varies wildly based on environment, and desired accuracy, and might outright fail<ul style="list-style-type: none">○ Just like wake-locks, location updates can continue after onPause(), so make sure to unregister○ If all apps unregister correctly, user can leave GPS enabled in Settings <div></div> <div> GOOG-HEADWATER-00000109</div> <p>See, e.g., GOOG-HEADWATER-00000092 at 20:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Foreground apps</p> <ul style="list-style-type: none">● Accelerometer/magnetic sensors<ul style="list-style-type: none">○ Normal: 10mA (used for orientation detection)○ UI: 15mA (about 1 per second)○ Game: 80mA○ Fastest: 90mA● Same cost for accelerometer, magnetic, orientation sensors on HTC Dream <div><p>GOOG-HEADWATER-00000111</p></div> <p>See, e.g., GOOG-HEADWATER-00000092 at 22:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p data-bbox="590 316 1119 362">How can we do better?</p> <p data-bbox="590 373 884 412">Background apps</p> <ul data-bbox="579 451 1690 966" style="list-style-type: none"><li data-bbox="579 451 1690 597">● Services should be short-lived; these aren't daemons<ul data-bbox="630 506 1690 597" style="list-style-type: none"><li data-bbox="630 506 1690 597">○ Each process costs 2MB and risks being killed/restarted as foreground apps need memory<li data-bbox="630 714 1690 805">○ Otherwise, keep memory usage low so you're not the first target<li data-bbox="579 820 1690 966">● Trigger wake-up through AlarmManager or with <receiver> manifest elements<ul data-bbox="630 924 1087 966" style="list-style-type: none"><li data-bbox="630 924 1087 966">○ stopSelf() when finished <div data-bbox="1566 1112 1770 1174"></div> <div data-bbox="1518 1230 1785 1252"> GOOG-HEADWATER-00000113</div> <p data-bbox="556 1284 1110 1312"><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 26:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Background apps</p> <ul style="list-style-type: none">●Dynamically enabling/disabling <receiver> components in manifest, especially when no-ops <pre><receiver android:name=".ConnectivityReceiver" android:enabled="false"> ... </receiver></pre> <pre>ComponentName receiver = new ComponentName(context, ConnectivityReceiver.class); PackageManager pm = context.getPackageManager(); pm.setComponentEnabledSetting(receiver, PackageManager.COMPONENT_ENABLED_STATE_ENABLED, PackageManager.DONT_KILL_APP);</pre> <div>Google 09 O</div> <div>GOOG-HEADWATER-00000117</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 27:</p> <h2>How can we do better?</h2> <h3>Background apps</h3> <ul style="list-style-type: none"> • Checking current battery and network state before running a full update <pre> public void onCreate() { // Register for sticky broadcast and send default registerReceiver(mReceiver, mFilter); mHandler.sendMessageDelayed(MSG_BATT, 1000); } IntentFilter mFilter = new IntentFilter(Intent.ACTION_BATTERY_CHANGED); BroadcastReceiver mReceiver = new BroadcastReceiver() { public void onReceive(Context context, Intent intent) { // Found sticky broadcast, so trigger update unregisterReceiver(mReceiver); mHandler.removeMessages(MSG_BATT); mHandler.obtainMessage(MSG_BATT, intent).sendToTarget(); } }; </pre>  <p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 29:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
	<p data-bbox="575 321 1100 375">Users will be watching!</p> <div data-bbox="552 440 947 1029">  </div> <ul data-bbox="995 461 1680 1133" style="list-style-type: none"> ● SpareParts has "Battery history" <ul style="list-style-type: none"> ○ 1.5 is already keeping stats on which apps are using CPU, network, wakelocks ○ Simplified version coming in future, and users will uninstall apps that abuse battery ● Consider giving users options for battery usage, like update intervals, and check the "no background data" flag <div data-bbox="1654 423 1730 521">  </div> <div data-bbox="1556 1127 1759 1187">  </div> <p data-bbox="1514 1247 1766 1263">GOOG-HEADWATER-00000120</p> <p data-bbox="554 1295 1108 1321"><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 30:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>Takeaways</p> <ul style="list-style-type: none">● Use an efficient parser and GZIP to make best use of network and CPU resources● Services that sleep or poll are bad, use <receiver> and AlarmManager instead<ul style="list-style-type: none">○ Disable manifest elements when no-op○ Wake up along with everyone else (inexact alarms)● Wait for better network/battery for bulk transfers● Give users choices about background behavior <p>Google 09 </p> <p>GOOG-HEADWATER-00000121</p>
[15] The wireless end-user device of claim 1,	Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
<p>wherein the one or more processors are further configured to dynamically change the determination of whether to apply the one or more Internet activity access controls based on power control state changes for the WWAN modem.</p>	<p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c]. <u>In addition:</u></p> <p><u>Android 1.0</u></p> <p><u>SAMSUNG_PRIORART0005487, Power</u></p> <pre> /** * Wake lock that ensures that the CPU is running. The screen might * not be on. */ public static final int PARTIAL_WAKE_LOCK = 1; /** * Wake lock that ensures that the screen is on. */ public static final int FULL_WAKE_LOCK = 2; * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; /** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p><u>SAMSUNG PRIORART0005487, BatteryManager</u></p> <p>// values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5;</p> <p>// values for "health" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_HEALTH_UNKNOWN = 1; public static final int BATTERY_HEALTH_GOOD = 2; public static final int BATTERY_HEALTH_OVERHEAT = 3; public static final int BATTERY_HEALTH_DEAD = 4; public static final int BATTERY_HEALTH_OVER_VOLTAGE = 5; public static final int BATTERY_HEALTH_UNSPECIFIED_FAILURE = 6;</p> <p>// values of the "plugged" field in the ACTION_BATTERY_CHANGED intent public static final int BATTERY_PLUGGED_AC = 1; public static final int BATTERY_PLUGGED_USB = 2;</p> <p><u>Android 1.6</u></p> <p><u>SAMSUNG PRIORART0005350, Power</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; /** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; SAMSUNG_PRIORART0005350, PowerManager /** * This class gives you control of the power state of the device. </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* * <p>Device battery life will be significantly affected by the use of this API. Do not * acquire WakeLocks unless you really need them, use the minimum levels possible, and be sure * to release it as soon as you can. * * <p>You can obtain an instance of this class by calling * {@link android.content.Context#getService(java.lang.String) Context.getService()}. * * <p>The primary API you'll use is {@link #newWakeLock(int, String) newWakeLock()}. This will * create a {@link PowerManager.WakeLock} object. You can then use methods on this object to * control the power state of the device. In practice it's quite simple: * * {@samplecode * PowerManager pm = (PowerManager) getService(Context.POWER_SERVICE); * PowerManager.WakeLock wl = pm.newWakeLock(PowerManager.SCREEN_DIM_WAKE_LOCK, "My Tag"); * wl.acquire(); * ..screen will stay on during this section.. * wl.release();</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * } * * <p>The following flags are defined, with varying effects on system power. <i>These flags are * mutually exclusive - you may only specify one of them.</i> * <table border="2" width="85%" align="center" frame="hsides" rules="rows"> * * <thead> * <tr><th>Flag Value</th> * <th>CPU</th> <th>Screen</th> <th>Keyboard</th></tr> * </thead> * * <tbody> * <tr><th>{@link #PARTIAL_WAKE_LOCK}</th> * <td>On</td> <td>Off</td> <td>Off</td> * </tr> * * <tr><th>{@link #SCREEN_DIM_WAKE_LOCK}</th> * <td>On</td> <td>Dim</td> <td>Off</td> </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* </tr></p> <p>* <tr><th>{@link #SCREEN_BRIGHT_WAKE_LOCK}</th></p> <p>* <td>On</td> <td>Bright</td> <td>Off</td></p> <p>* </tr></p> <p>* <tr><th>{@link #FULL_WAKE_LOCK}</th></p> <p>* <td>On</td> <td>Bright</td> <td>Bright</td></p> <p>* </tr></p> <p>* </tbody></p> <p>* </table></p> <p>* <p>*<i>If you hold a partial wakelock, the CPU will continue to run, irrespective of any timers and even after the user presses the power button. In all other wakelocks, the CPU will run, but the user can still put the device to sleep using the power button.</i></p> <p>* <p>In addition, you can add two more flags, which affect behavior of the screen only. <i>These flags have no effect when combined with a {@link #PARTIAL_WAKE_LOCK}.</i></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * <table border="2" width="85%" align="center" frame="hsides" rules="rows"> * * <thead> * <tr><th>Flag Value</th> <th>Description</th></tr> * </thead> * * <tbody> * <tr><th>{@link #ACQUIRE_CAUSES_WAKEUP}</th> * <td>Normal wake locks don't actually turn on the illumination. Instead, they cause * the illumination to remain on once it turns on (e.g. from user activity). This flag * will force the screen and/or keyboard to turn on immediately, when the WakeLock is * acquired. A typical use would be for notifications which are important for the user to * see immediately.</td> * </tr> * * <tr><th>{@link #ON_AFTER_RELEASE}</th> * <td>If this flag is set, the user activity timer will be reset when the WakeLock is * released, causing the illumination to remain on a bit longer. This can be used to </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * reduce flicker if you are cycling between wake lock conditions.</td> * </tr> * </tbody> * </table> * * */ private static final int WAKE_BIT_CPU_STRONG = 1; private static final int WAKE_BIT_CPU_WEAK = 2; private static final int WAKE_BIT_SCREEN_DIM = 4; private static final int WAKE_BIT_SCREEN_BRIGHT = 8; private static final int WAKE_BIT_KEYBOARD_BRIGHT = 16; <u>SAMSUNG_PRIORART0005350, BatteryManager</u> <u>/**</u> </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* The BatteryManager class contains strings and constants used for values * in the ACTION_BATTERY_CHANGED Intent. */ public class BatteryManager { // values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values for "health" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_HEALTH_UNKNOWN = 1; public static final int BATTERY_HEALTH_GOOD = 2; public static final int BATTERY_HEALTH_OVERHEAT = 3; public static final int BATTERY_HEALTH_DEAD = 4; public static final int BATTERY_HEALTH_OVER_VOLTAGE = 5;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int BATTERY_HEALTH_UNSPECIFIED_FAILURE = 6; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent. // These must be powers of 2. /** Power source is an AC charger. */ public static final int BATTERY_PLUGGED_AC = 1; /** Power source is a USB port. */ public static final int BATTERY_PLUGGED_USB = 2; }</pre> <p><u>SAMSUNG_PRIORART0005350, BatteryStats</u></p> <pre>/** * A constant indicating a a wifi turn on timer * * {@hide} */</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int WIFI_TURNED_ON = 4; /** * A constant indicating a full wifi lock timer * * {@hide} */ public static final int FULL_WIFI_LOCK = 5; /** * A constant indicating a scan wifi lock timer * * {@hide} */ public static final int SCAN_WIFI_LOCK = 6; /** * A constant indicating a wifi multicast timer</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* * {@hide} */ public static final int WIFI_MULTICAST_ENABLED = 7; /** * A constant indicating an audio turn on timer * * {@hide} */ public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Include all of the data in the stats, including previously saved data. */ public static final int STATS_TOTAL = 0; /** * Include only the last run in the stats. */ public static final int STATS_LAST = 1; /** * Include only the current run in the stats. */ public static final int STATS_CURRENT = 2; /** * Include only the run since the last time the device was unplugged in the stats.</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>*/ public static final int STATS_UNPLUGGED = 3; public abstract void noteWifiTurnedOnLocked(); public abstract void noteWifiTurnedOffLocked(); public abstract void noteFullWifiLockAcquiredLocked(); public abstract void noteFullWifiLockReleasedLocked(); public abstract void noteScanWifiLockAcquiredLocked(); public abstract void noteScanWifiLockReleasedLocked(); public abstract void noteWifiMulticastEnabledLocked(); public abstract void noteWifiMulticastDisabledLocked(); /** * Returns the time in microseconds that the screen has been on while the device was * running on battery. * * {@hide} */</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public abstract long getScreenOnTime(long batteryRealtime, int which); public static final int SCREEN_BRIGHTNESS_DARK = 0; public static final int SCREEN_BRIGHTNESS_DIM = 1; public static final int SCREEN_BRIGHTNESS_MEDIUM = 2; public static final int SCREEN_BRIGHTNESS_LIGHT = 3; public static final int SCREEN_BRIGHTNESS_BRIGHT = 4; public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4; /** * Returns the time in microseconds that wifi has been on while the device was * running on battery. * </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* {@hide} */ public abstract long getWifiOnTime(long batteryRealtime, int which); /** * Returns the time in microseconds that bluetooth has been on while the device was * running on battery. * * {@hide} */ public abstract long getBluetoothOnTime(long batteryRealtime, int which); /** * Return whether we are currently running on battery. */ public abstract boolean getIsOnBattery(); /**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * Returns the time that the radio was on for data transfers. * @return the uptime in microseconds while unplugged */ public abstract long getRadioDataUptime(); /** * Returns the current battery realtime in microseconds. * * @param curTime the amount of elapsed realtime in microseconds. */ public abstract long getBatteryRealtime(long curTime); /** * Returns the battery percentage level at the last time the device was unplugged from power, or * the last time it booted on battery power. */ public abstract int getDischargeStartLevel(); </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p><u>Android 2.2</u></p> <p><u>SAMSUNG PRIORART0005353, Power</u></p> <pre>/** * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; /** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; /** * Turn the screen on or off * * @param on Whether you want the screen on or off */ public static native int setScreenState(boolean on);</pre> <p><u>SAMSUNG PRIORART0005353, BatteryManager</u></p> <pre>/**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer indicating whether the device is plugged in to a power * source; 0 means it is on battery, other constants are different * types of power sources. */ public static final String EXTRA_PLUGGED = "plugged"; /** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer containing the current battery voltage level. */ public static final String EXTRA_VOLTAGE = "voltage"; /** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer containing the current battery temperature. */ public static final String EXTRA_TEMPERATURE = "temperature"; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * String describing the technology of the current battery. */ public static final String EXTRA_TECHNOLOGY = "technology"; // values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent. // These must be powers of 2. /** Power source is an AC charger. */ public static final int BATTERY_PLUGGED_AC = 1;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** Power source is a USB port. */ public static final int BATTERY_PLUGGED_USB = 2;</pre> <p><u>SAMSUNG PRIORART0005353, BatteryStats</u></p> <pre>/** * A class providing access to battery usage statistics, including information on * wakelocks, processes, packages, and services. All times are represented in microseconds * except where indicated otherwise. * @hide */ /** * A constant indicating a a wifi turn on timer * * {@hide} */</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int WIFI_TURNED_ON = 4; /** * A constant indicating an audio turn on timer * * {@hide} */ public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8; public static final int SIGNAL_STRENGTH_NONE_OR_UNKNOWN = 0; public static final int SIGNAL_STRENGTH_POOR = 1;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int SIGNAL_STRENGTH_MODERATE = 2; public static final int SIGNAL_STRENGTH_GOOD = 3; public static final int SIGNAL_STRENGTH_GREAT = 4; static final String[] SIGNAL_STRENGTH_NAMES = { "none", "poor", "moderate", "good", "great" }; public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4;</pre> <p><u>GOOG-HEADWATER-00000092, Google I/O 2009 - Coding for Life -- Battery Life, That Is (June 2, 2009)</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 2:</p> <h2>Coding for Life--Battery Life, That Is</h2> <p>Jeff Sharkey May 27, 2009</p> <p>Post your questions for this talk on Google Moderator: code.google.com/events/io/questions</p> <p>Google </p> <hr/> <p>GOOG-HEADWATER-000000093</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 3:</p> <h2>Why does this matter?</h2> <ul style="list-style-type: none">• Phones primarily run on battery power, and each device has a "battery budget"<ul style="list-style-type: none">○ When it's gone, it's gone○ Apps need to work together to be good citizens of that shared resource○ Current measured in mA, battery capacity in mAh• HTC Dream: 1150mAh• HTC Magic: 1350mAh• Samsung I7500: 1500mAh• Asus Eee PC: 5800mAh <div></div> <p>GOOG-HEADWATER-000000094</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p data-bbox="554 318 1094 347">See, e.g., GOOG-HEADWATER-00000092 at 4:</p> <div data-bbox="554 347 1797 1305"> <h3 data-bbox="663 418 1121 467">Where does it all go?</h3>  <p data-bbox="898 591 1297 659">Source: Values measured using an industrial power monitor at 5kHz sampling rate, and taking average power with lowest standard deviation.</p> <p data-bbox="947 699 1199 781"> Baseline usage Specific item </p> <p data-bbox="659 854 690 902" style="transform: rotate(-90deg);">mA</p> <p data-bbox="1591 1187 1772 1227">Google 09 O</p> <p data-bbox="1549 1284 1780 1300">GOOG-HEADWATER-00000095</p> </div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 9:</p> <h2>How can we do better?</h2> <h3>Networking</h3> <ul style="list-style-type: none">● Check network connection, wait for 3G or WiFi <pre>ConnectivityManager mConnectivity; TelephonyManager mTelephony; // Skip if no connection, or background data disabled NetworkInfo info = mConnectivity.getActiveNetworkInfo(); if (info == null !mConnectivity.getBackgroundDataSetting()) { return false; }</pre>  <div>Google 09 IO</div> <div>GOOG-HEADWATER-00000100</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 11:</p> <p>How can we do better? Networking</p> <ul style="list-style-type: none">● Check network connection, wait for 3G or WiFi <pre>// Only update if WiFi or 3G is connected and not roaming int netType = info.getType(); int netSubtype = info.getSubtype(); if (netType == ConnectivityManager.TYPE_WIFI) { return info.isConnected(); } else if (netType == ConnectivityManager.TYPE_MOBILE && netSubtype == TelephonyManager.NETWORK_TYPE_UMTS && !mTelephony.isNetworkRoaming()) { return info.isConnected(); } else { return false; }</pre> <p>Google 09 O</p> <p>GOOG-HEADWATER-00000101</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 16:</p> <h2>How can we do better?</h2> <p>Foreground apps</p> <ul style="list-style-type: none">● Wakelocks are costly if forgotten<ul style="list-style-type: none">○ Pick the lowest level possible, and use specific timeouts to work around unforeseen bugs○ Consider using <code>android:keepScreenOn</code> to ensure correctness <pre><LinearLayout android:orientation="vertical" android:layout_width="fill_parent" android:layout_height="fill_parent" android:keepScreenOn="true"></pre> <div></div> <div> GOOG-HEADWATER-00000107</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<i>See, e.g.</i> , GOOG-HEADWATER-000000092 at 18:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p>How can we do better? Foreground apps</p> <ul style="list-style-type: none">● Use coarse network location, it's much cheaper<ul style="list-style-type: none">○ GPS: 25 seconds * 140mA = 1mAh○ Network: 2 seconds * 180mA = 0.1mAh● 1.5 uses AGPS when network available● GPS time-to-fix varies wildly based on environment, and desired accuracy, and might outright fail<ul style="list-style-type: none">○ Just like wake-locks, location updates can continue after onPause(), so make sure to unregister○ If all apps unregister correctly, user can leave GPS enabled in Settings <p></p> <p>Google </p> <p>GOOG-HEADWATER-00000109</p> <p>See, e.g., GOOG-HEADWATER-00000092 at 20:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Foreground apps</p> <ul style="list-style-type: none">● Accelerometer/magnetic sensors<ul style="list-style-type: none">○ Normal: 10mA (used for orientation detection)○ UI: 15mA (about 1 per second)○ Game: 80mA○ Fastest: 90mA● Same cost for accelerometer, magnetic, orientation sensors on HTC Dream <div>  GOOG-HEADWATER-00000111</div> <p>See, e.g., GOOG-HEADWATER-00000092 at 22:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p data-bbox="590 316 1119 362">How can we do better?</p> <p data-bbox="590 373 884 412">Background apps</p> <ul data-bbox="579 451 1692 966" style="list-style-type: none"><li data-bbox="579 451 1692 597">● Services should be short-lived; these aren't daemons<ul data-bbox="630 506 1692 597" style="list-style-type: none"><li data-bbox="630 506 1692 597">○ Each process costs 2MB and risks being killed/restarted as foreground apps need memory<li data-bbox="630 714 1692 805">○ Otherwise, keep memory usage low so you're not the first target<li data-bbox="579 820 1692 966">● Trigger wake-up through AlarmManager or with <receiver> manifest elements<ul data-bbox="630 924 1087 966" style="list-style-type: none"><li data-bbox="630 924 1087 966">○ stopSelf() when finished <div data-bbox="1566 1112 1770 1174"></div> <div data-bbox="1518 1230 1785 1252"> GOOG-HEADWATER-00000113</div> <p data-bbox="556 1284 1110 1312"><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 26:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Background apps</p> <ul style="list-style-type: none">●Dynamically enabling/disabling <receiver> components in manifest, especially when no-ops <pre><receiver android:name=".ConnectivityReceiver" android:enabled="false"> ... </receiver></pre> <pre>ComponentName receiver = new ComponentName(context, ConnectivityReceiver.class); PackageManager pm = context.getPackageManager(); pm.setComponentEnabledSetting(receiver, PackageManager.COMPONENT_ENABLED_STATE_ENABLED, PackageManager.DONT_KILL_APP);</pre> <div>Google 09 O</div> <div>GOOG-HEADWATER-00000117</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 27:</p> <p>How can we do better?</p> <p>Background apps</p> <ul style="list-style-type: none">• Checking current battery and network state before running a full update <pre>public void onCreate() { // Register for sticky broadcast and send default registerReceiver(mReceiver, mFilter); mHandler.sendMessageDelayed(MSG_BATT, 1000); } IntentFilter mFilter = new IntentFilter(Intent.ACTION_BATTERY_CHANGED); BroadcastReceiver mReceiver = new BroadcastReceiver() { public void onReceive(Context context, Intent intent) { // Found sticky broadcast, so trigger update unregisterReceiver(mReceiver); mHandler.removeMessages(MSG_BATT); mHandler.obtainMessage(MSG_BATT, intent).sendToTarget(); } };</pre>  <p>GOOG-HEADWATER-00000118</p> <p>See, e.g., GOOG-HEADWATER-00000092 at 29:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p data-bbox="575 321 1100 375">Users will be watching!</p> <div data-bbox="552 440 947 1029">  </div> <ul data-bbox="995 461 1680 1133" style="list-style-type: none"> ● SpareParts has "Battery history" <ul style="list-style-type: none"> ○ 1.5 is already keeping stats on which apps are using CPU, network, wakelocks ○ Simplified version coming in future, and users will uninstall apps that abuse battery ● Consider giving users options for battery usage, like update intervals, and check the "no background data" flag <div data-bbox="1562 1127 1759 1187">  </div> <p data-bbox="1520 1247 1766 1263">GOOG-HEADWATER-00000120</p> <p data-bbox="554 1295 1108 1321">See, e.g., GOOG-HEADWATER-00000092 at 30:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p data-bbox="583 329 846 381">Takeaways</p> <ul data-bbox="569 467 1587 878" style="list-style-type: none"> ● Use an efficient parser and GZIP to make best use of network and CPU resources ● Services that sleep or poll are bad, use <receiver> and AlarmManager instead <ul data-bbox="617 678 1575 776" style="list-style-type: none"> ○ Disable manifest elements when no-op ○ Wake up along with everyone else (inexact alarms) ● Wait for better network/battery for bulk transfers ● Give users choices about background behavior <div data-bbox="1570 1133 1766 1192">  </div> <div data-bbox="1528 1252 1776 1271"> <p>GOOG-HEADWATER-00000121</p> </div>
<p data-bbox="201 1320 520 1417">[16] The wireless end-user device of claim 1, wherein the one or more</p>	<p data-bbox="554 1320 1875 1385">Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
Internet activity access controls further limit the allowed network activity to particular time windows.	<i>See, e.g.</i> , the disclosures identified for claims [1 pre]-[1c].
[17] The wireless end-user device of claim 1, wherein the one or more processors are further configured to update at least a portion of the network service activity control policy set based on information received from a network element.	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.</i>, the disclosures identified for claims [1 pre]-[1c].</p>
[18] The wireless end-user device of claim 1, wherein the one or more Internet activity access controls further prevent the first Internet access request from causing a change to a power state of the modem.	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.</i>, the disclosures identified for claims [1 pre]-[1c].</p> <p><u>Android 1.0</u></p> <p><u>SAMSUNG PRIORART0005487, Power</u></p> <p>/**</p> <p>* Wake lock that ensures that the CPU is running. The screen might</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * not be on. */ public static final int PARTIAL_WAKE_LOCK = 1; /** * Wake lock that ensures that the screen is on. */ public static final int FULL_WAKE_LOCK = 2; * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; /** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; <u>SAMSUNG PRIORART0005487, BatteryManager</u> // values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values for "health" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_HEALTH_UNKNOWN = 1; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public static final int BATTERY_HEALTH_GOOD = 2; public static final int BATTERY_HEALTH_OVERHEAT = 3; public static final int BATTERY_HEALTH_DEAD = 4; public static final int BATTERY_HEALTH_OVER_VOLTAGE = 5; public static final int BATTERY_HEALTH_UNSPECIFIED_FAILURE = 6; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent public static final int BATTERY_PLUGGED_AC = 1; public static final int BATTERY_PLUGGED_USB = 2; </pre> <p><u>Android 1.6</u></p> <p><u>SAMSUNG PRIORART0005350, Power</u></p> <p><u>/**</u></p> <p><u>* Brightness value to use when battery is low</u></p> <p><u>*/</u></p> <p><u>public static final int BRIGHTNESS_LOW_BATTERY = 10;</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> /** * Threshold for BRIGHTNESS LOW BATTERY (percentage) * Screen will stay dim if battery level is <= LOW BATTERY THRESHOLD */ public static final int LOW BATTERY THRESHOLD = 10; SAMSUNG_PRIORART0005350, PowerManager /** * This class gives you control of the power state of the device. * * <p>Device battery life will be significantly affected by the use of this API. Do not * acquire WakeLocks unless you really need them, use the minimum levels possible, and be sure * to release it as soon as you can. * * <p>You can obtain an instance of this class by calling * {@link android.content.Context#getSystemService(java.lang.String) Context.getSystemService()}. </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* * <p>The primary API you'll use is {@link #newWakeLock(int, String) newWakeLock()}. This will * create a {@link PowerManager.WakeLock} object. You can then use methods on this object to * control the power state of the device. In practice it's quite simple: * * {@samplecode * PowerManager pm = (PowerManager) getSystemService(Context.POWER_SERVICE); * PowerManager.WakeLock wl = pm.newWakeLock(PowerManager.SCREEN_DIM_WAKE_LOCK, "My Tag"); * wl.acquire(); * ..screen will stay on during this section.. * wl.release(); * } * * <p>The following flags are defined, with varying effects on system power. <i>These flags are * mutually exclusive - you may only specify one of them.</i> * <table border="2" width="85%" align="center" frame="hsides" rules="rows"> * * <thead></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * <tr><th>Flag Value</th> * <th>CPU</th> <th>Screen</th> <th>Keyboard</th></tr> * </thead> * * <tbody> * <tr><th>{@link #PARTIAL_WAKE_LOCK}</th> * <td>On*</td> <td>Off</td> <td>Off</td> * </tr> * * <tr><th>{@link #SCREEN_DIM_WAKE_LOCK}</th> * <td>On</td> <td>Dim</td> <td>Off</td> * </tr> * * <tr><th>{@link #SCREEN_BRIGHT_WAKE_LOCK}</th> * <td>On</td> <td>Bright</td> <td>Off</td> * </tr> * * <tr><th>{@link #FULL_WAKE_LOCK}</th> </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* <td>On</td> <td>Bright</td> <td>Bright</td></p> <p>* </tr></p> <p>* </tbody></p> <p>* </table></p> <p>*</p> <p>* <p>*<i>If you hold a partial wakelock, the CPU will continue to run, irrespective of any timers</p> <p>* and even after the user presses the power button. In all other wakelocks, the CPU will run, but</p> <p>* the user can still put the device to sleep using the power button.</i></p></p> <p>*</p> <p>* <p>In addition, you can add two more flags, which affect behavior of the screen only. <i>These</p> <p>* flags have no effect when combined with a {@link #PARTIAL_WAKE_LOCK}.</i></p> <p>* <table border="2" width="85%" align="center" frame="hsides" rules="rows"></p> <p>*</p> <p>* <thead></p> <p>* <tr><th>Flag Value</th> <th>Description</th></tr></p> <p>* </thead></p> <p>*</p> <p>* <tbody></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>* <tr><th>{@link #ACQUIRE_CAUSES_WAKEUP}</th></p> <p>* <td>Normal wake locks don't actually turn on the illumination. Instead, they cause</p> <p>* the illumination to remain on once it turns on (e.g. from user activity). This flag</p> <p>* will force the screen and/or keyboard to turn on immediately, when the WakeLock is</p> <p>* acquired. A typical use would be for notifications which are important for the user to</p> <p>* see immediately.</td></p> <p>* </tr></p> <p>* </p> <p>* <tr><th>{@link #ON_AFTER_RELEASE}</th></p> <p>* <td>If this flag is set, the user activity timer will be reset when the WakeLock is</p> <p>* released, causing the illumination to remain on a bit longer. This can be used to</p> <p>* reduce flicker if you are cycling between wake lock conditions.</td></p> <p>* </tr></p> <p>* </tbody></p> <p>* </table></p> <p>* </p> <p>* </p> <p>* /</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>private static final int WAKE_BIT_CPU_STRONG = 1; private static final int WAKE_BIT_CPU_WEAK = 2; private static final int WAKE_BIT_SCREEN_DIM = 4; private static final int WAKE_BIT_SCREEN_BRIGHT = 8; private static final int WAKE_BIT_KEYBOARD_BRIGHT = 16;</pre> <p><u>SAMSUNG PRIORART0005350, BatteryManager</u></p> <p><u>/**</u></p> <p>* The BatteryManager class contains strings and constants used for values</p> <p>* in the ACTION_BATTERY_CHANGED Intent.</p> <p>*/</p> <pre>public class BatteryManager { // values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1;</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values for "health" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_HEALTH_UNKNOWN = 1; public static final int BATTERY_HEALTH_GOOD = 2; public static final int BATTERY_HEALTH_OVERHEAT = 3; public static final int BATTERY_HEALTH_DEAD = 4; public static final int BATTERY_HEALTH_OVER_VOLTAGE = 5; public static final int BATTERY_HEALTH_UNSPECIFIED_FAILURE = 6; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent. // These must be powers of 2. /** Power source is an AC charger. */ public static final int BATTERY_PLUGGED_AC = 1; /** Power source is a USB port. */ </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int BATTERY_PLUGGED_USB = 2; }</pre> <p><u>SAMSUNG PRIORART0005350, BatteryStats</u></p> <pre>/** * A constant indicating a a wifi turn on timer * * {@hide} */ public static final int WIFI_TURNED_ON = 4; /** * A constant indicating a full wifi lock timer * * {@hide} */</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int FULL_WIFI_LOCK = 5; /** * A constant indicating a scan wifi lock timer * * {@hide} */ public static final int SCAN_WIFI_LOCK = 6; /** * A constant indicating a wifi multicast timer * * {@hide} */ public static final int WIFI_MULTICAST_ENABLED = 7; /** * A constant indicating an audio turn on timer</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* * {@hide} */ public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8; /** * Include all of the data in the stats, including previously saved data. */ public static final int STATS_TOTAL = 0; /**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* Include only the last run in the stats. */ public static final int STATS_LAST = 1; /** * Include only the current run in the stats. */ public static final int STATS_CURRENT = 2; /** * Include only the run since the last time the device was unplugged in the stats. */ public static final int STATS_UNPLUGGED = 3; public abstract void noteWifiTurnedOnLocked(); public abstract void noteWifiTurnedOffLocked(); public abstract void noteFullWifiLockAcquiredLocked(); public abstract void noteFullWifiLockReleasedLocked();</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> public abstract void noteScanWifiLockAcquiredLocked(); public abstract void noteScanWifiLockReleasedLocked(); public abstract void noteWifiMulticastEnabledLocked(); public abstract void noteWifiMulticastDisabledLocked(); /** * Returns the time in microseconds that the screen has been on while the device was * running on battery. * * {@hide} */ public abstract long getScreenOnTime(long batteryRealtime, int which); public static final int SCREEN_BRIGHTNESS_DARK = 0; public static final int SCREEN_BRIGHTNESS_DIM = 1; public static final int SCREEN_BRIGHTNESS_MEDIUM = 2; public static final int SCREEN_BRIGHTNESS_LIGHT = 3; public static final int SCREEN_BRIGHTNESS_BRIGHT = 4; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4; /** * Returns the time in microseconds that wifi has been on while the device was * running on battery. * * {@hide} */ public abstract long getWifiOnTime(long batteryRealtime, int which); /** * Returns the time in microseconds that bluetooth has been on while the device was * running on battery.</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>* * {@hide} */ public abstract long getBluetoothOnTime(long batteryRealtime, int which); /** * Return whether we are currently running on battery. */ public abstract boolean getIsOnBattery(); /** * Returns the time that the radio was on for data transfers. * @return the uptime in microseconds while unplugged */ public abstract long getRadioDataUptime(); /** * Returns the current battery realtime in microseconds.</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre> * * @param curTime the amount of elapsed realtime in microseconds. */ public abstract long getBatteryRealtime(long curTime); /** * Returns the battery percentage level at the last time the device was unplugged from power, or * the last time it booted on battery power. */ public abstract int getDischargeStartLevel(); </pre> <p><u>Android 2.2</u></p> <p><u>SAMSUNG_PRIORART0005353, Power</u></p> <pre> /** * Brightness value to use when battery is low */ public static final int BRIGHTNESS_LOW_BATTERY = 10; </pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Threshold for BRIGHTNESS_LOW_BATTERY (percentage) * Screen will stay dim if battery level is <= LOW_BATTERY_THRESHOLD */ public static final int LOW_BATTERY_THRESHOLD = 10; /** * Turn the screen on or off * * @param on Whether you want the screen on or off */ public static native int setScreenState(boolean on);</pre> <p><u>SAMSUNG PRIORART0005353, BatteryManager</u></p> <pre>/** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer indicating whether the device is plugged in to a power * source; 0 means it is on battery, other constants are different * types of power sources. */ public static final String EXTRA_PLUGGED = "plugged";</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>/** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer containing the current battery voltage level. */ public static final String EXTRA_VOLTAGE = "voltage"; /** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * integer containing the current battery temperature. */ public static final String EXTRA_TEMPERATURE = "temperature"; /** * Extra for {@link android.content.Intent#ACTION_BATTERY_CHANGED}: * String describing the technology of the current battery. */ public static final String EXTRA_TECHNOLOGY = "technology";</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>// values for "status" field in the ACTION_BATTERY_CHANGED Intent public static final int BATTERY_STATUS_UNKNOWN = 1; public static final int BATTERY_STATUS_CHARGING = 2; public static final int BATTERY_STATUS_DISCHARGING = 3; public static final int BATTERY_STATUS_NOT_CHARGING = 4; public static final int BATTERY_STATUS_FULL = 5; // values of the "plugged" field in the ACTION_BATTERY_CHANGED intent. // These must be powers of 2. /** Power source is an AC charger. */ public static final int BATTERY_PLUGGED_AC = 1; /** Power source is a USB port. */ public static final int BATTERY_PLUGGED_USB = 2; <u>SAMSUNG_PRIORART0005353, BatteryStats</u> /**</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<ul style="list-style-type: none">* A class providing access to battery usage statistics, including information on<ul style="list-style-type: none">* wakelocks, processes, packages, and services. All times are represented in microseconds* except where indicated otherwise.* @hide*//**<ul style="list-style-type: none">* A constant indicating a a wifi turn on timer** {@hide}*/public static final int WIFI_TURNED_ON = 4;/**<ul style="list-style-type: none">* A constant indicating an audio turn on timer** {@hide}*/

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int AUDIO_TURNED_ON = 7; /** * A constant indicating a video turn on timer * * {@hide} */ public static final int VIDEO_TURNED_ON = 8; public static final int SIGNAL_STRENGTH_NONE_OR_UNKNOWN = 0; public static final int SIGNAL_STRENGTH_POOR = 1; public static final int SIGNAL_STRENGTH_MODERATE = 2; public static final int SIGNAL_STRENGTH_GOOD = 3; public static final int SIGNAL_STRENGTH_GREAT = 4; static final String[] SIGNAL_STRENGTH_NAMES = { "none", "poor", "moderate", "good", "great" };</pre>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<pre>public static final int DATA_CONNECTION_NONE = 0; public static final int DATA_CONNECTION_GPRS = 1; public static final int DATA_CONNECTION_EDGE = 2; public static final int DATA_CONNECTION_UMTS = 3; public static final int DATA_CONNECTION_OTHER = 4;</pre> <p><u>GOOG-HEADWATER-00000092, Google I/O 2009 - Coding for Life -- Battery Life, That Is (June 2, 2009)</u></p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 2:</p> <h2>Coding for Life--Battery Life, That Is</h2> <p>Jeff Sharkey May 27, 2009</p> <p>Post your questions for this talk on Google Moderator: code.google.com/events/io/questions</p> <p>Google </p> <hr/> <p>GOOG-HEADWATER-000000093</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-000000092 at 3:</p> <h2>Why does this matter?</h2> <ul style="list-style-type: none">● Phones primarily run on battery power, and each device has a "battery budget"<ul style="list-style-type: none">○ When it's gone, it's gone○ Apps need to work together to be good citizens of that shared resource○ Current measured in mA, battery capacity in mAh● HTC Dream: 1150mAh● HTC Magic: 1350mAh● Samsung I7500: 1500mAh● Asus Eee PC: 5800mAh <div></div> <p>GOOG-HEADWATER-000000094</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p data-bbox="554 318 1094 345">See, e.g., GOOG-HEADWATER-00000092 at 4:</p> <div data-bbox="554 345 1797 1304"> <h3 data-bbox="663 418 1121 467">Where does it all go?</h3>  <p data-bbox="900 591 1297 659">Source: Values measured using an industrial power monitor at 5kHz sampling rate, and taking average power with lowest standard deviation.</p> <p data-bbox="947 699 1199 781"> Baseline usage Specific item </p> <p data-bbox="663 854 695 902" style="transform: rotate(-90deg);">mA</p> <p data-bbox="785 1024 1640 1198" style="text-align: center;"> Airplane 3G idle EDGE idle WiFi idle LCD normal CPU 50% CPU full Game sensors GPS radio 3G full EDGE full WiFi full </p> <p data-bbox="1591 1182 1772 1230" style="text-align: right;">Google 09 O</p> <p data-bbox="1549 1284 1780 1300" style="text-align: right;">GOOG-HEADWATER-00000095</p> </div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
	<p data-bbox="556 316 1094 345"><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 9:</p> <h2 data-bbox="585 370 1115 418">How can we do better?</h2> <h3 data-bbox="585 430 774 472">Networking</h3> <ul data-bbox="573 509 1482 552" style="list-style-type: none">● Check network connection, wait for 3G or WiFi <pre data-bbox="585 662 1644 987">ConnectivityManager mConnectivity; TelephonyManager mTelephony; // Skip if no connection, or background data disabled NetworkInfo info = mConnectivity.getActiveNetworkInfo(); if (info == null !mConnectivity.getBackgroundDataSetting()) { return false; }</pre>  <div data-bbox="1577 1177 1772 1235"> 09 </div> <div data-bbox="1528 1295 1780 1315">GOOG-HEADWATER-00000100</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>See, e.g., GOOG-HEADWATER-00000092 at 11:</p> <p>How can we do better? Networking</p> <ul style="list-style-type: none">● Check network connection, wait for 3G or WiFi <pre>// Only update if WiFi or 3G is connected and not roaming int netType = info.getType(); int netSubtype = info.getSubtype(); if (netType == ConnectivityManager.TYPE_WIFI) { return info.isConnected(); } else if (netType == ConnectivityManager.TYPE_MOBILE && netSubtype == TelephonyManager.NETWORK_TYPE_UMTS && !mTelephony.isNetworkRoaming()) { return info.isConnected(); } else { return false; }</pre> <p>Google 09 O</p> <p>GOOG-HEADWATER-00000101</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 16:</p> <h2>How can we do better?</h2> <p>Foreground apps</p> <ul style="list-style-type: none">● Wakelocks are costly if forgotten<ul style="list-style-type: none">○ Pick the lowest level possible, and use specific timeouts to work around unforeseen bugs○ Consider using <code>android:keepScreenOn</code> to ensure correctness <pre><LinearLayout android:orientation="vertical" android:layout_width="fill_parent" android:layout_height="fill_parent" android:keepScreenOn="true"></pre> <div></div> <div></div> <p>GOOG-HEADWATER-00000107</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<i>See, e.g.</i> , GOOG-HEADWATER-000000092 at 18:

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p>How can we do better? Foreground apps</p> <ul style="list-style-type: none">● Use coarse network location, it's much cheaper<ul style="list-style-type: none">○ GPS: 25 seconds * 140mA = 1mAh○ Network: 2 seconds * 180mA = 0.1mAh● 1.5 uses AGPS when network available● GPS time-to-fix varies wildly based on environment, and desired accuracy, and might outright fail<ul style="list-style-type: none">○ Just like wake-locks, location updates can continue after onPause(), so make sure to unregister○ If all apps unregister correctly, user can leave GPS enabled in Settings <p></p> <p>Google </p> <p>GOOG-HEADWATER-00000109</p> <p>See, e.g., GOOG-HEADWATER-00000092 at 20:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433



'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Foreground apps</p> <ul style="list-style-type: none">● Accelerometer/magnetic sensors<ul style="list-style-type: none">○ Normal: 10mA (used for orientation detection)○ UI: 15mA (about 1 per second)○ Game: 80mA○ Fastest: 90mA● Same cost for accelerometer, magnetic, orientation sensors on HTC Dream <div>  GOOG-HEADWATER-00000111</div> <p>See, e.g., GOOG-HEADWATER-00000092 at 22:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
	<p>How can we do better? Background apps</p> <ul style="list-style-type: none">● Services should be short-lived; these aren't daemons<ul style="list-style-type: none">○ Each process costs 2MB and risks being killed/restarted as foreground apps need memory○ Otherwise, keep memory usage low so you're not the first target● Trigger wake-up through AlarmManager or with <receiver> manifest elements<ul style="list-style-type: none">○ stopSelf() when finished <div> </div> <div></div> <p>GOOG-HEADWATER-00000113</p> <p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 26:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<p>How can we do better?</p> <p>Background apps</p> <ul style="list-style-type: none">●Dynamically enabling/disabling <receiver> components in manifest, especially when no-ops <pre><receiver android:name=".ConnectivityReceiver" android:enabled="false"> ... </receiver></pre> <pre>ComponentName receiver = new ComponentName(context, ConnectivityReceiver.class); PackageManager pm = context.getPackageManager(); pm.setComponentEnabledSetting(receiver, PackageManager.COMPONENT_ENABLED_STATE_ENABLED, PackageManager.DONT_KILL_APP);</pre> <div>Google 09 O</div> <div>GOOG-HEADWATER-00000117</div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433


'433 Claims	Android Device with One or More Apps
	<p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 27:</p> <h2>How can we do better?</h2> <h3>Background apps</h3> <ul style="list-style-type: none"> • Checking current battery and network state before running a full update <pre> public void onCreate() { // Register for sticky broadcast and send default registerReceiver(mReceiver, mFilter); mHandler.sendMessageDelayed(MSG_BATT, 1000); } IntentFilter mFilter = new IntentFilter(Intent.ACTION_BATTERY_CHANGED); BroadcastReceiver mReceiver = new BroadcastReceiver() { public void onReceive(Context context, Intent intent) { // Found sticky broadcast, so trigger update unregisterReceiver(mReceiver); mHandler.removeMessages(MSG_BATT); mHandler.obtainMessage(MSG_BATT, intent).sendToTarget(); } }; </pre>  <p><i>See, e.g.,</i> GOOG-HEADWATER-00000092 at 29:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433




'433 Claims	Android Device with One or More Apps
	<p data-bbox="575 321 1100 375">Users will be watching!</p> <div data-bbox="552 440 947 1029">  </div> <ul data-bbox="995 461 1680 1133" style="list-style-type: none"> ● SpareParts has "Battery history" <ul style="list-style-type: none"> ○ 1.5 is already keeping stats on which apps are using CPU, network, wakelocks ○ Simplified version coming in future, and users will uninstall apps that abuse battery ● Consider giving users options for battery usage, like update intervals, and check the "no background data" flag <div data-bbox="1654 423 1730 521">  </div> <div data-bbox="1556 1127 1759 1187">  </div> <p data-bbox="1514 1247 1766 1263">GOOG-HEADWATER-00000120</p> <p data-bbox="554 1295 1108 1321">See, e.g., GOOG-HEADWATER-00000092 at 30:</p>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
	<div><h2>Takeaways</h2><ul style="list-style-type: none">● Use an efficient parser and GZIP to make best use of network and CPU resources● Services that sleep or poll are bad, use <receiver> and AlarmManager instead<ul style="list-style-type: none">○ Disable manifest elements when no-op○ Wake up along with everyone else (inexact alarms)● Wait for better network/battery for bulk transfers● Give users choices about background behavior<div><div>Google 09 O</div><div>GOOG-HEADWATER-00000121</div></div></div>

Exhibit G-10 to Defendants' Amended Invalidity Contentions
U.S. Patent No. 9,277,433

'433 Claims	Android Device with One or More Apps
<p>[19] The wireless end-user device of claim 18, wherein when the power state of the modem is idle or sleeping, the one or more Internet activity access controls prevent power state changes to the modem until a data communication request is received from a second end-user application for which the one or more Internet activity access controls do not apply.</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c], [18].</p>
<p>[20] The wireless end-user device of claim 1, wherein when the one or more Internet activity access controls are to be applied, the one or more processors are configured to instruct the first end-user application to transition to a different state.</p>	<p>Android Device with One or More Apps discloses and/or renders obvious this limitation. For example, see the following passages and/or figures, as well as related disclosures:</p> <p><i>See, e.g.,</i> the disclosures identified for claims [1 pre]-[1c].</p>